



SATA III 6Gb/s SSD370S

Transcend's SATA III 6Gb/s SSD370S boasts incredibly fast transfer speeds, MLC NAND flash memory, a compact and lightweight design, and shock and vibration resistance. With this solid state drive, you will enjoy a seamless, lag-free computing experience.



MLC NAND flash inside

Transcend's SSD370S is manufactured with reliable, top-tier MLC NAND flash memory to ensure superior stability and endurance, making it well-suited to high-end applications.



Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface, DDR3 DRAM cache and a powerful controller, Transcend's SSD370S delivers blazing-fast read and write speeds of up to 530MB/s and 460MB/s.



Guaranteed endurance and reliability

Transcend's SSD370S offers great Terabytes Written (TBW) values (up to 2,940 TB) indicating the total amount of data you can write into the drive over its lifetime. It also features Error Correcting Code (ECC), Garbage Collection, Wear-leveling, and DevSleep.





2.5" Solid State Drive

SATA III 6Gb/s SSD370S

Features

- · Up to 530 MB/s read; 460 MB/s write
- MLC NAND flash memory and DDR3 DRAM cache
- Engineered with ECC (Error Correcting Code) to ensure data integrity
- Supports DevSleep ultra low power state,
 S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website

Transcend

SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specification

A	р	р	е	а	r	а	r	1	C	е
---	---	---	---	---	---	---	---	---	---	---

Dimensions (Max.) 100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")

Weight (Max.) 57 g (2.01 oz)

Storage

Flash Type MLC NAND flash

Capacity 32 GB / 64 GB / 128 GB / 256 GB / 512 GB / 1 TB

Operating Environment

Operating Temperature $0^{\circ}\text{C}(32^{\circ}\text{F}) \sim 70^{\circ}\text{C}(158^{\circ}\text{F})$ Operating Voltage $5\text{V}\pm5\%$

Performance

Sequential Read/Write Read: 530 MB/s (CrystalDiskMark, max.) Write: 460 MB/s 4K Random Read/Write Read: 75,000 IOPS (IOmeter, max.) Write: 75,000 IOPS Mean Time Between Failures 2,000,000 hour(s) (MTBF) Terabytes Written (Max.) 2,940 TB Drive Writes Per Day 2.5 (3 yrs) (DWPD) Speed may vary due to host hardware, software, usage, Note and storage capacity.

Warranty

Certificate	CE/FCC/BSMI/KC/RCM
Warranty	Three-year Limited Warranty

Ordering Information

ordering information		
32GB	TS32GSSD370S	
64GB	TS64GSSD370S	
128GB	TS128GSSD370S	
256GB	TS256GSSD370S	
512GB	TS512GSSD370S	
1TB	TS1TSSD370S	

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



2.5" SSD Comparison









	SSD220Q Salled State Center	SSD230S Select States Dates	SSD2205 Solid State Dicks	SSD3705 Solid State Drive		
	SATA III 6Gb/s SSD220Q	SATA III 6Gb/s SSD230S	SATA III 6Gb/s SSD220S	SATA III 6Gb/s SSD370S		
Appearance						
Dimensions		100 mm x 69.85 mm x	6.8 mm (3.94" x 2.75" x 0.2	28")		
Weight	45 g (1.59 oz)	53 g (1.87 oz)	45 g (1.59 oz)	57 g (2.01 oz)		
Storage						
Flash Type	QLC NAND flash	3D NAND flash	3D NAND flash	MLC NAND flash		
Capacity	500GB / 1TB	128GB ~ 2TB	120GB ~ 960GB	32GB ~ 1TB		
Operating Environment						
Operating Temperature		0°C (32°F)	0°C (32°F) ~ 70°C (158°F)			
Performance						
Sequential Read/Write (CrystalDiskMark)	550 MB/s 500 MB/s	560 MB/s 520 MB/s	550 MB/s 500 MB/s	530 MB/s 460 MB/s		
4K Random Read/Write (lOmeter)	57,000 IOPS 59,000 IOPS	85,000 IOPS 89,000 IOPS	65,000 IOPS 75,000 IOPS	75,000 IOPS 75,000 IOPS		
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)		
Terabytes Written (TBW)	200 TB	1,120 TB	320 TB	2,940 TB		
Drive Writes Per Day (DWPD)	0.19 (3 yrs)	0.3 (5 yrs)	0.3 (3 yrs)	2.5 (3 yrs)		
Warranty						
Warranty	Three-year Limited Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty		
Technology	,	,	,	,		
Technology TRIM & NCQ Command	✓ ./	V	∀	V		
Technology TRIM & NCQ Command S.M.A.R.T.	✓	~	✓	~		
Technology TRIM & NCQ Command S.M.A.R.T. DDR3 DRAM Cache	-	✓ ✓	-	✓ ✓		
Technology TRIM & NCQ Command S.M.A.R.T. DDR3 DRAM Cache Advanced Garbage Collection	- - -		✓	~		
Technology TRIM & NCQ Command S.M.A.R.T. DDR3 DRAM Cache	-	✓ ✓	- -	✓ ✓ ✓		

^{*}Speed may vary due to host hardware, software, usage, and storage capacity.