

# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Pre-assembled relay module with screw connection, consisting of: relay base, power contact relay, plug-in display/interference suppression module, and retaining bracket. Contact type: 1 N/O contact, max. inrush current up to 130 A peak, 80 A (20 ms), 24 V DC input voltage

## Key commercial data

package_quantity	10
GTIN	4055626405223

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Width	16 mm
Height	93 mm
Depth	75 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Coil side

Nominal input voltage $U_N$	24 V DC
Input voltage range in reference to $U_N$	see diagram
Typical input current at $U_N$	18 mA
Typical response time	8 ms
Typical release time	10 ms
Protective circuit	Reverse polarity protection Polarity protection diode
Protective circuit	Free-wheeling diode Damping diode
Operating voltage display	Yellow LED
Power dissipation for nominal condition	0.43 W

### Contact side

Contact type	1 N/O contact
Type of switch contact	Single contact
Contact material	AgSnO

# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

## Technical data

### Contact side

<b>Maximum switching voltage</b>	250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
<b>Minimum switching voltage</b>	12 V AC/DC (at 100 mA)
<b>Min. switching current</b>	100 mA (at 12 V DC)
<b>Maximum inrush current</b>	80 A (for 20 ms)
<b>Maximum inrush current</b>	130 A (peak, at capacitive load, 230 V AC, 24 µF)
<b>Limiting continuous current</b>	6 A
<b>Limiting continuous current</b>	10 A (Value is permissible if connections 11 and 21, as well as connections 14 and 24 are bridged.)
<b>Interrupting rating (ohmic load) max.</b>	144 W (at 24 V DC)
<b>Interrupting rating (ohmic load) max.</b>	58 W (at 48 V DC)
<b>Interrupting rating (ohmic load) max.</b>	48 W (at 60 V DC)
<b>Interrupting rating (ohmic load) max.</b>	50 W (at 110 V DC)
<b>Interrupting rating (ohmic load) max.</b>	80 W (at 220 V DC)
<b>Interrupting rating (ohmic load) max.</b>	85 W (for 250 V DC)
<b>Interrupting rating (ohmic load) max.</b>	1500 VA (for 250 V AC)
<b>Interrupting rating (ohmic load) max. bridged</b>	240 W (for 24 V DC. The value is permissible if both connections 13, both connections 14 and both connections BB are bridged.)
<b>Interrupting rating (ohmic load) max. bridged</b>	2500 VA (for 250 V AC. The value is permissible if both connections 13, both connections 14 and both connections BB are bridged.)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	2 A (at 24 V, DC13)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	0.2 A (at 110 V, DC13)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	0.2 A (at 250 V, DC13)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	6 A (at 24 V, AC15)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	6 A (at 120 V, AC15)
<b>Switching capacity in acc. with DIN VDE 0660/IEC 60947</b>	6 A (at 250 V, AC15)

### Connection data input side

<b>Connection name</b>	Coil side
<b>Connection method</b>	Push-in connection
<b>Stripping length</b>	8 mm
<b>Conductor cross section solid</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
<b>Conductor cross section flexible</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with or without ferrule)
<b>Conductor cross section flexible (2 conductors with same cross section)</b>	0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve)
<b>Conductor cross section flexible (2 conductors with same cross section)</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrules without plastic sleeve)
<b>Conductor cross section AWG</b>	26 ... 16

### Connection data output side

<b>Connection name</b>	Contact side
<b>Connection method</b>	Push-in connection

# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

## Technical data

### Connection data output side

<b>Stripping length</b>	8 mm
<b>Conductor cross section solid</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
<b>Conductor cross section flexible</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with or without ferrule)
<b>Conductor cross section flexible (2 conductors with same cross section)</b>	0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve)
<b>Conductor cross section flexible (2 conductors with same cross section)</b>	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrules without plastic sleeve)
<b>Conductor cross section AWG</b>	26 ... 16

### General

<b>Type of note</b>	Notes on operation
<b>Note</b>	FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)
<b>Test voltage relay winding/relay contact</b>	4 kV AC (50 Hz, 1 min.)
<b>Operating mode</b>	100% operating factor
<b>Degree of protection</b>	IP20 (Relay socket)
<b>Degree of protection</b>	RT III (Relay)
<b>Mechanical service life</b>	3 x 10 <sup>7</sup> cycles
<b>Flammability rating according to UL 94</b>	V0
<b>Mounting position</b>	any
<b>Assembly instructions</b>	In rows with zero spacing

### Standards and Regulations

<b>Designation</b>	Standards/regulations
<b>Standards/regulations</b>	IEC 60664
<b>Standards/regulations</b>	EN 50178
<b>Rated surge voltage</b>	6 kV
<b>Insulation</b>	Safe isolation, reinforced insulation
<b>Degree of pollution</b>	2
<b>Overvoltage category</b>	III
<b>Flammability rating according to UL 94</b>	V0

## Classifications

### eCl@ss

<b>eCl@ss 5.0</b>	27371601
<b>eCl@ss 5.1</b>	27371601
<b>eCl@ss 6.0</b>	27371601
<b>eCl@ss 7.0</b>	27371601
<b>eCl@ss 8.0</b>	27371601
<b>eCl@ss 9.0</b>	27371601

### ETIM

<b>ETIM 2.0</b>	EC001437
-----------------	----------

# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

## Classifications

### ETIM

ETIM 3.0	EC001437
ETIM 4.0	EC001437
ETIM 5.0	EC001437
ETIM 6.0	EC001437

## Accessories

### Jumper

FBS 2-6 - 3030336



FBS 2-6 BU - 3036932



FBS 2-6 GY - 3032237



FBS 2-8 - 3030284



## Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

### Accessories

FBS 2-8 BU - 3032567



FBS 2-8 GY 7042 - 3032541



### End block

CLIPFIX 35 - 3022218



### Test plug terminal block

MPS-MT - 0201744



### Insulating sleeve

MPS-IH WH - 0201663



# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

## Accessories

MPS-IH RD - 0201676



MPS-IH BU - 0201689



MPS-IH YE - 0201692



MPS-IH GN - 0201702



MPS-IH GY - 0201728



MPS-IH BK - 0201731



# Relay Module - RIF-1-RSC-LDP-24DC/1IC - 2909885

## Accessories

---

### Terminal marking

ZB 5 :UNBEDRUCKT - 1050004



ZB 15:UNBEDRUCKT - 0811972




### Marker carriers

STP 5-2 - 0800967



## Drawings

Circuit diagram



Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>