

AC charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



The EV-CC-AC1-M3-CBC-SER-HS charging controller with housing for DIN rail mounting is used for charging electric vehicles at 3-phase AC networks according to IEC 61851-1, Mode 3. All charging functions, comprehensive configuration settings as well as a locking controller are already integrated.



Key commercial data

package_quantity	1
GTIN	4055626039756

Technical data

Product definition

Product type	AC charging controller for private and commercial applications (EU/CN)
Type	in housing
Locking release in the event of mains failure	Integrated release function of the locking actuator for disconnection of Infrastructure Plug and Infrastructure Socket Outlet
Standards/regulations	IEC 61851-1
Standards/regulations	GB/T 18487.1-2015
Standards/regulations	SAE J1772
Charging mode	Mode 3, Case B + C
Type of charging current	AC
Conformance	CE-compliant

Dimensions

Height	128 mm
Width	124 mm
Depth	64.00 mm

Ambient conditions

Ambient temperature (operation)	-35 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	30 % ... 95 %
Degree of protection	IP20

Inputs

AC charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Technical data

Inputs

Number of digital inputs	5
Frequency range	50 Hz ... 60 Hz
Nominal power consumption	< 0.5 W (No-load)
Nominal current I_N	≤ 1 mA
Nominal input voltage U_N	12 V
Input voltage range U1	0 V ... 3 V (Off)
Input voltage range U2	9 V ... 15 V (On)

Switching outputs

Control of charging contactor	Relay output $C_{1,2}$
Minimum switching capacity	1500 VA
Maximum switching voltage	250 V AC (External supply)
Max. switching current	6 A
Control of locking actuator	Relay output LO+/-
Minimum switching capacity	24 VA
Maximum switching voltage	12 V (Internal supply)
Max. switching current	2 A

Digital outputs

Control of additional functions	4 digital outputs
Connection technology	Screw connection
Maximum output voltage	30 V
Maximum output current	0.5 A (Total current for all outputs; internally supplied)
Maximum output current	0.6 A (Per output; externally supplied)

Data interfaces

RS-485 interface	RS-485 2-wire
Bus system	RS-485
Number of interfaces	1
Connection method	Screw connection
Transmission speed	9.6 kbps (Standard)
Transmission speed range	9.6 kbps ... 19.2 kbps (adjustable)
Data flow control/protocols	Modbus/RTU (slave)

Connection data

Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Connection method	Screw connection

Device supply

AC charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Technical data

Device supply

Supply voltage	230 V
Supply voltage range	100 V AC ... 240 V AC (nominal voltage range)
Max. current consumption	40 mA
Nominal power consumption	< 1 W (No-load)
Frequency range	50 Hz ... 60 Hz

Classifications

eCl@ss

eCl@ss 4.0	27210902
eCl@ss 4.1	27371105
eCl@ss 5.0	27371801
eCl@ss 5.1	27371810
eCl@ss 6.0	27371810
eCl@ss 7.0	27371810
eCl@ss 8.0	27242207
eCl@ss 9.0	27144703

ETIM

ETIM 3.0	EC001505
ETIM 4.0	EC001599
ETIM 5.0	EC001413
ETIM 6.0	EC002889

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121535
UNSPSC 11	39121535
UNSPSC 12.01	39121535
UNSPSC 13.2	39121801

Accessories

Evaluation unit

EV-RCM-C1-AC30-DC6 - 1622450



AC charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Accessories

EV-RCM-C2-AC30-DC6 - 1622451



Infrastructure socket outlet

EV-T2M3SE12-3AC32A-0,7M6,0E10 - 1405214



AC charging cable

EV-T2G3C-3AC32A-5,0M6,0ESBK01 - 1627355



Parameterization memory

SD-FLASH-2GB-EV-EMOB - 1624092



License

USB-DONGLE-EV-EMOB - 1627632



AC charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Accessories

Drawings

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>