

Holder - EV-T1AC-PARK - 1624139

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Retainer for Vehicle Connector as parking position at charging stations (EVSE), Type 1, SAE J1772

Article description

Retainer for Vehicle Connector as parking position at charging stations for E-Mobility (EVSE)

Your advantages

Production in accordance with ISO TS 16949

Material data available in the IMDS (International Material Data System of the automotive industry)

Key commercial data

| package_quantity | 1 |
|------------------|---------------|
| GTIN | 4055626241555 |

Technical data

Product definition

| Product type | Retainer for Vehicle Connector as parking position at charging stations (EVSE) |
|--------------------------|--|
| Standards/regulations | SAE J1772 |
| Charging standard | Туре 1 |
| Charging mode | Mode 3 |
| Type of charging current | AC |

Dimensions

| Height | 75 mm |
|-----------------|---------------|
| Width | 75 mm |
| Depth | 37.5 mm |
| Bore dimensions | 60 mm x 60 mm |

Ambient conditions

| Ambient temperature (operation) | -30 °C 50 °C |
|---|--------------|
| Ambient temperature (storage/transport) | -40 °C 80 °C |
| Degree of protection | IP54 |

Mechanical properties

| Vehicle Connector fixing | With actuation lever |
|----------------------------------|-----------------------------|
| Removal of the Vehicle Connector | Lever actuation and removal |



Holder - EV-T1AC-PARK - 1624139

Technical data

Mechanical properties

| On request | | |
|--|--|--|
| Mounting | | |
| Front mounting | | |
| Only 0 to 45 degree frontal inclination possible, see figure | | |
| 6.00 mm (ø) | | |
| Design | | |
| black | | |
| On request | | |
| Material | | |
| Plastic | | |
| Environmental Product Compliance | | |
| Environmentally friendly use period: unlimited = EFUP-e | | |
| No hazardous substances above threshold values | | |
| | | |

Classifications

eCl@ss

| eCl@ss 4.0 | 272607xx |
|------------|----------|
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27059110 |
| eCl@ss 6.0 | 27279220 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27449001 |
| eCl@ss 9.0 | 27144792 |

ETIM

| ETIM 2.0 | EC000241 |
|----------|----------|
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC002061 |
| ETIM 5.0 | EC002839 |
| ETIM 6.0 | EC002839 |

UNSPSC


| UNSPSC 6.01 | 30211923 |
|---------------|----------|
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Drawings



Holder - EV-T1AC-PARK - 1624139

Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com