

# Electronic housing - UCS 237-195-F-GD 7035 - 2203341

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Complete housing for PCBs, can be positioned flexibly; includes housing half shells, side panels closed, adhesive domes for PCB attachment, screws for housing and PCB attachment; light gray housing with turquoise-green corner inlays

## Your advantages

- High degree of application flexibility, thanks to the modular housing design
- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Reduced logistics outlay, thanks to components which are compatible with one another

## Key commercial data

<b>package_quantity</b>	1
<b>GTIN</b>	4055626404523

## Technical data

### General

<b>Housing type</b>	Complete housing
<b>Housing material</b>	PC
<b>Color (RAL)</b>	gray (7035)

### Ambient conditions

<b>Ambient temperature (storage/transport)</b>	-40 °C ... 70 °C
<b>Ambient temperature (assembly)</b>	-5 °C ... 100 °C
<b>Ambient temperature (operation)</b>	-40 °C ... 100 °C (depending on power dissipation)

### Dimensions

<b>Width</b>	237 mm
<b>Height</b>	195 mm
<b>Depth</b>	47 mm

### Technical data

<b>Flammability rating according to UL 94</b>	V0
---	----

### Standards and Regulations

<b>Flammability rating according to UL 94</b>	V0
---	----

## Electronic housing - UCS 237-195-F-GD 7035 - 2203341

### Classifications

#### eCl@ss

<b>eCl@ss 5.1</b>	27180506
<b>eCl@ss 8.0</b>	27182702
<b>eCl@ss 9.0</b>	27182702

#### ETIM

<b>ETIM 5.0</b>	EC001031
-----------------	----------

### Drawings

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>