

Electronic housing - UCS 237-195-H-GD 7035 - 2203344

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Complete housing for PCBs, can be positioned flexibly; includes housing half shells, side panels closed, adhesive domes for PCB attachment, screws for housing and PCB attachment; light gray housing with turquoise-green corner inlays

Your advantages

- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Geduced logistics outlay, thanks to components which are compatible with one another

Key commercial data

package_quantity	1
GTIN	4055626404547

Technical data

General

Housing type	Complete housing
Housing material	PC
Color (RAL)	gray (7035)

Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C 100 °C (depending on power dissipation)

Dimensions

Width	237 mm	
Height	195 mm	
Depth	67 mm	
Technical data		
Flammability rating according to UL 94	VO	

Standards and Regulations	
Flammability rating according to UL 94	V0



Electronic housing - UCS 237-195-H-GD 7035 - 2203344

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

	ETIM 5.0	EC001031
--	----------	----------

Drawings

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com