

Electronic housing - UCS 195-145-F-CCD 9005 - 2203441

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Complete housing for PCBs, fixed to the corner inlays, includes housing half shells, side panels closed, corner inlays with PCB attachment, screws for housing and PCB attachment, black housing with turquoise-green corner inlays

Your advantages

- High degree of application flexibility, thanks to the modular housing design
- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Reduced logistics outlay, thanks to components which are compatible with one another

Key commercial data

package_quantity	1
GTIN	4055626402598

Technical data

General

Housing type	Complete housing
Housing material	PC
Color (RAL)	black (9005)

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 100 °C (depending on power dissipation)

Dimensions

Width	195 mm
Height	145 mm
Depth	47 mm

Technical data

Flammability rating according to UL 94	V0
---	----

Standards and Regulations

Flammability rating according to UL 94	V0
---	----

Electronic housing - UCS 195-145-F-CCD 9005 - 2203441

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
-----------------	----------

Drawings

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>