

Page 1 / 5

#### 1. IDENTIFICATION

Lithium-Manganese-Dioxide-Batteries Sizes: All cells ≤ 1 g Lithium content

All batteries ≤ 2 g Lithium content

Anabasis Handelsgesellschaft mbH Zwinkelweg 2, 89561 Dischingen/Germany

Phone +49 7327 / 92086 Fax +49 7327 / 922049

#### 2. HAZARDS IDENTIFICATION

**Note:** The batteries described in this Safety Data Sheet are sealed and are not harmful, as

long as they are used in compliance with the manufacturer instructions. The content of the battery housing does not create a hazard, as long as the integrity of the battery housing is not affected by abuse (mechanicel, thermal, electrical). Fire,

explosion and severe, burn hazard in such abuse conditions may occur.

**Warning:** Do not charge, short circuit, puncture, deform, disassemble, heat above

85 °C, incinerate or expose contents to water. Keep batteries away from small children. International Standard IEC 60086-4 contains more detailed

information on safety of lithium batteries.

GHS Classification: N/A

### 3. COMPOSITION / INFORMATION on INGREDIENTS

| Substance                          | Approximate percent of total weight |
|------------------------------------|-------------------------------------|
| Lithium Metal                      | 1 - 5                               |
| Lithium-Trifluoromethane-Sulfonate | < 1.5                               |
| Lithium perchlorate                | < 1.6                               |
| Manganese Dioxide                  | 13 - 75                             |
| Dimethoxyether                     | 1 - 10                              |
| Graphite                           | 1 - 5                               |
| Stainless Steel                    | 33 - 75                             |
| Teflon                             | 1 - 5                               |
| Propylene Carbonate                | 2 - 9                               |
| Plastic                            | < 20                                |
| Dioxolane                          | 1 - 9                               |

Date of issue: 2019-04-05



Page 2 / 5

Lithium Hexafluoroarsenate 1 - 4

 Mercury (Hg)
 < 0.0005</td>

 Lead (Pb)
 < 0.004</td>

 Cadmium (Cd)
 < 0.002</td>

SVHC substances according to REACH (Article 33)

Contents EC No. CAS No. Material

> 0,1% 203-794-9 110-71-4 1,2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME)

#### 4. FIRST AID MEASURES

### **Contact to internal Battery content:**

**Skin:** Immediately flush with plenty of water for at least 15 minutes.

If symptoms are present after flushing, get medical attention.

**Eyes:** Immediately flush with plenty of water for at least 15 minutes

and get medical attention.

▶ Respiratory Leave area immediately. With large quantities and irritation

**system:** of the respiratory tract get medical attention.

▶ **Ingestion:** Rinse mouth and sorrounding area with water.

Seek for immediate medical attention.

## 5. FIRE – FIGHTING MEASURES

### A. Extinguishing Media:

► Copious amounts of water is an effective extinguishing medium for lithium batteries, as long as batteries are not yet venting or exploding.



Page 3 / 5

- Lith-X (Class D extinguishing media) is effective on fires involving only a few lithium batteries.
- ▶ Dry chemical type extinguishers have only limited extinguishing potential.

### B. Fire Fighting Procedures:

- ▶ Use a positive pressure self-contained breathing apparatus if batteries are involved in a fire.
- Full protective clothing is necessary.
- During water application caution is advised as burning pieces of lithium may be ejected from the fire.

#### 6. ACCIDENTAL RELEASE MEASURES

When the battery housing is damaged, small amounts of electrolyte may leak. Seal battery air tight in a plastic bag, adding some dry sand, chalk (CaCO<sub>3</sub>) or lime (CaO) powder or Vermiculite. Electrolyte traces may be wiped off dryly using household paper. Rinse with water afterwards.

### 7. HANDLING AND STORAGE

- Do not allow terminals to short-circuit.
  - Storage preferably in a cool (below 30 °C), dry area that is subject to little temperature change.
  - Do not place near heating equipment, nor expose to direct sunlight for long periods. Elevated temperatures can result in reduced battery service life.

Date of issue: 2019-04-05



Page 4 / 5

| 8.     | EXPOSURE C                                    | ONTROLS / PERSONAL PROTECTION   |
|--------|---|---|
| Hand   | ratory eqipment:<br>protection:<br>rotection: | None required under normal use conditions.  None required under normal use conditions. Use butyl gloves when handling leaking batteries.  None required under normal use conditions. Wear safety glasses when handling leaking batteries. |
| 9.     | PHYSICAL AN                                   | ID CHEMICAL PROPERTIES  |
| Geom   | etric solid objects                           | S.  |
| 10.    | STABILITY AN                                  | ND REACTIVITY   |
|        | May rupture vio                               | plently when heated above 100 °C or when charged.   |
| 11.    | TOXIOLOGICA                                   | AL INFORMATION  |
| Not ap | pplicable.                                    |   |
| 12.    | ECOLOGICAL  Not applicable.                   | . INFORMATION   |
| 13.    | DISPOSAL CO                                   | DNSIDERATIONS   |
|        | In accordance                                 | with appropriate national regulations.  |
| 14.    | TRANSPORT                                     | INFORMATION   |
|        | Lithium-Metal                                 | Batteries (UN 3090)   |

That we supply to our customers are subject to the regulations on dangerous goods.



Page 5 / 5

Transport may be facilitated by observing the following special provisions.

**Air transport:** IATA Dangerous Goods Regulations 58th Edition Packing instruction 968 Section II

UN 3090 = FORBIDDEN with PAX (Passenger- and Cargo Aircraft) ONLY: CAO

**Sea transport:** IMDG Code 37. Amendment Special provision 188/230, packing instruction 903

Road and rail transport: ADR/RID 2017 special provision 188/230, packing instruction 903

The requirements of the UN manual of Test and Criteria, Part III, sub-section 38.3 are fulfilled

All of these batteries are packed and marked within appropriate protection for prevention of short circuits.

### Lithium-Metal Batteries contained in equipment (UN 3091)

That we supply to our customers are subject to the regulations on dangerous goods. Transport may be facilitated by observing the following special provisions.

**Air transport:** IATA Dangerous Goods Regulations 58th Edition Packing instruction 970 Section II

**Sea transport:** IMDG Code 37. Amendment Special provision 188/230, packing instruction 903

Road and rail transport: ADR/RID 2017 special provision 188/230, packing instruction 903

The requirements of the UN manual of Test and Criteria, Part III, sub-section 38.3 are fulfilled.

All of these batteries are packed and marked within appropriate protection for prevention of short circuits.

### Lithium-Metal Batteries contained with equipment (UN 3091)


That we supply to our customers are subject to the regulations on dangerous goods. Transport may be facilitated by observing the following special provisions.

Air transport: IATA Dangerous Goods Regulations 58th Edition Packing instruction 969 Section II

**Sea transport:** IMDG Code 37. Amendment Special provision 188/230, packing instruction 903

**Road and rail transport**: ADR/RID 2017 special provision 188/230, packing instruction 903 The requirements of the UN manual of Test and Criteria, Part III, sub-section 38.3 are fulfilled.

All of these batteries are packed and marked within appropriate protection for prevention of short circuits.





Page 6 / 5

| 15. | REGULATORY INFORMATION |  |  |
|-----|------------------------|--|--|
|     | Not applicable.        |  |  |
|     |                        |  |  |
| 16. | OTHER INFORMATION      |  |  |

For lithium batteries in general, Safety standard IEC 60086-4 applies. It contains detailed recommendations for manufactures of equipment and users.

Date of issue: 2019-04-05