


MSDS Report

Prepared For :		
Product Name:	Power Bank	
Model:	T200AC	(c)
Nominal Voltage:	Input: DC 5V Output: DC 5V	
Typical Capacity:	20000mAh, 74Wh	
Weight:	392.3g	
Dimension :	136.0mm×70.7mm×29.6mm (L×W×T)	
Prepared By:	Shenzhen TCT Testing Technology Co., Ltd. 1F, No.1 Building, No.1 Chongqing Road, Yibaolai Industrial Park,Qiaotou Village, Fuyong Town, Baoan District, Shenzhen	
Report No.:	TCT170418M009	(C)

Written by: _____ Approved by:____

Inspected by:



Report No.: TCT170418M009

Page 1

This report shall not be reproduced except in full, without the written approval of Shenzhen TCT Testing Technology Co., Ltd.





Section 1- Chemical Product & Company Identification

Product Name	: Power Bank		(c ¹)		(C ¹)	
Manufacture:						
Address:						
Contact Person	n:					
Fax: Emergency Te	l: +86-755-3699999					
E-mail:		i				
Item Code: TC	T170418M009					
Section 2- H	lazards Ident	ification				
Classification of Danger	See section 14		(6)			
Primary Route(s) of Exposure	Eye, skin contact, ing	estion		(c ⁴)		(
Health Hazard	The batteries are r manufacturer under r heat, leakage of inter but not limited to the fire, whacked with ha	normal condition nal components following cases	s. In case of a , with could ca :: charged for	abuse, there's use casualty lo long time, sho	risk of rupture oss. Abuses ir rt circuited, pu	e, fire, iclude ut into
Reported as carcinogen	Not applicable					

Report No.: TCT170418M009 Page 2 of 8 Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Section 3- Composition/Information on Ingredients

Li-ion Battery (Contained In Power Bank) is a mixture

Hazardous Ingredients (Chemical Name)	Concentration or concentration ranges (%)	CAS Number
Lithium Cobalt Oxide (CoLiO ₂)	15-40	12190-79-3
Graphite	10-30	7782-42-5
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3
Copper	7-13	7440-50-8
Aluminum foil	5-10	7429-90-5
Nickel	1-5	7440-02-0

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures

Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5- Fire Fighting Measures

Characteristics of Hazard	Toxic fumes; gases or vapors may evolve on burning.	
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.	
Fire-extinguishing Methods and Extinguishing Media	Water, CO ₂ . Don't use Halon fire extinguisher. May use dry powder, sand, earth.	
Attention in Fire-extinguishing	The Firemen should put on antigas masks and full fire-fighting suits.	

Report No.: TCT170418M009

Page 3 of 8 Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com





Section 6- Accidental Release Measures

	Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
E	Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
1	Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
1	Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7- Handling and Storage

Handling	Don't handing the batteries in manner that allows terminals to short circuit
Storage	Store and used far away from heat, sparks, open flame, or other heat ignition sources, and under room temperature(<30°C) in ventilating and dehumidifying environments.
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Section 8 - Exposure Controls/Personal Protection

Engineering Controls	No engineering controls are required for handling batteries that have not been damaged. Personal protective equipments for damaged batteries should include chemical resistant gloves and safety glasses.
	Respiratory Protection: In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory
Personal Protective Equipment	Protection is not necessary under conditions of normal use. Not necessary under conditions of normal use.
	Protective Gloves: Not necessary under conditions of normal use.

Report No.: TCT170418M009 Page 4 of 8
Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Other Protective Clothing or Equipment: Not necessary under conditions of normal use.
Personal Protection is recommended for venting battery: Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

Section 9-Physical and Chemical Properties

	Appearance: Square	
Physical State	Color: White or Black	
Odour: If leaking, smells of medical ether.		of medical ether.
Change in condi	tion:	
pH		Not applicable as supplied.
Flash Point		Not applicable unless individual components exposed.
Flammability	(c)	Not applicable unless individual components exposed.
Relative density:		Not applicable unless individual components exposed.
Solubility (water)		Not applicable unless individual components exposed.
Solubility (other)		Not applicable unless individual components exposed.

Section 10 - Stability and Reactivity

Stability	Stable under normal temperatures and pressures.	
Conditions to Avoid	Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.	
Hazardous Decomposition Products	Toxic Fumes, and may form peroxides.	
If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons		

Section 11 - Toxicological Information

Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available
Reproductive Toxicity	Not Available
Toxicologically Synergistic Materials	Not Available

Report No.: TCT170418M009

Page 5 of 8 Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Section 12-Ecological Information

General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available

Section 13 - Disposal Considerations

Waste Treatment	Recycle or dispose of in accordance with government, stat & local regulations.
Attention for Waste Treatment	Deserted batteries couldn't be treated as ordinary trash. Couldn't be thrown into fire or placed in high temperature. Couldn't be dissected, pierced, crushed or treated similarly. Best way is recycling.

Section 14 - Transport Information

UN number	3480
UN Proper shipping name	Lithium ion Batteries
	(limited to a maximum of 30% SoC)
Transport hazard class(es)	9
Marine pollutant (Yes/No)	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	No information available.

Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Transport information:

The goods can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section II/Section IB appropriate of IATA DGR 58th (2017 Edition) for transportation.

Report No.: TCT170418M009 Page 6 of 8
Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com



According to the special provision 188 of IMDG CODE (Amdt. 38-16) 2016 Edition, the products are not subject to dangerous goods.

Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

More information concerning shipping, testing, marking and packaging can be obtained from label master at http://www.labelmaster.com/.

Transport Fashion: By air, by sea, by railway, by road.

Section 15 - Regulatory Information

Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods 》

《Occupational Safety and Health Act 》 (OSHA)

《Toxic Substance Control Act》(TSCA)

《Consumer Product Safety Act 》 (CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act TitleIII(302/311/312/313) 》 (SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws

Report No.: TCT170418M009 Page 7 of 8
Hotline: 400-6611-140 Tel: 86-755- 27673339 Fax: 86-755-27673332 http://www.tct-lab.com





Section 16 – Additional Information

MSDS creation date: 2017/05 Version: 1.0





The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Report No.: TCT170418M009

Shenzhen TCT Testing Technology Co., Ltd.

1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town, Baoan District, Shenzhen,

Guangdong, P.R.C (518101)

Search Number: TCT170418M009C

Search System: http://www.tct-lab.com/cn/search.asp