



### Absolute Maximum Ratings (Ta=25°C)

Item	Symbol	Value	Unit
<b>Power Supply</b>	Voltage	5	V
<b>Duty Cycle</b>	Duty	1/12	-
<b>Operating Temperature</b>	Topr	-30 ~ +85	°C
<b>Storage Temperature</b>	Tstg	-40 ~ +100	°C
<b>Lead Soldering Temperature</b>	Tsol	260°C/5sec	-

\* Pulse width Max 0.1ms, Duty ratio max 1/10

### Electrical –Optical Characteristics (Ta=25°C)

Part Number	Color	V <sub>F</sub> (V)			I <sub>V</sub> (mcd)*			λD (nm)*			Fled (Hz)* Typ.	2Ø1/2 (deg) Typ.		
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.				
LED-5-BL-2,4-WEISS-750	Cool White	3.0	3.3	5.0	500	750	-	CCT: 8000-18000K			2.4	130		
LED-5-BL-2,4-W-WEISS-750	Warm White	3.0	3.3	5.0	500	750	-	CCT: 2700-3200K						
LED-5-BL-2,4-BLAU-150	Blue	3.0	3.3	5.0	100	150	-	465	470	475				
LED-5-BL-2,4-GRÜN-750	Pure Green	3.0	3.3	5.0	500	750	-	520	525	530				
LED-5-BL-2,4-GELB-750	Yellow	3.0	3.3	5.0	500	750	-	585	590	595				
LED-5-BL-2,4-ORANGE-900	Orange	3.0	3.3	5.0	750	900	-	600	605	610				
LED-5-BL-2,4-ROT-750	Red	3.0	3.3	5.0	500	750	-	620	625	630				

\*1 Tolerance of measurements of chromaticity coordinates is ± 10%

\*2 Tolerance of measurements of dominant wavelength is ± 1nm

\*3 Tolerance of measurements of luminous intensity is ± 15%

\*4 Tolerance of measurements of forward voltage is ± 0.1V

\*5 Tolerance of measurements of Frequency is 20%.