

Datasheet

Item no.: 1605263-1 roll
1605264-5 rolls

V1_0712_01_en

ESD Anti-static Grid Tapes



Description:

ESD antistatic grid tape uses OPP as materials, it features a high performance adhesive tape for antistatic function, has the characteristics of discharge electrostatic charge and transparency, widely used in static sensitive product, such as semiconductor and electronic components.

Features

Excellent static shielding and anti static effects.
Reliable ESD protection.
Electronic products anti static protection.

Applications

Packaging requiring EMI Shielding
Sealing ESD packaging and containers
Secure (bundle) IC DIP tubes
Tape dispensing: voltage generated by unrolling will effectively be reduced to zero
Used as ESD symbols for ESD awareness

Specification:

Material: OPP
Color: Black
Thickness: 60 μ m (\pm 0.5 μ m)
Width: 60mm
Length: 50{
Inner diameter of core: 76 { { (Tolerance: \pm 2mm)
Rupture ^longation factor: 60Å
Tensile strength: 4.5kg/cm²
Heat resistance temperature: 80°C
Surface Resistance: 10^{^9} Ω

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str.1 , D-92240 Hirschau (www.conrad.com) .

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represent the technical status at the time of printing.

© Copyright 2017 by Conrad Electronic SE.