



TI-30X Plus MathPrint™ Scientific Calculator Guidebook

Important Information

Except as otherwise expressly stated in the License that accompanies a program, Texas Instruments makes no warranty, either express or implied, including but not limited to any implied warranties of merchantability and fitness for a particular purpose, regarding any programs or book materials and makes such materials available solely on an "as-is" basis. In no event shall Texas Instruments be liable to anyone for special, collateral, incidental, or consequential damages in connection with or arising out of the purchase or use of these materials, and the sole and exclusive liability of Texas Instruments, regardless of the form of action, shall not exceed the amount set forth in the license for the program. Moreover, Texas Instruments shall not be liable for any claim of any kind whatsoever against the use of these materials by any other party.

MathPrint, APD, Automatic Power Down, and EOS are trademarks of Texas Instruments Incorporated.

Copyright © 2025 Texas Instruments Incorporated

Actual products may vary slightly from provided images.

Contents

Getting Started	1
Switching the Calculator On and Off	1
Display Contrast	1
Home Screen	1
2nd Functions	2
Modes	2
Multi-Tap Keys	5
Menus	5
Examples	6
Scrolling Expressions and History	6
Answer Toggle	6
Last Answer	7
Order of Operations	8
Clearing and Correcting	10
Memory and Stored Variables	10
Math Functions	14
Fractions	14
Scientific Notation [EE]	16
Powers, Roots and Inverses	17
Pi (symbol Pi)	18
Math	19
Number Functions	20
Angles	21
Trigonometry	24
Hyperbolics	26
Logarithm and Exponential Functions	26
Statistics, Regressions, and Distributions	27
Probability	39
Math Tools	41
Stored Operations	41
Data Editor and List Formulas	42
Function Table	46
Expression Evaluation	49
Constants	50
Complex Numbers	51
Reference Information	54
Errors and Messages	54
Battery Information	58

Australian Lithium Battery Warning 59

In Case of Difficulty 59

General Information 60

Getting Started

This section contains information about basic calculator functionality.

Switching the Calculator On and Off

[on] turns on the calculator. **[2nd] [off]** turns it off. The display is cleared, but the history, settings, and memory are retained.

The APD™ (Automatic Power Down™) feature turns off the calculator automatically if no key is pressed for about 3 minutes. Press **[on]** after APD™. The display, pending operations, settings, and memory are retained.

Display Contrast

The brightness and contrast of the display can depend on room lighting, battery freshness, and viewing angle.

To adjust the contrast:

1. Press and release the **[2nd]** key.
2. Press **[◀]** (to darken the screen) or **[▶]** (to lighten the screen).

Note: This will adjust the contrast one level at a time. Repeat steps 1 and 2 as needed.

Home Screen

On the Home screen, you can enter mathematical expressions and functions, along with other instructions. The answers are displayed on the Home screen.

The TI-30X Plus MathPrint™ screen can display a maximum of four lines with a maximum of 16 characters per line. For entries and expressions longer than the visible screen area, you can scroll left and right (**[◀]** and **[▶]**) to view the entire entry or expression.

In the MathPrint™ mode, you can enter up to four levels of consecutive nested functions and expressions, which include fractions, square roots, exponents with $^{\wedge}$, $\sqrt[n]{y}$, e^x , and 10^x .

When you calculate an entry on the Home screen, depending upon space, the answer is displayed either directly to the right of the entry or on the right side of the next line.

Special indicators and cursors may display on the screen to provide additional information concerning functions or results.

Indicator	Definition
2ND	2nd function.
FIX	Fixed-decimal setting. (See Mode section.)
SCI, ENG	Scientific or engineering notation. (See Mode section.)

Indicator	Definition
DEG, RAD, GRAD	Angle mode (degrees, radians, or gradians). (See Mode section.)
L1, L2, L3	Displays above the lists in data editor.
H, B, O	Indicates HEX, BIN, or OCT number-base mode. No indicator displayed for default DEC mode.
	The calculator is performing an operation. Use on to break the calculation.
▲ ▼	An entry is stored in memory before and/or after the visible screen area. Press ☞ and ☛ to scroll.
►	Indicates that the multi-tap key is active.
■	Normal cursor. Shows where the next item you type will appear. Replaces any current character.
▣	Entry-limit cursor. No additional characters can be entered.
—	Insert cursor. A character is inserted in front of the cursor location.
□□	Placeholder box for empty MathPrint™ template. Use arrow keys to move into the box.
▶	MathPrint™ cursor. Continue entering in the current MathPrint™ template, or press ⏏ to exit the template.

2nd Functions

2nd


Most keys can perform more than one function. The primary function is indicated on the key and the secondary function is displayed above it. Press **2nd** to activate the secondary function of a given key. Notice that **2ND** appears as an indicator on the screen. To cancel before pressing the next key, press **2nd** again. For example, **2nd** **[√]** **25** **enter** calculates the square root of 25 and returns the result, 5.

Modes

mode

Use **mode** to choose modes. Press **☛** **☞** **⏏** **⏏** to choose a mode, and **enter** to select it. Press **clear** or **2nd** **[quit]** to return to the Home screen and perform your work using the chosen mode settings.

Default settings are highlighted in these sample screens.



DEGREE RADIAN GRADIAN - Sets the angle mode to degrees, radians, or gradians.

NORMAL SCI ENG - Sets the numeric notation mode. Numeric notation modes affect only the display of results, and not the accuracy of the values stored in the unit, which remain maximal.

NORMAL displays results with digits to the left and right of the decimal, as in 123456.78.

SCI expresses numbers with one digit to the left of the decimal and the appropriate power of 10, as in 1.2345678E5, which is the same as the value (1.2345678×10^5) including the parentheses for correct order of operation.

ENG displays results as a number from 1 to 999 times 10 to an integer power. The integer power is always a multiple of 3.

Note: $\boxed{\boxed{EE}}$ is a shortcut key to enter a number in scientific notation format. The result displays in the numeric notation format selected in the mode menu.

FLOAT 0 1 2 3 4 5 6 7 8 9 - Sets the decimal notation mode.

FLOAT (floating decimal point) displays up to 10 digits, plus the sign and decimal.

0 1 2 3 4 5 6 7 8 9 (fixed decimal point) specifies the number of digits (0 through 9) to display to the right of the decimal.

REAL a+bi r$\angle\theta$ - Sets the format of complex number results.

REAL real results

a+bi rectangular results

r$\angle\theta$ polar results

DEC HEX BIN OCT - Sets the number base used for calculations.

DEC decimal

HEX hexadecimal (To enter hex digits A through F, use $\boxed{2nd} \boxed{[A]}$, $\boxed{2nd} \boxed{[B]}$, and so on.)

BIN binary











OCT octal

MATHPRINT CLASSIC

MATHPRINT mode displays most inputs and outputs in textbook format.

CLASSIC mode displays inputs and outputs in a single line.

Examples of MathPrint™ Mode and Classic Modes

MathPrint™ Mode	Classic Mode
Sci 	Sci 
Float mode and answer toggle key 	Float mode and answer toggle key. 
Fix 2 and answer toggle key 	Fix 2 
Un/d 	Un/d entry 
Exponent example 	Exponent example 
Square root example 	Square root example 
Cube root example 	Cube root example 

Multi-Tap Keys

A multi-tap key is one that cycles through multiple functions when you press it. Press $\rightarrow$ to stop multi-tap.

For example, the $\left[\frac{\sin}{\sin^{-1}}\right]$ key contains the trigonometry functions **sin** and **sin⁻¹** as well as the hyperbolic functions **sinh** and **sinh⁻¹**. Press the key repeatedly to display the function that you want to enter.

Multi-tap keys include $\left[\frac{x^{yzt}}{abcd}\right]$, $\left[\frac{\sin}{\sin^{-1}}\right]$, $\left[\frac{\cos}{\cos^{-1}}\right]$, $\left[\frac{\tan}{\tan^{-1}}\right]$, $\left[e^{\square} 10^{\square}\right]$, $\left[\ln \log\right]$, $\left[\frac{! nCr}{nPr}\right]$, and $\left[\pi \frac{e}{i}\right]$. Applicable sections of this guidebook describe how to use the keys.

Menus

Menus give you access to a large number of calculator functions. Some menu keys, such as $\left[2nd\right]$ [recall], display a single menu. Others, such as $\left[math\right]$, display multiple menus.

Press $\rightarrow$ and $\leftarrow$ to scroll and select a menu item, or press the corresponding number next to the item. To return to the previous screen without selecting the item, press $\left[clear\right]$. To exit a menu and return to the Home screen, press $\left[2nd\right]$ [quit].

$\left[2nd\right]$ [recall] (key with a single menu):

RECALL VAR

1:x = 0
2:y = 0
3:z = 0
4:t = 0
5:a = 0
6:b = 0
7:c = 0
8:d = 0

$\left[math\right]$ (key with multiple menus):

MATH	NUM	DMS	R $\leftrightarrow$ P
1: $\rightarrow$ n/d $\leftrightarrow$ Un/d	1:abs(	1: $^{\circ}$	1:P $\rightarrow$ Rx(
2:lcm(	2:round(	2: $'$	2:P $\rightarrow$ Ry(
3:gcd(	3:iPart(	3: $''$	3:R $\rightarrow$ Pr(
4: $\rightarrow$ Pfactor	4:fPart(	4:r	4:R $\rightarrow$ P θ (
5:sum(	5:int(	5:g	
6:prod(	6:min(	6: $\rightarrow$ DMS	
	7:max(		
	8:mod(		

Examples

Some sections are followed by instructions for keystroke examples that demonstrate the TI-30X Plus MathPrint™ functions.

Notes:

- Examples assume all default settings, as shown in the Modes section unless noted in the example.
- Use **clear** to clear the home screen as needed.
- Some screen elements may differ from those shown in this document.
- Since wizards retain their memory, some keystrokes may be different.

Scrolling Expressions and History



Press **left arrow** or **right arrow** to move the cursor within an expression that you are entering or editing. Press **2nd** **left arrow** or **2nd** **right arrow** to move the cursor directly to the beginning or end of the expression.

From an expression or edit, **double right arrow** moves the cursor to the history. Pressing **enter** from an input or output in history will paste that expression back to the cursor position on the edit line.

Press **2nd** **double right arrow** from the denominator of a fraction in the expressions edit to move the cursor to the history. Pressing **enter** from an input or output in the history will paste that expression to the denominator.

Example

$7 \times^2 \square 4$ $\square 3 \square \square 1 \square \text{enter}$	DEG $7^2 - 4(3)(1) \quad 37$
$\text{2nd} \sqrt{\square} \square \square \text{enter}$ enter	DEG $\frac{7^2 - 4(3)(1)}{\sqrt{7^2 - 4(3)(1)}} \quad \frac{37}{\sqrt{37}}$
$\square \square \approx$	DEG $\frac{7^4 - 4(3)(1)}{\sqrt{7^2 - 4(3)(1)}} \quad \frac{37}{\sqrt{37}}$ $\sqrt{37} \blacktriangleright 6.08276253$

Answer Toggle



Press the $\frac{\square}{\square}$ key to toggle the display result (when possible) between fraction and decimal answers, exact square root and decimal, and exact pi and decimal.

Example

Answer toggle	2^{nd} $\sqrt{\square}$ 8 enter	$\sqrt{8}$ DEG $2\sqrt{2}$
	$\frac{\square}{\square}$	$\sqrt{8}$ DEG $2\sqrt{2}$ $2\sqrt{2}$ 2.828427125

Note: $\frac{\square}{\square}$ is also available to toggle number formats for values in cells in the Function Table and in the Data Editor.

Last Answer

2^{nd} [answer]

The last entry performed on the home screen is stored to the variable **ans**. This variable is retained in memory, even after the calculator is turned off. To recall the value of **ans**:

- Press 2^{nd} [answer] (**ans** displays on the screen), or
- Press any operations key ($+$, $-$, and so forth) in most edit lines as the first part of an entry. **ans** and the operator are both displayed.



Examples

ans	3 $\times$ 3 enter	$3*3$ DEG 9
	$\times$ 3 enter	$3*3$ DEG 9 $\text{ans}*3$ 27
	3 2^{nd} $\sqrt{\square}$ 2^{nd} [answer] enter	$3*3$ DEG 9 $\text{ans}*3$ 27 $\sqrt[3]{\text{ans}}$ 3

Note: The variable **ans** is stored and pastes in full precision which is 13 digits.

Order of Operations

The TI-30X Plus MathPrint™ calculator uses Equation Operating System (EOS™) to evaluate expressions. Within a priority level, EOS™ evaluates functions from left to right and in the following order.

1st	Expressions inside parentheses.
2nd	Functions that need a) and precede the argument, such as sin , log , and all R4P menu items.
3rd	Functions that are entered after the argument, such as x² and angle unit modifiers.
4th	Exponentiation (^) and roots (x[√]). Note: In Classic mode, exponentiation using the x[□] key is evaluated from left to right. The expression 2^3^2 is evaluated as (2^3)^2, with a result of 64.  In MathPrint™ mode, exponentiation using the x[□] key is evaluated from right to left. The expression 2^3^2 is evaluated as 2^(3^2), with a result of 512.  The calculator evaluates expressions entered with x² and [1/x] from left to right in both Classic and MathPrint™ modes. Pressing 3 x² x² is calculated as (3²)² = 81.
5th	Negation (-).
6th	Fractions.
7th	Permutations (nPr) and combinations (nCr).
8th	Multiplication, implied multiplication, division, and angle indicator ∠ .
9th	Addition and subtraction.
10th	Logic operators and , nand .
11th	Logic operators or , xor , xnor .
12th	Conversions such as ►n/d◄►Un/d , F◄►D , ►DMS .

13th	sto→
14th	enter evaluates the input expression.

Note: End of expression operators and Base n conversions such as ►Bin, angle conversion ►DMS, ►Pfactor, and complex number conversions ►Polar and ►Rectangle, are only valid in the Home Screen. They are ignored in wizards, function table display and data editor features where the expression result, if valid, will display without a conversion.

Note: Use parentheses to clearly indicate the operation order you expect for your expression entry. If necessary, the parentheses can be used to override the order of operations followed by the algorithms in the calculator. If the result is not as expected, check how the expression was entered and add parentheses as needed.

Examples

+ × ÷ -	60 + 5 × (-) 12 enter	60+5*-12 DEG 0
(-)	1 + (-) 8 + 12 enter	1+ -8+12 DEG 5
√ and +	2nd [√] 9 + 16 enter	√9+16 DEG 5
()	4 × (2 + 3) enter	4*(2+3) DEG 20
() and +	4 (2 + 3) enter	4(2+3) DEG 20
^ and √	2nd [√] 3 [x[□]] 2 ⊙ + 4 [x[□]] 2 enter	√3 ² +4 ² DEG 5
() and -	((-) 3) [x²] enter (-) 3 [x²] enter	(-3) ² DEG 9 -3 ² -9

Clearing and Correcting

2nd [quit]	Returns the cursor to the home screen. Quickly dismisses these applications: Expression Evaluation, Set Operation, Function Table, Data Editor, Statistics and Distributions.
clear	Clears an error message. Clears characters on entry line.
delete	Deletes the character at the cursor. When the cursor is at the end of an expression, it will backspace and delete.
2nd [insert]	Inserts a character at the cursor.
2nd [clear var] 1	Clears variables x , y , z , t , a , b , c , and d to their default value of 0. Any computed Stat Vars will no longer be available in the Stat Vars menu. Recompute statistic features as needed.
2nd [reset] 2	Resets the calculator. Returns the calculator to default settings; clears memory variables, pending operations, all entries in history, and statistical data; clears any stored operation, and ans .

Memory and Stored Variables

x^{yzt} **sto→** **2nd** [recall] **2nd** [clear var]

The TI-30X Plus MathPrint™ calculator has 8 memory variables—**x**, **y**, **z**, **t**, **a**, **b**, **c**, and **d**. You can store the following to a memory variable:

- real or complex numbers
- expression results
- calculations from various applications such as Distributions
- data editor cell values (stored from the edit line)

Features of the calculator that use variables will use the values that you store.



sto→ lets you store values to variables. Press **sto→** to store a variable, and press **x^{yzt}** to select the variable to store. Press **enter** to store the value in the selected variable. If this variable already has a value, that value is replaced by the new one.

x^{yzt} is a multi-tap key that cycles through the variable names **x**, **y**, **z**, **t**, **a**, **b**, **c**, and **d**. You can also use **x^{yzt}** to recall the stored values for these variables. The name of the variable is inserted into the current entry, but the value assigned to the variable is used to evaluate the expression. To enter two or more variables in succession, press **⏎** after each.

2nd **[recall]** recalls the values of variables. Press **2nd** **[recall]** to display a menu of variables and their stored values. Select the variable you want to recall and press **enter**. The value assigned to the variable is inserted into the current entry and used to evaluate the expression.

2nd **[clear var]** clears variable values. Press **2nd** **[clear var]** and select **1:Yes** to clear all variable values. Any computed Stat Vars will no longer be available in the Stat Vars menu. Recompute statistic features as needed.

Examples

Start with clear screen	2nd [quit] [clear]	
Clear Var	2nd [clear var] 1 (Selects Yes)	
Store	15 [sto→] x^{yz} _{abcd}	
	enter	
Recall	2nd [recall]	
	enter x² enter	
	[sto→] x^{yz} _{abcd} x^{yz} _{abcd}	
	enter	

x^{yzt} $abcd$	x^{yzt} $abcd$	15^2x 15^2 $ans \rightarrow y$ y	DEG 15^2 225 225
enter	$\div$ 4 enter	15^2 $ans \rightarrow y$ y $ans / 4$	DEG 15^2 225 225 225 56.25

Problem

In a gravel quarry, two new excavations have been opened. The first one measures 350 meters by 560 meters, the second one measures 340 meters by 610 meters. What volume of gravel does the company need to extract from each excavation to reach a depth of 150 meters? To reach 210 meters? Display the results in engineering notation.

mode $\odot$ $\odot$ $\odot$ enter clear 350 $\times$ 560 $\rightarrow$ x^{yzt} $abcd$ enter	$350 \times 560 \rightarrow x$	ENG DEG $196E3$
340 $\times$ 610 $\rightarrow$ x^{yzt} $abcd$ x^{yzt} $abcd$ enter	$350 \times 560 \rightarrow x$ $340 \times 610 \rightarrow y$	ENG DEG $196E3$ $207.4E3$
clear 150 $\times$ 2nd [recall]	RECALL VAR 1: $x=196E3$ 2: $y=207.4E3$ 3: $z=0E0$	
enter enter	150×196000	ENG DEG $29.4E6$
clear 210 $\times$ 2nd [recall] enter enter	210×196000	ENG DEG $41.16E6$

For the first excavation, the company needs to extract 29.4 million cubic meters to reach a depth of 150 meters, and extract 41.16 million cubic meters to reach a depth of 210 meters.

clear 150 x <input button"="" type="button" value="enter"/>	ENG DEG 150*y 31.11E6
210 x <input button"="" type="button" value="enter"/>	ENG DEG 150*y 31.11E6 210*y 43.554E6

For the second excavation, the company needs to extract 31.11 million cubic meters to reach a depth of 150 meters, and extract 43.554 million cubic meters to reach a depth of 210 meters.

Math Functions

This section contains information about using the calculator math functions such as trigonometry, statistics, and probability.

Fractions

2nd **math** 1 **2nd**

Fractions with can include real and complex numbers, operation keys ($+$, $\times$, etc.), and most function keys (x^2 , **2nd** , etc.).

In Classic mode or classic entries in MathPrint™ mode, the fraction bar displays in-line as a thick bar, for example $8\frac{1}{9}$. Use parentheses to clearly indicate the arithmetic you expect. While the Order of Operations rules will apply, you are in control of the way an expression evaluates by placing the correct parentheses in your inputs.

Fraction Results

- Fraction results are automatically simplified and output is in improper fraction format.
- When mixed number output is desired, use the $\blacktriangleright n/d \blacktriangleleft \blacktriangleright Un/d$ mixed number conversion at the end of the input expression. This feature is located in **math** 1: $\blacktriangleright n/d \blacktriangleleft \blacktriangleright Un/d$.
- Fraction results are obtained when the calculated value can display within the limits of the fraction format supported by the calculator and no decimal value was entered in the input expression.
- If decimal numbers are used or calculated in a fraction numerator or denominator, the result will display as a decimal. Entering a decimal forces the result to display in decimal format.
- Use **2nd** (above) on results to attempt fraction to decimal conversions within the fraction display limits offered by this numeric calculator.

Mixed Numbers and Conversions

- **2nd** enters a mixed number. Press the arrow keys to cycle through the unit, numerator, and denominator.
- **math** 1 converts between simple fractions and mixed-number form ($\blacktriangleright n/d \blacktriangleleft \blacktriangleright Un/d$).
- **2nd** converts results between fractions and decimals.

MathPrint™ Entry

- To enter numbers or expressions in the numerator and denominator in MathPrint™ mode, press .
- Press or to move the cursor between the numerator and denominator.
- Pressing before or after numbers or functions may pre-populate the numerator with parts of your expression. Watch the screen as you press keys to ensure you enter the expression exactly as needed.

On the Home Screen

- To paste a previous entry from history in the numerator or mixed number unit, place the cursor in the numerator or unit, press $\leftarrow$ to scroll to the desired entry, and then press $\boxed{\text{enter}}$ to paste the entry to the numerator or unit.
- To paste a previous entry from history in the denominator, place the cursor in the denominator, press $\boxed{2\text{nd}} \leftarrow$ to jump into history. Press $\leftarrow$ to scroll to the desired entry, and then press $\boxed{\text{enter}}$ to paste the entry to the denominator.

Evaluation of Your Expression

- When $\boxed{\text{enter}}$ is pressed to evaluate your input expression, parentheses may be displayed to clearly indicate how it was interpreted and calculated by the calculator. If it is not what you expected, copy the input expression and edit as needed.

Classic Mode or Classic Entry

- If the cursor is in a classic entry location, enter the numerator expression enclosed by parentheses, then press $\boxed{\frac{\Box}{\Box}}$ to display the thick fraction bar, and then enter the denominator expression also enclosed with parentheses for the result to be calculated as you expect for your problem.

Examples in MathPrint™ Mode

n/d, Un/d	$\boxed{\frac{\Box}{\Box}} \ 3 \ \leftarrow \ 4 \ \rightarrow \ \boxed{+} \ 1$ $\boxed{2\text{nd}} \ \boxed{\frac{\Box}{\Box}} \ 7 \ \leftarrow \ 12$ $\boxed{\text{enter}}$ Note: Parentheses are added automatically.	$\frac{3}{4} + \left(1 \frac{7}{12} \right)$
$\blacktriangleright n/d \blacktriangleleft Un/d$	$9 \ \boxed{\frac{\Box}{\Box}} \ 2 \ \rightarrow \ \boxed{\text{math}} \ 1$ $\boxed{\text{enter}}$	$\frac{9}{2} \blacktriangleright n/d \blacktriangleleft Un/d \quad 4 \frac{1}{2}$
f $\leftrightarrow$ d	$4 \ \boxed{2\text{nd}} \ \boxed{\frac{\Box}{\Box}} \ 1 \ \leftarrow \ 2 \ \rightarrow$ $\boxed{2\text{nd}} \ \boxed{f \leftrightarrow d} \ \boxed{\text{enter}}$	$4 \frac{1}{2} \blacktriangleright f \leftrightarrow d \quad 4.5$
Example	$\boxed{\frac{\Box}{\Box}} \ 1.2 \ \boxed{+} \ 1.3 \ \leftarrow \ 4$ $\boxed{\text{enter}}$ Note: Result is decimal since decimal numbers were used in the fraction.	$\frac{1.2+1.3}{4} \quad 0.625$

Example	$\frac{5(-5+2\sqrt{5^2-4(1)(6)})}{2(1)}$	$\frac{-5+\sqrt{5^2-4(1)(6)}}{2(1)} = -2$
---------	--	---

Examples in Classic Mode

n/d, Un/d	$3 \div 4 + 1 \div 12$	$3/4 + 1/12 = 7/3$
►n/d◄Un/d	$9 \div 2 \div 1$	$9/2 \div 1 = 4.5$
f◄d	$4 \div 1 \div 2$	$4/1 \div 2 = 4.5$
Parentheses	$(2x^2 - 1)(2x^2 + 1)$	$(2^2 - 1)(2^2 + 1) = 3/5$

Scientific Notation [EE]

EE

EE is a shortcut key to enter a number in scientific notation format. A number such as (1.2×10^{-4}) is entered in the calculator as the number 1.2E-4.

Example

$2 \text{ EE } 5 \text{ enter}$ Note: Enters (2×10^5) using the calculator E notation.	$2 \text{ E } 5 = 200000$
$\text{mode} \rightarrow \text{enter}$ Note: The SCI mode setting displays results in scientific notation.	DEGREE RADI AN GRADIAN NORMAL SCI ENG FLOAT 0 1 2 3 4 5 6 7 8 9 REAL a+bi r∠θ

clear enter	$\frac{2 \times 10^5}{2 \times 10^5} = \frac{200000}{2 \times 10^5}$
clear 4 EE 2 × 6 EE (-) 1 enter	$4 \times 10^2 \times 6 \times 10^{-1} = 2.4 \times 10^2$
$\frac{\square}{\square}$ 5 EE 3 $\div$ 2 EE 4 enter 2nd [answer] 2nd [f $\leftrightarrow$ d]	$\frac{5 \times 10^3}{2 \times 10^4} = \frac{1}{4} = 2.5 \times 10^{-1}$

Example

Textbook Problem clear $\left(\frac{5 \times 10}{10 \times 4} \right)^3 \div \left(\frac{1}{2} \right)^2$ enter	$\left(\frac{5 \times 10^3}{2 \times 10^4} \right)^3 \div \left(\frac{1}{2} \right)^2 = 2.5 \times 10^{-1}$
Using EE clear 5 EE 3 $\div$ 2 EE 4 enter	$5 \times 10^3 / 2 \times 10^4 = 2.5 \times 10^{-1}$

Powers, Roots and Inverses

x^2	Calculates the square of a value.
$x^\square$	Raises a value to the power indicated. Use $\rightarrow$ to move the cursor out of the power in MathPrint™ mode.
2nd [$\sqrt{}$]	Calculates the square root of a non-negative value. In complex number modes, a+bi and r $\angle$ θ , calculates the square root of a negative real value.
2nd [$\sqrt[n]{}$]	Calculates the x th root of any non-negative value and any odd integer root of a negative value.
$\frac{1}{\square}$	Inverts the entered value as $1/x$.

Examples

5 x^2 + 4 x^2 2 + 1 $\rightarrow$ enter	$5^2 + 4^{2+1} = 89$
--	----------------------

10 $x^{\square}$ $(-)$ 2 enter	10^{-2} DEG $\frac{1}{100}$
2nd $\sqrt{}$ 49 enter	$\sqrt{49}$ DEG 7
2nd $\sqrt{}$ 3 x^2 + 2 $x^{\square}$ 4 enter	$\sqrt{3^2+2^4}$ DEG 5
6 2nd $\sqrt[n]{}$ 64 enter	$\sqrt[6]{64}$ DEG 2
3 enter 2nd $\left[\frac{\square}{\square}\right]$ enter	$\frac{3}{1}$ DEG $\frac{3}{1}$ ans $\frac{1}{3}$

Pi (symbol Pi)

π (multi-tap key)

$\pi \approx 3.14159265359$ for calculations.

$\pi \approx 3.141592654$ for display in Float mode.

Example

π	2 $\times$ π enter	$2 \times \pi$ DEG 2π
	$\leftrightarrow \approx$	$2 \times \pi$ $2\pi \leftrightarrow$ 6.283185307 DEG 2π

Problem

What is the area of a circle if the radius is 12 cm?

Reminder: $A = \pi \times r^2$

π $\times$ 12 $\times^2$ enter $\leftrightarrow \approx$	DEG $\pi \times 12^2$ 144 π 144 π 452.3893421
---	--

The area of the circle is 144π square cm. The area of the circle is approximately 452.4 square cm when rounded to one decimal place.

Math

math MATH

math displays the **MATH** menu:

1: $\rightarrow$ n/d $\leftrightarrow$ Un/d	Converts between simple fractions and mixed-number form.
2:lcm(	Least common multiple Syntax: lcm (valueA,valueB)
3:gcd(	Greatest common divisor Syntax: gcd (valueA,valueB)
4: $\rightarrow$ Pfactor	Prime factors
5:sum(	Summation Syntax: sum (expression,variable,lower,upper) (Classic mode syntax)
6:prod(	Product Syntax: prod (expression,variable,lower,upper) (Classic mode syntax)

Examples

$\rightarrow$ n/d $\leftrightarrow$ Un/d	$\frac{9}{2}$ $\frac{\square}{\square}$ 2 $\rightarrow$ math 1 enter	DEG $\frac{9}{2}$ $\rightarrow$ n/d $\leftrightarrow$ Un/d 4 $\frac{1}{2}$
lcm(	math 2 6 $\frac{\square}{\square}$ [,] 9 $\frac{\square}{\square}$ enter	DEG lcm(6,9) 18
gcd(	math 3 18 $\frac{\square}{\square}$ [,] 33 $\frac{\square}{\square}$ enter	DEG gcd(18,33) 3

►Pfactor	253 $\boxed{\text{math}}$ 4 $\boxed{\text{enter}}$	DEG 253►Pfactor 11*23
sum(	$\boxed{\text{math}}$ 5 1 $\rightarrow$ 4 $\rightarrow$ $\boxed{x^{y \div z}}$ $\boxed{\times}$ 2 $\boxed{\text{enter}}$	DEG $\sum_{x=1}^4 (x*2)$ 20
prod(	$\boxed{\text{math}}$ 6 1 $\rightarrow$ 5 $\rightarrow$ 1 $\boxed{\frac{\Box}{\Box}}$ $\boxed{x^{y \div z}}$ $\rightarrow$ $\rightarrow$ $\boxed{\text{enter}}$	SCI DEG $\prod_{x=1}^5 \left(\frac{1}{x} \right)$ $\frac{1}{120}$

Number Functions

$\boxed{\text{math}}$ **NUM**

$\boxed{\text{math}}$ $\rightarrow$ displays the **NUM** menu:

1:abs(	Absolute value Syntax: abs (value)
2:round(	Rounded value Syntax: round (value,#decimals)
3:iPart(	Integer part of a number Syntax: iPart (value)
4:fPart(	Fractional part of a number Syntax: fPart (value)
5:int(	Greatest integer that is $\leq$ the number Syntax: int (value)
6:min(	Minimum of two numbers Syntax: min (valueA,valueB)
7:max(	Maximum of two numbers Syntax: max (valueA,valueB)
8:mod(	Modulo (remainder of first number $\div$ second number) Syntax: mod (dividend,divisor)

Examples

abs(	$\boxed{\text{math}} \rightarrow 1$ $\boxed{(-)} \boxed{2\text{nd}} \boxed{\sqrt{}} 5 \boxed{\text{enter}}$	$ -\sqrt{5} $
round(	$\boxed{\text{math}} \rightarrow 2$ 1.245 $\boxed{2\text{nd}} \boxed{,} 1 \boxed{}$ $\boxed{\text{enter}}$ $\boxed{\leftarrow} \boxed{\leftarrow} \boxed{\text{enter}}$ $\boxed{\rightarrow} \boxed{\rightarrow} \boxed{\rightarrow} \boxed{\rightarrow} 5 \boxed{\text{enter}}$	$\text{round}(1.245, 1)$ $\text{round}(1.255, 1)$
iPart(fPart(	4.9 $\boxed{\text{sto}\rightarrow} \boxed{x_{abcd}} \boxed{\text{enter}}$ $\boxed{\text{math}} \rightarrow 3 \boxed{x_{abcd}} \boxed{}$ $\boxed{\text{enter}}$ $\boxed{\text{math}} \rightarrow 4 \boxed{x_{abcd}} \boxed{}$ $\boxed{\text{enter}}$	$4.9 \rightarrow x$ iPart(x) fPart(x)
int(	$\boxed{\text{math}} \rightarrow 5$ $\boxed{(-)} 5.6 \boxed{}$ $\boxed{\text{enter}}$	$\text{int}(-5.6)$
min(max(	$\boxed{\text{math}} \rightarrow 6$ 4 $\boxed{2\text{nd}} \boxed{,} \boxed{(-)} 5 \boxed{}$ $\boxed{\text{enter}}$ $\boxed{\text{math}} \rightarrow 7$.6 $\boxed{2\text{nd}} \boxed{,} .7 \boxed{}$ $\boxed{\text{enter}}$	$\text{min}(4, -5)$ $\text{max}(.6, .7)$
mod(	$\boxed{\text{math}} \rightarrow 8$ 17 $\boxed{2\text{nd}} \boxed{,} 12 \boxed{}$ $\boxed{\text{enter}}$ $\boxed{\leftarrow} \boxed{\leftarrow} \boxed{\text{enter}} \boxed{\rightarrow} \boxed{\rightarrow} 6$ $\boxed{\text{enter}}$	$\text{mod}(17, 12)$ $\text{mod}(17, 16)$

Angles

$\boxed{\text{math}}$ **DMS**

$\boxed{\text{math}} \rightarrow \rightarrow$ displays the **DMS** menu:

1:°	Specifies the angle unit modifier as degrees (°).
2:′	Specifies the angle unit modifier as minutes (′).
3:″	Specifies the angle unit modifier as seconds (″).
4:r	Specifies a radian angle.
5:g	Specifies a gradian angle.
6:→DMS	Converts angle from decimal degrees to degrees, minutes, and seconds.

Choose an angle mode from the mode screen. You can choose from DEGREE (default), RADIAN, or GRADIAN. Entries are interpreted and results displayed according to the angle mode setting without needing to enter an angle unit modifier.

Note: You can also convert between rectangular coordinate form (R) and polar coordinate form (P). (See Rectangular to Polar for more information.)

Examples

RADIAN	<code>mode</code> $\rightarrow$ <code>enter</code>	$\overset{\text{RAD}}{\text{DEGREE RADI AN GRADI AN}}$ NORMAL SCI ENG $\text{FLOAT } 0 \ 1 \ 2 \ 3 \ 4 \ 5 \ 6 \ 7 \ 8 \ 9$ $\text{REAL } a+bi \ r\angle\theta$ $\downarrow$
	<code>clear</code> <code>sin</code> 30 <code>math</code> $\rightarrow$ $\rightarrow$	MATH NUM DMS $1 \rightarrow^\circ$ $2 \rightarrow'$ $3 \rightarrow''$
	1 <code>)</code> <code>enter</code>	$\overset{\text{RAD}}{\sin(30^\circ)}$ $\frac{1}{2}$
DEGREE	<code>mode</code> <code>enter</code>	$\overset{\text{DEG}}{\text{DEGREE RADI AN GRADI AN}}$ NORMAL SCI ENG $\text{FLOAT } 0 \ 1 \ 2 \ 3 \ 4 \ 5 \ 6 \ 7 \ 8 \ 9$ $\text{REAL } a+bi \ r\angle\theta$ $\downarrow$
	<code>clear</code> 2 <code>[π]</code> <code>math</code> $\rightarrow$ $\rightarrow$ 4 <code>enter</code>	$\overset{\text{DEG}}{\sin(30^\circ)}$ $2\pi^r$ $\frac{1}{2}$ 360
$\rightarrow$ DMS	1.5 <code>math</code> $\rightarrow$ $\rightarrow$ 6 <code>enter</code>	$\overset{\text{DEG}}{\sin(30^\circ)}$ $2\pi^r$ $1.5 \rightarrow \text{DMS}$ $1^\circ 30' 0''$

Problem

Two adjacent angles measure $12^\circ 31' 45''$ and $26^\circ 54' 38''$ respectively. Add the two angles and display the result in DMS format. Round the results to two decimal places.

<code>clear</code> <code>mode</code> $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ <code>enter</code>	$\overset{\text{FIX}}{\text{DEGREE RADI AN GRADI AN}}$ NORMAL SCI ENG $\text{FLOAT } 0 \ 1 \ 2 \ 3 \ 4 \ 5 \ 6 \ 7 \ 8 \ 9$ $\text{REAL } a+bi \ r\angle\theta$ $\downarrow$
---	---

clear 12 math ▸ ▸	MATH NUM DMS 18° 2:' 3↓"
1 31 math ▸ ▸ 2 45 math ▸ ▸ 3 + 26 math ▸ ▸ 1 54 math ▸ ▸ 2 38 math ▸ ▸ 3 enter	FIX DEG 12°31'45"+26°54'→ 39.44
math ▸ ▸ 6 enter	FIX DEG 12°31'45"+26°54'→ 39.44 ans→DMS 39°26'23"

The result is 39 degrees, 26 minutes and 23 seconds.

Problem

It is known that $30^\circ = \pi / 6$ radians. In the default mode, degrees, find the sine of 30° . Then set the calculator to radian mode and calculate the sine of $\pi / 6$ radians.

Notes

- Press **clear** to clear the screen between problems.
- The indicator row displays DEG or RAD mode setting for the current calculation only.

clear sin ⁻¹ 30) enter	FIX DEG sin(30) 1/2
mode ▸ enter clear sin ⁻¹ π / 6 6) enter	FIX RAD sin(30) sin($\frac{\pi}{6}$) 1/2 1/2

Retain radian mode on the calculator and calculate the sine of 30° . Change the calculator to degree mode and find the sine of $\pi / 6$ radians.

clear sin ⁻¹ 30 math ▸ ▸ enter) enter mode enter clear sin ⁻¹ π / 6 6 ▸ math ▸ ▸ 4) enter	FIX DEG sin(30°) sin($\frac{\pi}{6}$) 1/2 1/2
---	---

Trigonometry

$\sin$ $\sin^{-1}$ $\cos$ $\cos^{-1}$ $\tan$ $\tan^{-1}$ (multi-tap keys)

Pressing one of these multi-tap keys repeatedly lets you access the corresponding trigonometric or inverse trigonometric function. Set the Angle mode - Degree or Radian - before your calculation.

Example in Degree Mode

tan	clear mode enter clear $\tan$ $\tan^{-1}$ 45 enter	$\tan(45)$ DEG $\hat{=}$ 1
$\tan^{-1}$	clear $\tan$ $\tan^{-1}$ 1 enter	$\tan^{-1}(1)$ DEG $\hat{=}$ 45
COS	clear 5 $\times$ $\cos$ $\cos^{-1}$ 60 enter	$5*\cos(60)$ DEG $\hat{=}$ $\frac{5}{2}$

Example in Radian Mode

tan	clear mode $\rightarrow$ enter clear $\tan$ $\tan^{-1}$ π $\div$ 4 $\rightarrow$ enter	$\tan\left(\frac{\pi}{4}\right)$ RAD $\hat{=}$ 1
$\tan^{-1}$	clear $\tan$ $\tan^{-1}$ 1 enter	$\tan^{-1}(1)$ RAD $\hat{=}$ $\frac{\pi}{4}$
	$\leftrightarrow \approx$	$\tan^{-1}(1)$ RAD $\hat{=}$ $\frac{\pi}{4}$ $\frac{\pi}{4} \leftrightarrow 0.785398163$
COS	clear 5 $\times$ $\cos$ $\cos^{-1}$ π $\div$ 4 $\rightarrow$ enter	$5*\cos\left(\frac{\pi}{4}\right)$ RAD $\hat{=}$ $\frac{5\sqrt{2}}{2}$

	clear $\leftrightarrow \approx$	5√2 2 ↔ 3.535533906
--	---------------------------------	---

Problem

Find angle A of the right triangle below. Then calculate angle B and the length of the hypotenuse c . Lengths are in meters. Round results to one decimal place.


Reminder:

$$\tan A = \frac{7}{3} \text{ therefore } m\angle A = \tan^{-1}\left(\frac{7}{3}\right)$$

$$m\angle A + m\angle B + 90^\circ = 180^\circ$$

$$\text{therefore } m\angle B = 90^\circ - m\angle A$$

$$c = \sqrt{3^2 + 7^2}$$



Note: Set mode to **DEGREE** and fix 1 decimal place for the calculations.

mode enter $\odot$ $\odot$ $\blacktriangleright$ $\blacktriangleleft$ enter	FIX DEG DEGREE RADI AN GRADIAN NORMAL SCI ENG FLOAT 0 1 2 3 4 5 6 7 8 9 REAL a+bi r∠θ
clear	
$\tan$ $\tan^{-1}$ 7 $\div$ 3 $\blacktriangleright$) enter	FIX DEG $\tan^{-1}\left(\frac{7}{3}\right)$ 66.8
90 $\square$ 2nd [answer] enter	FIX DEG $\tan^{-1}\left(\frac{7}{3}\right)$ 66.8 90-ans 23.2
2nd [$\sqrt{}$] 3 $\square x^2$ + 7 $\square x^2$ enter	FIX DEG $\tan^{-1}\left(\frac{7}{3}\right)$ 66.8 90-ans 23.2 $\sqrt{3^2+7^2}$ $\sqrt{58}$

$\leftrightarrow \approx$	FIX DEG 90-ans 23.2 $\sqrt{3^2+7^2}$ $\sqrt{58}$ $\sqrt{58}$ 7.6
mode enter $\downarrow$ $\downarrow$ $\uparrow$ $\uparrow$ enter	FIX DEG DEGREE RADIAN GRADIAN NORMAL SCI ENG FLOAT 0 1 2 3 4 5 6 7 8 9 REAL a+bi r$\angle$$\theta$

To one decimal place, the measure of angle A is 66.8° , the measure of angle B is 23.2° , and the length of the hypotenuse is 7.6 meters.

Hyperbolics

$\sin^{-1}$ $\cos^{-1}$ $\tan^{-1}$ (multi-tap keys)

Pressing one of these multi-tap keys repeatedly lets you access the corresponding hyperbolic or inverse hyperbolic function. Angle modes do not affect hyperbolic calculations.

Example

Set floating decimal	mode $\downarrow$ $\downarrow$ enter	DEG DEGREE RADIAN GRADIAN NORMAL SCI ENG FLOAT 0 1 2 3 4 5 6 7 8 9 REAL a+bi r$\angle$$\theta$
	clear $\sin^{-1}$ $\sin^{-1}$ $\sin^{-1}$ 5 $\downarrow$ + 2 enter	DEG $\sinh(5)+2$ 76.20321058
	$\sin^{-1}$ $\sin^{-1}$ $\sin^{-1}$ enter 2nd $\downarrow$ $\sin^{-1}$ enter	DEG $\sinh(5)+2$ 76.20321058 $\sinh^{-1}(5)+2$ 4.312438341

Logarithm and Exponential Functions

$\ln$ log $e^x 10^x$ (multi-tap keys)

$\ln$ log pastes the natural logarithm, $\ln$, of a number to the base e. The argument of the function is $\ln(\text{value})$.

$e \approx 2.718281828459$ for calculations.

$e \approx 2.718281828$ for display in Float mode.





$\ln$ log $\ln$ log pastes the common logarithm, $\log_{10}$, of a number. The argument of the function is $\log(\text{value})$.

ln log **ln log** **ln log** pastes the logBASE function as a MathPrint™ template. When needed, the arguments in classic entry are **logBASE**(value,base).

e[□]10[□] pastes e to the power function.

e[□]10[□] **e[□]10[□]** pastes 10 to the power function.

Examples

log	ln log ln log 1) enter	
ln	ln log 5) × 2 enter	
10 [□]	clear e[□]10[□] e[□]10[□] ln log ln log 2) enter ln log ln log e[□]10[□] e[□]10[□] 5)) enter	
e [□]	clear e[□]10[□] .5 enter	

Statistics, Regressions, and Distributions

data **2nd** [stat-reg/distr]

data lets you enter and edit the data lists. (See Data Editor section.)

2nd [stat-reg/distr] displays the **STAT-REG** menu, which has the following options.

Notes:

- Regressions store the regression information, along with the 2-Var statistics for the data, in StatVars (menu item 1).
- A regression can be stored to either f(x) or g(x). The regression coefficients display in full precision.

Important note about results: Many of the regression equations share the same variables **a**, **b**, **c**, and **d**. If you perform any regression calculation, the regression calculation and the 2-Var statistics for that data are stored in the **StatVars** menu until the next statistics or regression calculation. The results must be interpreted based on which type of statistics or regression calculation was last performed. To help you interpret correctly, the title bar reminds you of which calculation was last performed.

1:StatVars	Displays a secondary menu of the last computed statistical result variables. Use $\leftarrow$ and $\rightarrow$ to locate the desired variable, and press enter to select it. If you select this option before calculating 1-Var stats, 2-Var stats, or any of the regressions, a reminder appears.
2:1-VAR STATS	Analyzes statistical data from 1 data set with 1 measured variable, x . Frequency data may be included.
3:2-VAR STATS	Analyzes paired data from 2 data sets with 2 measured variables— x , the independent variable, and y , the dependent variable. Frequency data may be included. Note: 2-Var Stats also computes a linear regression and populates the linear regression results. It displays values for a (slope) and b (y-intercept); it also displays values for r^2 and r .
4:LinReg $ax+b$	Fits the model equation $y=ax+b$ to the data using a least-squares fit for at least two data points. It displays values for a (slope) and b (y-intercept); it also displays values for r^2 and r .
5:PropReg ax	Fits the model equation $y=ax$ to the data using least squares fit for at least one data point. It displays the value for a . Supports data forming a vertical line with the exception of all 0 data.
6:RecipReg $a/x+b$	Fits the model equation $y=a/x+b$ to the data using least squares fit on linearized data for at least two data points. It displays values for a and b ; it also displays values for r^2 and r .
7:QuadraticReg	Fits the second-degree polynomial $y=ax^2+bx+c$ to the data. It displays values for a , b , and c ; it also displays a value for R^2 . For three data points, the equation is a polynomial fit; for four or more, it is a polynomial regression. At least three data points are required.
8:CubicReg	Fits the third-degree polynomial $y=ax^3+bx^2+cx+d$ to the data. It displays values for a , b , c , and d ; it also displays a value for R^2 . For four points, the equation is a polynomial fit; for five or more, it is a polynomial regression. At least four points are required.
9:LnReg $a+b\ln x$	Fits the model equation $y=a+b\ln(x)$ to the data using a least squares fit and transformed values $\ln(x)$ and y . It displays values for a and b ; it also displays values for r^2 and r .

:PwrReg ax^b	Fits the model equation $y=ax^b$ to the data using a least-squares fit and transformed values $\ln(x)$ and $\ln(y)$. It displays values for a and b ; it also displays values for r^2 and r .
:ExpReg ab^x	Fits the model equation $y=ab^x$ to the data using a least-squares fit and transformed values x and $\ln(y)$. It displays values for a and b ; it also displays values for r^2 and r .
:expReg $ae^{(bx)}$	Fits the model equation $y=a e^{(bx)}$ to the data using least squares fit on linearized data for at least two data points. It displays values for a and b ; it also displays values for r^2 and r .

[2nd] [stat-reg/distr] **Ⓐ** displays the **DISTR** menu, which has the following distribution functions:

1:Normalpdf	Computes the probability density function (pdf) for the normal distribution at a specified x value. The defaults are mean $\mu=0$ and standard deviation $\sigma=1$. The probability density function (pdf) is: $f(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x-\mu)^2}{2\sigma^2}}, \sigma > 0$
2:Normalcdf	Computes the normal distribution probability between <i>LOWERbnd</i> and <i>UPPERbnd</i> for the specified mean μ and standard deviation σ. The defaults are $\mu=0$; $\sigma=1$; with <i>LOWERbnd</i> = $-1E99$ and <i>UPPERbnd</i> = $1E99$. Note: $-1E99$ to $1E99$ represents $-\infty$ to ∞.
3:invNormal	Computes the inverse cumulative normal distribution function for a given area under the normal distribution curve specified by mean μ and standard deviation σ. It calculates the x value associated with an area to the left of the x value. $0 \leq \text{area} \leq 1$ must be true. The defaults are $\text{area}=1$, $\mu=0$ and $\sigma=1$.
4:Binomialpdf	Computes a probability at x for the discrete binomial distribution with the specified <i>numtrials</i> and probability of success (p) on each trial. x is a non-negative integer and can be entered with options of SINGLE entry, LIST of entries or ALL (list of probabilities from 0 to <i>numtrials</i> is returned). $0 \leq p \leq 1$ must be true. The probability density function (pdf) is: $f(x) = \binom{n}{x} p^x (1-p)^{n-x}, x = 0, 1, \dots, n$

5:Binomialcdf	Computes a cumulative probability at x for the discrete binomial distribution with the specified <i>numtrials</i> and probability of success (p) on each trial. x can be non-negative integer and can be entered with options of SINGLE, LIST or ALL (a list of cumulative probabilities is returned.) $0 \leq p \leq 1$ must be true.
6:Poissonpdf	Computes a probability at x for the discrete Poisson distribution with the specified mean μ (μ), which must be a real number > 0 . x can be an non-negative integer (SINGLE) or a list of integers (LIST). The default is $\mu=1$. The probability density function (pdf) is: $f(x) = e^{-\mu} \mu^x / x!, x = 0, 1, 2, \dots$
7:Poissoncdf	Computes a cumulative probability at x for the discrete Poisson distribution with the specified mean μ , which must be a real number > 0 . x can be an non-negative integer (SINGLE) or a list of integers (LIST). The default is $\mu=1$.

Stats Results

Variables	1-Var or 2-Var	Definition
n	Both	Number of x or (x,y) data points.
$\bar{x}$	Both	Mean of all x values.
$\bar{y}$	2-Var	Mean of all y values.
Sx	Both	Sample standard deviation of x .
Sy	2-Var	Sample standard deviation of y .
σ_x	Both	Population standard deviation of x .
σ_y	2-Var	Population standard deviation of y .
Σx or Σx^2	Both	Sum of all x or x^2 values.
Σy or Σy^2	2-Var	Sum of all y or y^2 values.
Σxy	2-Var	Sum of $(x \times y)$ for all xy pairs.
a	2-Var	Linear regression slope.
b	2-Var	Linear regression y -intercept.
r^2 or r	2-Var	Correlation coefficient.
x'	2-Var	Uses a and b to calculate predicted x value when you input a y value.

Variables y'	1-Var or 2-Var	Definition
$\min X$ or $\max X$	Both	Uses a and b to calculate predicted y value when you input an x value.
Q1	1-Var	Median of the elements between $\min X$ and Med (1st quartile).
Med	1-Var	Median of all data points.
Q3	1-Var	Median of the elements between Med and $\max X$ (3rd quartile).
$\min Y$ or $\max Y$	2-Var	Minimum or maximum of y values.

To define statistical data points:

1. Enter data in L1, L2, or L3. (See Data Editor section.)

Note: Non-integer frequency elements are valid. This is useful when entering frequencies expressed as percentages or parts that add up to 1. However, the sample standard deviation, S_x , is undefined for non-integer frequencies, and $S_x=\text{Error}$ is displayed for that value. All other statistics are displayed.

2. Press **[2nd]** **[stat-reg/distr]**. Select **1-Var** or **2-Var** and press **[enter]**.
3. Select L1, L2, or L3, and the frequency.
4. Press **[enter]** to display the menu of variables.
5. To clear data, press **[data]** **[data]**, select a list to clear, and press **[enter]**.

1-Var Example

Find the mean of {45,55,55,55}.

Clear all data	[data] [data] [>] [>] [>]	
Data	[enter] 45 [>] 55 [>] 55 [>] 55 [enter]	
Stat	[2nd] [quit] [2nd] [stat-reg/distr]	

	2 (Selects 1-VAR STATS) ⏮ ⏭	
	enter	
Stat Var	2 enter	
	x 2 enter	

2-Var Example

Data: (45,30); (55,25). Find: $x'(45)$.

Clear all data	data data ⏮ ⏭ ⏮	
Data	enter 45 ⏮ 55 ⏮ ⏭ 30 ⏮ 25 ⏮	
Stat	2nd [stat-reg/distr]	
	3 (Selects 2-VAR STATS) ⏮ ⏭ ⏮	
StatVars	enter 2nd [quit] 2nd [stat-reg/distr] 1 ⏮ ⏮ ⏮ ⏮ ⏮ ⏮	

enter 45) enter	x' (45) DEG 15
------------------	----------------

Problem

For his last four tests, Anthony obtained the following scores. Tests 2 and 4 were given a weight of 0.5, and tests 1 and 3 were given a weight of 1.

Test No.	1	2	3	4
Score	12	13	10	11
Weight	1	0.5	1	0.5

- Find Anthony's average grade (weighted average).
- What does the value of n given by the calculator represent? What does the value of Σx given by the calculator represent?

Reminder: The weighted average is

$$\frac{\Sigma x}{n} = \frac{(12)(1) + (13)(0.5) + (10)(1) + (11)(0.5)}{1+0.5+1+0.5}$$

- The teacher gave Anthony 4 more points on test 4 due to a grading error. Find Anthony's new average grade.

data data > > >	DEG CLR FORMULA OPS 2↑Clear L2 3:Clear L3 4:Clear ALL
enter data > > > > >	DEG CLR FORMULA OPS 3↑Clear L2 Frmla 4:Clear L3 Frmla 5:Clear ALL
enter 12 > 13 > 10 > 11 > > 1 > .5 > 1 > .5 enter	DEG 13 0.5 10 1 11 0.5 ----- L2(5)=
2nd [stat-reg/distr]	DEG STAT-REG DISTR 1:StatVars 2:1-VAR STATS 3↓2-VAR STATS

2 ⏮ ⏪ ⏩ ⏭ enter	DEG 1-Var:STATS DATA: L1 L2 L3 FREQ: ONE L1 ☒ L3 CALC
enter	DEG 1-Var:L1,L2 1:n=3 2:x=11.333333333 3↓Sx=Error

Anthony has an average ($\bar{x}$) of 11.33 (to the nearest hundredth).

On the calculator, n represents the total sum of the weights.

$$n = 1 + 0.5 + 1 + 0.5.$$

Σx represents the weighted sum of his scores.

$$(12)(1) + (13)(0.5) + (10)(1) + (11)(0.5) = 34.$$

Change Anthony's last score from 11 to 15.

data ⏮ ⏪ ⏩ 15 enter	DEG 13 0.5 10 1 15 0.5 ----- L1(5)=
2nd [stat-reg/distr] 2 ⏮ ⏪ ⏩ enter enter	DEG 1-Var:L1,L2 1:n=3 2:x=12 3↓Sx=Error

If the teacher adds 4 points to Test 4, Anthony's average grade is 12.

Problem

The table below gives the results of a braking test.

Test No.	1	2	3	4
Speed (kph)	33	49	65	79
Braking distance (m)	5.30	14.45	20.21	38.45

Use the relationship between speed and braking distance to estimate the braking distance required for a vehicle traveling at 55 kph.

A hand-drawn scatter plot of these data points suggest a linear relationship. The calculator uses the least squares method to find the line of best fit, $y' = ax' + b$, for data entered in lists.

data data $\odot$ $\odot$ $\odot$	DEG CLR FORMULA OPS 2↑Clear L2 3:Clear L3 4:Clear ALL
enter 33 $\odot$ 49 $\odot$ 65 $\odot$ 79 $\odot$ 5.3 $\odot$ 14.45 $\odot$ 20.21 $\odot$ 38.45 enter	DEG 49 14.45 65 20.21 79 38.45 ----- L2(5)=
2nd [quit] 2nd [stat-reg/distr]	DEG STAT-REG DISTR 1:StatVars 2:1-VAR STATS 3↓2-VAR STATS
3 (Selects 2-VAR STATS) $\odot$ $\odot$ $\odot$	DEG 2-VAR STATS ↑ xDATA: L1 L2 L3 yDATA: L1 L2 L3 FREQ: ONE L1 L2 L3 CALC
enter	DEG 2-Var:L1,L2,1 1:n=4 2:x=56.5 3↓Sx=19.89137166
Press $\odot$ as necessary to view a and b .	DEG 2-Var:L1,L2,1 ↑ $\Sigma xy=5234.15$:a=0.6773251895 ↓b=-18.66637320

This line of best fit, $y'=0.67732519x'-18.66637321$ models the linear trend of the data.

Press $\odot$ until y' is highlighted.	DEG 2-Var:L1,L2,1 ↑ $r=0.9634117172$:x'(↓y'()
enter 55 $\square$ enter	DEG y' (55) 18.58651222

The linear model gives an estimated braking distance of 18.59 meters for a vehicle traveling at 55 kph.

Regression Example 1

Calculate an $ax+b$ linear regression for the following data: {1,2,3,4,5}; {5,8,11,14,17}.

Clear all data	data data ↻ ↻ ↻	DEG CLR FORMULA OPS 2↑Clear L2 3:Clear L3 4↓Clear ALL												
Data	enter 1 ↻ 2 ↻ 3 ↻ 4 ↻ 5 ↻ ↻ 5 ↻ 8 ↻ 11 ↻ 14 ↻ 17 enter	DEG <table><tr><td>3</td><td>11</td><td></td></tr><tr><td>4</td><td>14</td><td></td></tr><tr><td>5</td><td>17</td><td></td></tr><tr><td>-----</td><td></td><td></td></tr></table> L2(6)=	3	11		4	14		5	17		-----		
3	11													
4	14													
5	17													

Regression	2nd [quit] 2nd [stat-reg/distr] ↻ ↻ ↻	DEG STAT-REG DISTR 2↑1-VAR STATS 3:2-VAR STATS 4↓LinReg ax+b												
	enter	DEG xDATA: [L1] L2 L3 ↑ yDATA: L1 [L2] L3 FREQ: ONE L1 L2 L3 Regress: NO f(x) g(x) y=a.x+b CALC												
	↻ ↻ ↻ ↻ enter Press ↻ to examine all the result variables.	DEG ax+b: L1, L2, 1 1:a=3 2:b=2 3↓r²=1												

Regression Example 2

Calculate the exponential regression for the following data:

- L1 = {0,1,2,3,4}; L2 = {10,14,23,35,48}
- Find the average value of the data in L2.
- Compare the exponential regression values to L2.

Clear all data	[data] [data] 4	DEG <table> <tr><td>-----</td><td></td><td></td></tr> <tr><td>-----</td><td></td><td></td></tr> <tr><td>-----</td><td></td><td></td></tr> </table> L1(1)=	-----			-----			-----					

Data	0 $\odot$ 1 $\odot$ 2 $\odot$ 3 $\odot$ 4 $\odot$ $\odot$ 10 $\odot$ 14 $\odot$ 23 $\odot$ 35 $\odot$ 48 [enter]	DEG <table> <tr><td>2</td><td>23</td><td></td></tr> <tr><td>3</td><td>35</td><td></td></tr> <tr><td>4</td><td>48</td><td></td></tr> <tr><td>-----</td><td></td><td></td></tr> </table> L2(6)=	2	23		3	35		4	48		-----		
2	23													
3	35													
4	48													

Regression	2nd [stat-reg/distr] ⬆ ⬆	
Save the regression equation to $f(x)$ in the table menu.	enter ⬇ ⬇ ⬇ ⬆ enter	
Regression Equation	enter	
Find the average value ($\bar{y}$) of the data in L2 using StatVars.	2nd [stat-reg/distr] 1 (Selects StatVars) ⬇ ⬇ ⬇ ⬇ ⬇ ⬇ ⬇ ⬇	Notice that the title bar reminds you of your last statistical or regression calculation.
Examine the table of values of the regression equation.	table 1	
	enter ⬇ 0 enter 1 enter	
	enter enter	

Warning: If you now calculate 2-Var Stats on your data, the variables **a** and **b** (along with **r** and **r²**) will be calculated as a linear regression. Do not recalculate 2-Var Stats after any other regression calculation if you want to preserve your regression coefficients (**a**, **b**, **c**, **d**) and **r** values for your particular problem in the **StatVars** menu.

Distribution Example

Compute the binomial pdf distribution at x values {3,6,9} with 20 trials and a success probability of 0.6. Enter the x values in list L1, store the results in L2, and then find the sum of the probabilities and store in the variable t .

Clear all data	[data] [data] [<] [<] [<]	DEG CLR FORMULA OPS 2↑Clear L2 3:Clear L3 4HClear ALL
Data	[enter] 3 [>] 6 [>] 9 [enter]	L1 DEG L2 L3 L1(4)=
DISTR	[2nd] [stat-reg/distr] [>] [>] [>] [>]	DISTR 1:Normalpdf 2:Normalcdf 3↓Binomialpdf
	[enter] [>]	Binomialpdf DEG x: SINGLE LIST ALL
	[enter] 20 [>] 0.6	Binomialpdf: LIST DEG TRIALS=n=20 p(SUCCESS)=0.6
	[enter] [>] [>]	Binomialpdf: LIST DEG xLIST: L1 L2 L3 SAVE TO: L1 L2 L3 CALC
	[enter]	L1 DEG L2 L3 L1(1)=3
	[data] [<] 4 [>] [enter]	SUM LIST DEG SUM LIST: L1 L2 L3 CALC
	[enter] [>] [>] [>] [>] [enter] [enter]	SUM LIST DEG SUM OF LIST=0.0758915335... STORE: No x y z a b c d DONE

Probability

$\frac{nCr}{nPr}$

2nd [random]

$\frac{nCr}{nPr}$ is a multi-tap key that cycles through the following options:



!	A factorial , $n!$, is the product of the positive integers from 1 to n . The value of n must be a positive whole number ≤ 69 . When $n = 0$, $n! = 1$
nCr	Calculates the number of possible combinations given n and r , non-negative integers. The order of objects is not important, as in a hand of cards.
nPr	Calculates the number of possible permutations of n items taken r at a time, given n and r , non-negative integers. The order of objects is important, as in a race.

2nd [random] displays a menu with the following options:

rand	Generates a random real number between 0 and 1. To control a sequence of random numbers, store an integer (seed value) ≥ 0 to rand . The seed value changes randomly every time a random number is generated.
randint(	Generates a random integer between two integers, A and B , where $A \leq \text{randint} \leq B$. The arguments of the function are: randint(integerA, integerB)


Examples

!	4 $\frac{nCr}{nPr}$ enter	4 ! DEG 24
nCr	52 $\frac{nCr}{nPr}$ $\frac{nCr}{nPr}$ 5 enter	4 ! DEG 24 52 nCr 5 2598960
nPr	8 $\frac{nCr}{nPr}$ $\frac{nCr}{nPr}$ $\frac{nCr}{nPr}$ 3 enter	4 ! DEG 24 52 nCr 5 2598960 8 nPr 3 336

Store value to rand	5 sto→ 2nd [random]	DEG 
	1 (Selects rand) enter	DEG 
rand	2nd [random] 1 enter	DEG 
randint(	2nd [random] 2 3 2nd [,] 5) enter	DEG 

Problem

An ice cream store advertises that it makes 25 flavors of home made ice cream. You like to order three different flavors in a dish. How many combinations of ice cream can you test over a very hot summer?

clear 25 1 nCr 1 nCr 3 enter	DEG 
---	--

You can choose from 2300 dishes with different combinations of flavors!

Math Tools

This section contains information about using the calculator tools such as data lists, functions, and conversions.

Stored Operations

2nd **[op]** **2nd** **[set op]**

2nd **[set op]** lets you store an operation.

2nd **[op]** pastes operation to the home screen.

To set an operation and then recall it:

1. Press **2nd** **[set op]**.
2. Enter any combination of numbers, operations, and/or values.
3. Press **enter** to store the operation.
4. Press **2nd** **[op]** to recall the stored operation and apply it to the last answer or the current entry.

If you apply **2nd** **[op]** directly to a **2nd** **[op]** result, the **n=1** iteration counter is incremented.

Examples

Clear op	2nd [set op] If a stored op is present, press clear to clear it.	DEG OP= Enter operation. Set op:[enter] ↓
Set op	× 2 + 3	DEG OP= *2+3 ↓
	enter	DEG Operation set! [2nd][op] pastes to Home Screen.
Recall op	4 2nd [op]	DEG 4*2+3 n=1 11
	2nd [op]	DEG 4*2+3 n=1 11 11*2+3 n=2 25

	2nd [op]	$\begin{array}{r} 4 \times 2 + 3 \\ 11 \times 2 + 3 \\ 25 \times 2 + 3 \end{array}$ DEG n=1 11 n=2 25 n=3 53
Redefine op	clear 2nd [set op] clear x^2 enter	$OP = 2$ DEG ↓
Recall op	5 2nd [op] 20 2nd [op]	$\begin{array}{r} 5^2 \\ 20^2 \end{array}$ DEG n=1 25 n=1 400

Problem

A local store allows you to earn loyalty points that you can redeem for various gifts. The store adds 35 points to your mobile app for every visit. You would like to get a music download which costs 275 points. How many visits will it take? Currently, you have 0 points.

2nd [set op] clear $+$ 35 enter	$OP = +35$ DEG ↓
0 2nd [op] 2nd [op] 2nd [op] 2nd [op]	$\begin{array}{r} 0 + 35 \\ 35 + 35 \\ 70 + 35 \\ 105 + 35 \end{array}$ DEG n=1 35 n=2 70 n=3 105 n=4 140
2nd [op] 2nd [op] 2nd [op] 2nd [op]	$\begin{array}{r} 140 + 35 \\ 175 + 35 \\ 210 + 35 \\ 245 + 35 \end{array}$ DEG n=5 175 n=6 210 n=7 245 n=8 280

After 8 visits to the store you will have 280 points which is enough for your download!

Data Editor and List Formulas

data

Pressing **data** displays the Data Editor where you can enter data in up to 3 lists (L1, L2, L3). Each list can contain up to 50 items.

Note: This feature is available in DEC mode only.

When editing a list, press **data** to access the following menus:

CLR	FORMULA	OPS
1:Clear L1	1:Add/Edit Frmla	1:Sort Sm-Lg...
2:Clear L2	2:Clear L1 Frmla	2:Sort Lg-Sm...
3:Clear L3	3:Clear L2 Frmla	3:Sequence...
4:Clear ALL	4:Clear L3 Frmla	4:Sum List...
	5:Clear ALL	

Entering and Editing Data

- Use $\leftarrow$ $\rightarrow$ $\uparrow$ $\downarrow$ to highlight a cell in the data editor and then enter a value.
- Mode settings such as number format, Float/Fix decimal and angle modes affect the display of a cell value.
- Fractions, radicals and π values will display.
- Press:
 - $\boxed{\text{sto} \rightarrow}$ in a cell edit to store the value of the cell to a variable.
 - $\boxed{\leftarrow \rightarrow}$ to toggle the number format when a cell is highlighted.
 - $\boxed{\text{delete}}$ to delete a cell.
 - $\boxed{\text{enter}}$ $\boxed{\text{clear}}$ to clear the edit line of a cell.
 - $\boxed{2\text{nd}}$ $\boxed{[\text{quit}]}$ to return to the Home Screen.
 - $\boxed{2\text{nd}}$ $\boxed{\uparrow}$ to go to the top of a list.
 - $\boxed{2\text{nd}}$ $\boxed{\downarrow}$ to go to the bottom of a list.
- Use the **CLR** menu to clear the data from a list.

List Formulas (FORMULA menu)

- In the data editor, press $\boxed{\text{data}}$ $\rightarrow$ to display the **FORMULA** menu. Select the appropriate menu item to add or edit a list formula in the highlighted column, or clear formulas from a particular list.
- When a data cell is highlighted, pressing $\boxed{\text{sto} \rightarrow}$ is a shortcut to open the formula edit state.
- In the formula edit state, pressing $\boxed{\text{data}}$ displays a menu to paste L1, L2 or L3 in the formula.
- Formulas cannot contain a circular reference such as $L1=L1$.
- When a list contains a formula, the edit line will display the reversed cell name. Cells will update if referenced lists are updated.
- To clear a formula list, clear the formula first, and then clear the list.
- If $\boxed{\text{sto} \rightarrow}$ is used in a list formula, the last element of the computed list is stored to the variable. Lists cannot be stored.
- List formulas accept all calculator functions and real numbers.

Options (OPS menu)

In the data editor, press **[data]** **[◀]** to display the **OPS** menu. Select the appropriate menu item to:

- Sort values from smallest to largest or largest to smallest.
- Create a Sequence of values to fill a list.
- Sum the elements in a list and store to a variable for further investigation.

Example

L1	[data] [data] 4 [data] 1 [] 4 [▼] 2 [] 4 [▼] 3 [] 4 [▼] 4 [] 4 [enter]	
Formula	[▶] [data] [▶]	
	[enter]	
	[data]	
	[enter] [2nd] [f◀▶d]	
	[enter]	
Fill a list with a sequence	[▶] [data] [▶] 3 [▶] [▶] [enter]	

	π $\frac{e}{i}$ $x^{y=z}$ $\frac{a}{bcd}$ enter 1 enter 4 enter 1 enter	DEG EXPR IN $x:\pi x$ START $x:1$ END $x:4$ STEP SIZE:1 SEQUENCE FILL
	enter	DEG 1/4 0.25 π 1/2 0.5 2π 3/4 0.75 3π 1 1 4π L3(1)= π
Store the Sum of L1 to the variable z	data 4 enter	DEG SUM LIST SUM LIST: L1 L2 L3 CALC
	enter > > > enter enter	DEG SUM LIST SUM OF LIST=5/2 STORE: No x y t a b c d DONE

Problem

On a November day, a weather report on the Internet listed the following temperatures.

Paris, France 8°C

Moscow, Russia -1°C

Montreal, Canada 4°C

Convert these temperatures from degrees Celsius to degrees Fahrenheit. (See also the section on Conversions.)

Reminder: $F = \frac{9}{5}C + 32$

data data 4 data 5	DEG CLR FORMULA OPS 2↑Clear L2 3:Clear L3 4:Clear ALL DEG CLR FORMULA OPS 3↑Clear L2 Frmla 4:Clear L3 Frmla 5:Clear ALL
8 > (-) 1 > 4 > >	DEG 8 -1 4 ----- L2(1)=

The function table allows you to display a defined function in a tabular form. To set up a function table:

1. Press **table** and select **Add/Edit Func.**
2. Enter one or two functions and press **enter**.
3. Select the table start, table step, auto, or ask- x options and press **enter**.

The table is displayed using the specified values. Table results will display as Real numbers in DEC mode only. Complex functions evaluate on the home screen only.

Start	Specifies the starting value for the independent variable, x .
Step	Specifies the incremental value for the independent variable, x . The step can be positive or negative.
Auto	The calculator automatically generates a series of values based on table start and table step.
Ask- x	Lets you build a table manually by entering specific values for the independent variable, x . The table has a maximum of three rows, but you can overwrite the x values as needed to see more results.

Note: In the Function Table view, press **clear** to display and edit the Table Setup wizard as needed.

Problem

Find the vertex of the parabola, $y = x(36 - x)$ using a table of values.

Reminder: The vertex of the parabola is the point on the parabola that is also on the line of symmetry.

table 1 clear x_{abcd} (36 - x_{abcd})	$f(x) = x(36 - x)$
enter clear enter	TABLE SETUP Start=0 Step=1 Auto $x = ?$ CALC
15 ↵ 3 ↵ ↵	TABLE SETUP Start=15 Step=3 Auto $x = ?$ CALC

enter	
x	DEG $f(x)$
15	315
18	324
21	315
$x=15$	

After searching close to $x = 18$, the point (18,324) appears to be the vertex of the parabola since it appears to be the turning point of the set of points of this function. To search closer to $x = 18$, change the Step value to smaller and smaller values to see points closer to (18,324).

Problem

A charity collected \$3,600 to help support a local food kitchen. \$450 will be given to the food kitchen every month until the funds run out. How many months will the charity support the kitchen?

Reminder: If x = months and y = money left, then $y = 3600 - 450x$.

table 1 clear 3600 $\square$ 450 x^{yzt} x_{abcd}	$f(x) = 3600 - 450x$								
enter clear enter 0 $\downarrow$ 1 $\downarrow$ $\rightarrow$ enter enter	TABLE SETUP Start=0 Step=1 Auto $x = ?$ CALC								
Input each guess and press enter .	<table><thead><tr><th>x</th><th>$f(x)$</th></tr></thead><tbody><tr><td>2</td><td>2700</td></tr><tr><td>7</td><td>450</td></tr><tr><td>8</td><td>0</td></tr></tbody></table> $x=8$	x	$f(x)$	2	2700	7	450	8	0
x	$f(x)$								
2	2700								
7	450								
8	0								
Calculate the value of $f(8)$ on the Home screen. 2nd [quit] table	FUNCTION TABLE 1: Add/Edit Func 2: f(3: 9(								
2 Selects $f($ 8 $)$ enter	$f(8)$								

The support of \$450 per month will last for 8 months since $y(8) = 3600 - 450(8) = 0$ as shown in the table of values.

Problem

Find the intersection of the lines $f(x) = -2x + 5$ and $g(x) = x - 4$.

table1clear(-)2x^{yzt}_{abcd}+5	$f(x) = -2x + 5$												
enterclearx^{yzt}_{abcd}-4	$g(x) = x - 4$												
enter2enter1 Select Auto enterenter	TABLE SETUP Start=2 Step=1 Auto $x = ?$ CALC												
enter↵	<table><thead><tr><th>x</th><th>$f(x)$</th><th>$g(x)$</th></tr></thead><tbody><tr><td>2</td><td>1</td><td>-2</td></tr><tr><td>3</td><td>-1</td><td>-1</td></tr><tr><td>4</td><td>-3</td><td>0</td></tr></tbody></table>$x=3$	x	$f(x)$	$g(x)$	2	1	-2	3	-1	-1	4	-3	0
x	$f(x)$	$g(x)$											
2	1	-2											
3	-1	-1											
4	-3	0											

The two lines intersect at $(x,y) = (3,-1)$.

Expression Evaluation

2nd [expr-eval]

Press **2nd** [expr-eval] to input and calculate an expression using numbers, functions, and variables/parameters. Pressing **2nd** [expr-eval] from a populated home screen expression pastes the content to **Expr=**. If the cursor focus is in history, the selected expression will paste to **Expr=** when **2nd** [expr-eval] is pressed.

If variables, x , y , z , t , a , b , c or d are used in the expression, you will be prompted for values or use the stored values displayed for each prompt. The number stored in the variables will update in the calculator.

Example

2nd [expr-eval] clear	Expr= Enter Expression
2 x^{yzt}_{abcd} + x^{yzt}_{abcd} x^{yzt}_{abcd} x^{yzt}_{abcd}	Expr= $2x + z$

enter clear 1 $\frac{\square}{\square}$ 4	$x = \frac{1}{4}$ ■ DEG ↑ ↓
enter clear 2nd $\sqrt{}$ 27	$z = \sqrt{27}$ ■ DEG ↑ ↓
enter	$2x + z$ DEG $\frac{1+6\sqrt{3}}{2}$ ↑ ↓
2nd [expr-eval]	Expr=2x+z DEG ↓
enter clear 2nd $\sqrt{}$ 40	$x = \sqrt{40}$ ■ DEG ↑ ↓
enter clear 2nd $\sqrt{}$ 45 $\rightarrow$ π_i° π_i° π_i°	$z = \sqrt{45}i$ ■ DEG ↑ ↓
enter	$2x + z$ DEG $4\sqrt{10} + 3\sqrt{5}i$ ↑ ↓

Constants

Constants lets you access scientific constants to paste in various areas of the TI-30X Plus MathPrint™ calculator. Press **2nd** [constants] to access, and $\rightarrow$ or $\leftarrow$ to select either the **NAMES** or **UNITS** menus of the same 20 physical constants. Use $\uparrow$ and $\downarrow$ to scroll through the list of constants in the two menus. The **NAMES** menu displays an abbreviated name next to the character of the constant. The **UNITS** menu has the same constants as **NAMES** but the units of the constant show in the menu.

NAMES	UNITS
1:c	Speed Light
2:g	GravityAccel
3:h	Planck Const

NAMES	UNITS
1:c	m/s
2:g	m/s ²
3:h	J s

Note: Displayed constant values are rounded. The values used for calculations are given in the following table (NIST 2018).

	Constant	Value used for calculations
c	speed of light	299792458 meters per second
g	gravitational acceleration	9.80665 meters per second ²
h	Planck's constant	6.62607015×10 ⁻³⁴ Joule seconds
NA	Avogadro's number	6.02214076×10 ²³ molecules per mole
R	ideal gas constant	8.314462618 Joules per mole per Kelvin
m _e	electron mass	9.1093837015×10 ⁻³¹ kilograms
m _p	proton mass	1.67262192369×10 ⁻²⁷ kilograms
m _n	neutron mass	1.67492749804×10 ⁻²⁷ kilograms
m _μ	muon mass	1.883531627×10 ⁻²⁸ kilograms
G	universal gravitation	6.6743×10 ⁻¹¹ meters ³ per kilogram per seconds ²
F	Faraday constant	96485.33212 Coulombs per mole
a ₀	Bohr radius	5.29177210903×10 ⁻¹¹ meters
r _e	classical electron radius	2.8179403262×10 ⁻¹⁵ meters
k	Boltzmann constant	1.380649×10 ⁻²³ Joules per Kelvin
e	electron charge	1.602176634×10 ⁻¹⁹ Coulombs
u	atomic mass unit	1.6605390666×10 ⁻²⁷ kilograms
atm	standard atmosphere	101325 Pascals
ε0	permittivity of vacuum	8.8541878128×10 ⁻¹² Farads per meter
μ0	permeability of vacuum	1.25663706212×10 ⁻⁶ Newtons per ampere ²
Cc	Coulomb's constant	8.987551792261×10 ⁹ meters per Farad

Complex Numbers

2nd [complex]

The calculator performs the following complex number calculations:

- Addition, subtraction, multiplication, and division
- Argument and absolute value calculations
- Reciprocal, square, and cube calculations
- Complex Conjugate number calculations

Setting the Complex Format

Set the calculator to DEC mode when computing with complex numbers.

[mode]    Selects the **REAL** menu. Use  and  to scroll with in the **REAL** menu to highlight the desired complex results format **a+bi**, or **r∠θ**, and press **[enter]**.

REAL, **a+bi**, or **r∠θ** set the format of complex number results.

a+bi rectangular complex results

r∠θ polar complex results

Notes:

- Complex results are not displayed unless complex numbers are entered.
- To access i on the keypad, use the multi-tap key .
- Variables x, y, z, t, a, b, c , and d are real or complex.
- Complex numbers can be stored.
- For **conj()**, **real()**, and **imag()**, the argument can be in either rectangular or polar form. The output for **conj()** is determined by the mode setting.
- The output for **real()** and **imag()** are real numbers.
- Set mode to DEGREE or RADIAN depending on the angle measure needed.

Complex Menu	Description
1:∠	∠ (polar angle character) Lets you paste the polar representation of a complex number (such as $5∠\pi$).
2:polar angle	Returns the polar angle of a complex number. Syntax: angle(value)
3:magnitude	Returns the magnitude (modulus) of a complex number. Syntax: abs(value) (or $ \square $ in MathPrint™ mode)
4:↻r∠θ	Displays a complex result in polar form. Valid only at the end of an expression.
5:↻a+bi	Displays a complex result in rectangular form. Valid only at the end of an expression.
6:conjugate	Returns the conjugate of a complex number. Syntax: conj(value)

Complex Menu 7:real	Description Returns the real part of a complex number. Syntax: real (value)
8:imaginary	Returns the imaginary (nonreal) part of a complex number. Syntax: imag (value)

Examples (set mode to RADIAN)

Polar angle character: $\angle$	clear 5 2nd [complex] enter π $\frac{\pi}{i}$ $\frac{\pi}{i}$ 2 enter	RRD $5\angle\frac{\pi}{2}$ $5i$
Polar angle: angle(	clear 2nd [complex] $\downarrow$ enter 3 + 4 π $\frac{\pi}{i}$ π $\frac{\pi}{i}$ $\frac{\pi}{i}$) enter	RRD angle(3+4i) 0.927295218
Magnitude: abs(	clear 2nd [complex] 3 (3 + 4 π $\frac{\pi}{i}$ π $\frac{\pi}{i}$) enter	RRD (3+4i) 5
$\triangleright r\angle\theta$	clear 3 + 4 π $\frac{\pi}{i}$ π $\frac{\pi}{i}$ π $\frac{\pi}{i}$) 2nd [complex] 4 enter	RRD 3+4i $\triangleright r\angle\theta$ 5 $\angle$ 0.927295218
$\triangleright a+bi$	clear 5 2nd [complex] enter 3 π $\frac{\pi}{i}$ $\frac{\pi}{i}$ 2 $\downarrow$ 2nd [complex] 5 enter	RRD $5\angle\frac{3\pi}{2}$ $\triangleright a+bi$ -5i
Conjugate: conj(	clear 2nd [complex] 6 5 - 6 π $\frac{\pi}{i}$ π $\frac{\pi}{i}$ π $\frac{\pi}{i}$) enter	RRD conj(5-6i) 5+6i
Real: real(	clear 2nd [complex] 7 5 - 6 π $\frac{\pi}{i}$ π $\frac{\pi}{i}$ π $\frac{\pi}{i}$) enter	RRD real(5-6i) 5

Reference Information

This section contains information about errors, maintaining and replacing the batteries, and troubleshooting problems.

Errors and Messages

When the calculator detects an error, the screen will display the error type or a message.

- To correct an error: Press **[clear]** to clear the error screen. The cursor will display at or near the error. Correct the expression.
- To close the error screen without correcting the expression: Press **[2nd]** **[quit]** to return to the Home Screen.

The following list includes some of the errors and messages that you may encounter.

Error/Message	Description
Argument	This error is returned when: • a function does not have the correct number of arguments • the lower limit is greater than upper limit in summation or product function
Bounds: Enter $\text{LOWER} \leq \text{UPPER}$	This error is returned when input for lower bound > upper bound for Normalcdf distribution.
Break	This error is returned when the [on] key is pressed to stop the evaluation of an expression.
Calculate 1-Var,2-Var Stat or a regression.	This message is returned when no statistics or regression calculation has been stored.
Change mode to DEC.	This error is returned when the mode is set to BIN, HEX or OCT and the following apps are accessed: [expr-eval] [table] [convert] [stat-reg/distr] [data] These apps are available in DEC mode only.
Dimension mismatch	This error is returned if: • the dimensions of lists used in a data formula are not the same length for the operation • a calculation of 2-var stats is attempted when the data lists are not of equal length
Division by 0	This error is returned if the expression evaluation contains division by 0.

Error/Message	Description
Domain	This error is returned when an argument is not in the function domain. For example: - For $x\sqrt{y}$: $x = 0$ – or – $y < 0$ and x is not an odd integer. - For y^x: y and $x = 0$. - For $\sqrt{x}$: $x < 0$. - For log, ln or logBASE: $x \leq 0$. - For tan: $x = 90^\circ, -90^\circ, 270^\circ, -270^\circ, 450^\circ$, etc., and equivalent for radian mode. - For sin⁻¹ or cos⁻¹: $x > 1$. - For nCr or nPr: n or r are not integers ≥ 0. - For $x!$: x is not an integer between 0 and 69.
Enter $0 \leq \text{area} \leq 1$	This error is returned when you enter an invalid area value in invNormal for a distribution.
Enter $\sigma > 0$	This error is returned when the input for sigma in a distribution is invalid.
Expression is too long	This error is returned when an entry exceeds the digit limits. For example, pasting an expression entry with a constant that exceeds the limit. A checkerboard cursor may display when limits are reached in each MathPrint™ feature.
Formula	This error is returned in data when: - the formula does not contain a list name (L1, L2, or L3) - the formula for a list contains its own list name For example, a formula for L1 contains L1.
Frequency: Enter $\text{FREQ} \geq 0$	This error is returned when at least one element in a list selected for FREQ is a negative real number in 1-VAR or 2-VAR STATS .
Input must be non-negative Integer.	This error is returned when an input is not the expected number type. For example, in distribution arguments TRIALS and x in Binomialpdf.
Input	This error is returned when an input requires a

Error/Message must be Real	Description real number.
Invalid data type	This error is returned when the argument of a command or function is the incorrect data type. For example, the error will be displayed for $\sin(i)$ or $\min(i,7)$ where the arguments must be Real numbers.
Invalid function	This error is returned when no function is defined and a function evaluation is attempted. Define functions in table .
List Dimension $1 \leq \dim(\text{list}) \leq 50$	This error is returned when, in data : - the SUM LIST function is executed on an empty list - a sequence is created with a length of 0 or >50.
Mean: Enter $\mu > 0$	This error is returned when an invalid value is input for the mean ($mean = \mu$) in <code>poissonpdf</code> or <code>poissoncdf</code> .
Memory limit reached	This error is returned when a calculation contains a circular reference such as two functions referencing each other, or a very long calculation.
[2nd] [set op]: Operation is not defined.	This error is returned when an operation has not been defined in 2nd [set op] and 2nd [op] is pressed.
Operation set! [2nd] [op] pastes to Home Screen.	This message is returned when an operation is stored (set) from 2nd [set op] editor. Press any key to continue.
Overflow	This error is returned when a calculation or value is beyond the range of the calculator.
Probability: Enter $0 \leq p \leq 1$	This error is returned when input for the probability in distributions is invalid.
Statistics	This error is returned when a statistical or regression function is invalid. For example, when a calculation of 1-var or 2-var stats is attempted with no defined data points.
Step size must not be 0.	This error is returned when, in data , the STEP SIZE input is set to 0 in the SEQUENCE FILL function.
Syntax	This error is returned when an expression contains misplaced functions, arguments,

Error/Message	Description
	parentheses, or commas.
TRIALS: Enter $0 \leq n \leq 49$	This error is returned in Binomialpdf and Binomialcdf, when the number of trials is out of range, $0 \leq n \leq 49$ in the case of ALL.

Battery Information


Battery Caution:

- Do not ingest battery, Chemical Burn Hazard.
- This product contains a coin or button cell battery. If the coin or button cell battery is swallowed, it can cause severe internal burns in just 2 hours and can lead to death.
- Keep new and used batteries away from children.
- Always completely secure the battery compartment. If the battery compartment does not close securely, stop using the product, remove the batteries, and keep them away from children.
- If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Call a local poison control center for treatment information.
- Even used batteries may cause severe injury or death.
- Non-rechargeable batteries are not to be recharged.
- Do not force discharge, recharge, disassemble, heat above 140F (60C) or incinerate. Doing so may result in injury due to venting, leakage or explosion resulting in chemical burns.
- Ensure the batteries are installed correctly according to polarity (+ and -).
- Do not mix old and new batteries, different brands or types of batteries, such as alkaline, carbon-zinc or rechargeable batteries.
- Risk of fire or explosion if battery is replaced by an incorrect type.
- Remove and immediately recycle or dispose of batteries from equipment not used for an extended period of time according to local regulations. Do NOT dispose of batteries in household trash or incinerate.

How to Remove or Replace the Batteries

The TI-30X Plus MathPrint™ calculator uses two 3-volt CR2032 batteries.

- Remove the protective cover and turn the calculator face downwards.
- With a small screwdriver, remove the screws from the back of the case.
- From the bottom, carefully separate the front from the back. Be careful not to damage any of the internal parts.
- With a small screwdriver, remove the screw on the battery clip and remove the batteries.



- To replace the batteries, check the polarity (+ and -) and slide in the new batteries. Press firmly to snap the new batteries into place and replace the screw in the battery clip.

Important: When replacing the batteries, avoid any contact with the other components of the calculator.

Dispose of the dead batteries immediately and in accordance with local regulations.

Per CA Regulation 22 CCR 67384.4, the following applies to the button cell batteries in this unit:

Perchlorate Material - Special handling may apply.

See: www.dtsc.ca.gov/hazardouswaste/perchlorate

Australian Lithium Battery Warning



WARNING

KEEP BATTERIES OUT OF THE REACH
OF CHILDREN

Coin Battery
inside the product.

- Swallowing may lead to severe or fatal injuries in as little as 2 hours or less due to chemical burns and potential perforation of the esophagus.
- Never allow children to replace coin batteries of any device.
- If it is suspected your child has swallowed or inserted a coin battery immediately call the 24-hour Poisons Information Centre on 13 11 26 immediately for expert advice.
- Examine devices and make sure the battery compartment is correctly secured. E.g. that the screw or other mechanical fastener is tightened. Do not use if compartment is not secure.
- Dispose of used coin batteries immediately and safely. A battery can still be dangerous even when it can no longer operate the device.
- Tell others about the risk associated with the coin batteries and how to keep their children safe.

In Case of Difficulty

Review instructions to be certain calculations were performed properly.

Check the batteries to ensure that they are fresh and properly installed.

Change the batteries when:

- ☐ **on** does not turn the unit on, or
- the screen goes blank, or
- you get unexpected results.

General Information

Online Help

education.ti.com/eguide

Select your country for more product information.

Contact TI Support

education.ti.com/ti-cares

Select your country for technical and other support resources.

Service and Warranty Information

education.ti.com/warranty

Select your country for information about the length and terms of the warranty or about product service.

Limited Warranty. This warranty does not affect your statutory rights.

Texas Instruments Incorporated

12500 TI Blvd.

Dallas, TX 75243