

W-Series
WPD 106 1X70/2X25+3X16 BL**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

General ordering data

Type	WPD 106 1X70/2X25+3X16 BL
Order No.	2518570000
Version	W-Series, Distribution block, Rated cross-section: Terminal rail / mounting plate
GTIN (EAN)	4050118531824
Qty.	1 pc(s).

W-Series
WPD 106 1X70/2X25+3X16 BL

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	39.5 mm	Width (inches)	1.555 inch
Height	74.5 mm	Height (inches)	2.933 inch
Depth	50.4 mm	Depth (inches)	1.984 inch
Net weight	200 g		

Temperatures

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	130 °C		

Material data

Material	Wemid	Colour	blue
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection	Tightening torque (clamping screw for aluminium conductors)	13.6 Nm (70 mm ²) / 5.1 Nm (25 mm ²)
Tightening torque (clamping screw for copper conductors)	10 Nm (70 mm ²) / 2 Nm (25 mm ²)		

Additional technical data

Installation advice	Terminal rail / mounting plate	Type of mounting	Snap-on
---------------------	--------------------------------	------------------	---------

CSA rating data

Certificate number (cCSAus)	70128467
-----------------------------	----------

Rating data

Rated AC voltage	1,000 V AC	Rated DC voltage	1,000 V DC
Standards	IEC 60947-7-1, UL 1059		

UL rating data

Certificate No. (UR)	E60693
----------------------	--------

Classifications

ETIM 5.0	EC001329	ETIM 6.0	EC000897
eClass 6.2	27-14-11-20	eClass 7.1	27-14-11-20
eClass 8.1	27-14-11-20	eClass 9.0	27-14-11-20
eClass 9.1	27-14-11-20		

Product information

Product information	Power distribution block (Bus Bar) also usable for distribution of neutral conductor and function earth.
---------------------	--

Data sheet**W-Series**
WPD 106 1X70/2X25+3X16 BL**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Technical data****Approvals**

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[Attestation of Conformity](#)

Engineering Data

[STEP](#)

Technical data

Inputs

Number of connections

Solid

Stranded

Flexible with ferrule

Ribbon cable

Torque

Clamping screw

Stripping length

Outputs

Number of connections

Solid

Stranded

Flexible with ferrule

Torque

Clamping screw

Stripping length

No. of poles

Note

IEC 60947-7-1, UL 1059

top	mid./left	mid./mid.	mid./right	bottom
		1		1
		10...70mm ²		
		10...70mm ²		
		6...50mm ²		
				15.5 x 5 mm
		10Nm		2Nm
		M 10 x 1		M 5 x 20
		17mm		17mm

top	mid./left	mid./mid.	mid./right	bottom
3				2
1.5...16mm ²				2.5...25mm ²
1.5...16mm ²				2.5...25mm ²
1.5...10mm ²				1.5...16mm ²
2Nm				2Nm
M 6 x 8				M 6 x 8
12mm				12mm

1