

HSM SECURIO B22 - 3.9 x 30 mm




HSM SECURIO B22 document shredder

Data security made easy! The powerful entry level model of the B-series for the workplace. With automatic start/stop and overload protection. The waste container with 33 litres of capacity can be easily removed and emptied.

Technical data

Order number:	1833121	Intake width:	240 mm
EAN	4026631047838	Container volume /	33
Cutting type:	particle cut	collecting:	
Cutting size:	3,9 x 30 mm	Collection volume in sheets (80 g):	435
Security level (DIN 66399):	E-3 F-1 P-4 T-4	Noise level (idle operation):	ca. 57 dB(A)
Cutting capacity in sheets 80g/m ² :	9 - 11	Weight x Depth x Height:	375 x 310 x 600 mm
•		Weight:	12,515 kg
Power consumption:	440 W	Shuadday waatayiah	Danier Stanley and many
Voltage / Frequency:	230 V / 50 Hz	Shredder material:	Paper, Staples and paper clips, Credit card

Product information



The induction-hardened, solid steel cutting rollers guarantee durability.




The full bin is indicated via the display and the machine switches off automatically.



The waste container can be easily removed and emptied.





For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Display bin full

The full bin is indicated via the display and the machine switches off automatically.



Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).







