

# TECHNICAL DATA SHEET

## Heat Shrinking Sleeve for Battery Set


Item No.: 1698483

This transparent battery shrink tubing range with the most common dimensions (flat dimensions) for battery packs of RC models, for single-cell protection or any other applications. The high shrinkage rate of 2: 1 (shrinkage ratio: 48% ± 5%) is therefore ideal for all conventional batteries and batteries and especially for creating additional individual battery packs. The valuable cells are thus compactly united together, protected and can still be read through the transparent protective skin or its optical condition can be assessed. The assortment includes various flat widths from 23 mm to 67 mm and is made of a thin rigid PVC. Each shrink tube has an ideal shrinking behavior and can adapt to the object within a very short time. Furthermore, it is so flame retardant and has a very good resistance to mildew. The very wide continuous use temperature range is between -40 ° C to +105 ° C. An application diagram as well as further technical data of the contained components are clearly printed on the inside of the lid.

**Akku-Schrumpfschlauchsortiment für Akkupsacks und gängige Batteriegehäuse**


GB Heat Shrinking Sleeve for Battery Set  
FR Manchon thermorétractable pour jeu de batteries  
NL Krimpous voor batterij set

Flachmaß / flat diameter / diamètre plat / plate diameter	Länge / length / longueur / pas	Farbe / color / couleur / kleur	Schrumpfrate / shrinking ratio / rapport de rétrécissement / verhouding
23 mm	1 m	Transparent	48 %
55 mm	1 m	Transparent	48 %
67 mm	1 m	Transparent	48 %



3 x 1 Meter


1698483



4 65199 1 54880

Distributed by Conrad Electronic SE Klaus-Conrad-Str. 1 D 92040 Hirschau


Material : PVC  
 Flat wide : 23mm, 55mm , 67mm  
 Length : 1 Meter  
 Shrinking temperature : from 70°C to 125°C  
 Shrinking ratio : 48% ± 5%  
 Operating temperature : -40°C to +105°C




Schrumpftemperatur / shrinking temperature	70°C - 125°C
Schrumpfrate / shrinking ratio	Horizontal / Vertical / 48% ± 5%
	Vertical / 15% ± 5%

Verwendungsbeispiele für Akku Typen / usage example for battery type


**Verwendung für 23 mm Schlauch**  
use for 23 mm sleeve



**Verwendung für 67 mm Schlauch**  
use for 67 mm sleeve




**Verwendung für 55 mm Schlauch**  
use for 55 mm sleeve




Details siehe Datenblatt  
For details see datasheet

### Usage example for battery type

**use for 23 mm sleeve**



**use for 67 mm sleeve**



**use for 55 mm sleeve**

