SIEMENS

Data sheet 3NE4333-3

SITOR fuse link, with slotted blade contacts, NH2, In: 450 A, aR, Un AC: 750 V, front indicator



Model		
Product brand name	SENTRON	
Product designation	SITOR fuse link	
Design of the product	With slotted blade contacts	
Design of an identification indicator	front indicator	
Design of the switching contact	With blade contacts, silver-plated	
Design of the fuse link	SITOR, LV HRC design	
General technical data		
Size of fuse system / acc. to DIN EN 60269-1	NH2	
Operating class of the fuse link	aR	
Varying load factor (WL)	0.9	
Supply voltage		
Type of voltage	AC	
Current / at AC / rated value	450 A	
Supply voltage		
• at AC / rated value	750 V	
Switching capacity		
Switching capacity current		

100 kA • acc. to IEC 60947-2 / rated value

Dissipation	tion	
Power loss [W]	70 W	
Power loss [W]		
 for rated value of the current / at AC / in hot operating state / per pole 	70 W	

Product description Not non-interchangeable

Mechanical Design	
Mounting position	Any, preferably vertical
Net weight	770 g

Environmental conditions	
Ambient temperature	-20 +50 °C
Environmental category	-20 to +50 at 95% relative humidity

Certificates

Reference code

• acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2

General Product Approval	Declaration of Conformity

F

F





Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE4333-3

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3NE4333-3

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE4333-3

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications

