


# ESP-12F

## WiFi Module



The ESP12-F is an ultra-low-power UART WiFi module specially designed for the needs of the networked world. It offers an excellent range of functions in the smallest design. Specially developed for mobile devices and the Internet of Things, the ESP12-F offers an independent network solution.

The module has powerful on-board processing and memory functions that allow minimal development time under minimal load during runtime.



## TECHNICAL SPECIFICATIONS

### GENERAL DATA


<b>Model</b>	ESP-12F
<b>Article No.</b>	SBC-ESP8266-12F
<b>MCU</b>	Low Power 32-Bit
<b>ADC</b>	10-Bit Analog-Digital-Converter
<b>Peripherals</b>	SDIO 2.0, UART, HSPI, I2C, I2S, IRDA, GPIO, PWM
<b>Amount of Pins</b>	Total: 18, GPIO: 10

### NETWORKING DATA

<b>Network</b>	TCP/IP Protocol-Stack, supports antenna diversity
<b>Network Protocols</b>	IPv4, TCP, UDP, HTTP, FTP
<b>Infrastructure-Modes</b>	STA, AP, STA+AP
<b>Encryptions</b>	WEP, TKIP, AES
<b>WiFi</b>	802.11 b/g/n 2.4 GHz - 2.5 GHz (2400M - 2483.5M) (supports WPA, WPA2)
<b>RF Switch</b>	Integrated TR-Switch, Balun, LNA, Power Amplifier
<b>Transmission Modes</b>	STBC, 1x1 MIMO, 2x1 MIMO
<b>Packet Transmission</b>	A-MPDU, A-MSDU, 0,4s guard interval


### OPERATING DATA

<b>Operating Temperature</b>	-40°C - +125°C
<b>Operating Voltage</b>	3.0 - 3.6V
<b>Operating Current</b>	Average: 80mA
<b>Standby Consumption</b>	<1.0mW (DTIM3)
<b>Deep Sleep Power</b>	<10uA
<b>Power Down Leakage Current</b>	<5uA
<b>Output Power</b>	+20dBm (im 802.11b Mode)



## PIN ASSIGNMENT

No.	Name	Function
1	RST	Reset the module
2	ADC	A/D Conversion result Input voltage range: 0 - 1V Scope: 0-1024
3	EN	Chip Enable Pin (Active High)
4	GPIO16	GPIO16, activation from deep sleep mode
5	GPIO14	GPIO14, HSPI_CLK
6	GPIO12	GPIO12, HSPI_MISO
7	GPIO13	GPIO13, HSPI_MOSI, UART0_CTS
8	VCC	3,3V
9	CS0	Chip selection
10	MISO	Slave-Output, Main-Input
11	GPIO9	GPIO9
12	GPIO10	GPIO10
13	MOSI	Main-Output, Slave-Input
14	SCLK	Clock
15	GND	GND
16	GPIO15	GPIO15, MTDO, HSPICS, UART0_RTS
17	GPIO2	GPIO2, UART1_RXD
18	GPIO0	GPIO0
19	GPIO4	GPIO4



## OTHER DATA

<b>Mobile Devices</b>	Supports Smart Link for Android and iOS devices
<b>Other Features</b>	Wakes up and transmits packets in: <2ms Firmware upgrade via UART Download and OTA Supports cloud server development
<b>Scope of Delivery</b>	ESP-12F
<b>EAN</b>	4250236816999