



**Residual current circuit breaker (RCCB), 80A, 4p, 300mA, type A**



**Part no.** PXF-80/4/03-A  
**Catalog No.** 102879

Similar to illustration

**Delivery program**

|                              |                |      |  |
|------------------------------|----------------|------|--|
| Basic function               |                |      | Residual current circuit-breakers                      |
| Number of poles              |                |      | 4 pole   |
| Application                  |                |      | Switchgear for residential and commercial applications |
| Rated current                | $I_n$          | A    | 80   |
| Rated short-circuit strength | $I_{cn}$       | kA   | 10   |
| Rated fault current          | $I_{\Delta N}$ | A    | 0.3  |
| Type                         |                |      | Type A   |
| Tripping                     |                | s... | non-delayed  |
| Product range                |                |      | PIX  |
| Sensitivity                  |                |      | Pulse-current sensitive                                |
| Impulse withstand current    |                |      | Partly surge-proof 250 A                               |

**Technical data**

**Electrical**

|  |                      |      |                         |
|--|----------------------|------|-------------------------|
| Standards  |                      |      | IEC/EN 61008            |
| Rated operational voltage  | $U_e$                | V    |                         |
|  | $U_e$                | V AC |                         |
| Rated operating voltage  | $U_e$                | V AC | 230/400                 |
| Rated frequency  | f                    | Hz   | 50                      |
| Limit values of the operating voltage  |                      |      |                         |
| Test circuit   |                      | V AC | 184 - 440               |
| Sensitivity  |                      |      | Pulse-current sensitive |
| Rated insulation voltage   | $U_i$                | V    | 440                     |
| Rated impulse withstand voltage  | $U_{imp}$            | kV   | 4                       |
| Rated short-circuit strength   | $I_{cn}$             | kA   | 10                      |
| Rated making and breaking capacity / Rated residual making and breaking capacity | $I_m / I_{\Delta m}$ | A    | 800                     |
| lifespan   |                      |      |                         |
| Electrical   | Operations           |      | $\geq 4000$             |
| Mechanical   | Operations           |      | $\geq 20000$            |

**References**

|   |  |  |                    |
|---|--|--|--------------------|
| Auxiliary switch for subsequent installation        |  |  | Z-HK 248432        |
| Tripping signal contact for subsequent installation |  |  | Z-NHK 248434       |
| Remote control and automatic switching device       |  |  | Z-FW/LP 248296     |
| Compact enclosure                                   |  |  | KLV-TC-4 276241    |
| Switching interlock                                 |  |  | IS/SPE-1TE 101911  |
| Sealing cover set                                   |  |  | Z-RC/AK-4MU 101062 |

**Mechanical**

|                          |  |    |   |
|--------------------------|--|----|---|
| Standard front dimension |  | mm | 45  |
| Device height            |  | mm | 80  |
| Built-in width           |  | mm | 70 (4TE)  |
| Mounting                 |  |    | Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715 |
| Degree of Protection     |  |    | IP20, IP40 with suitable enclosure                                |
| Terminals top and bottom |  |    | Open mouthed/lift terminals                                       |
| Terminal protection      |  |    | DGUV VS3, EN 50274  |
| Terminal cross-section   |  |    |   |

|  |                 |   |
|--|-----------------|---|
| Solid  | mm <sup>2</sup> | 1.5 - 35  |
| Stranded                                       | mm <sup>2</sup> | 2 x 16  |
| Thickness of busbar material                   | mm              | 0.8 - 2   |
| Permissible storage and transport temperatures | °C              | -35 - +60   |
| Climatic proofing                              |                 | 25-55°C/90-95% relative humidity according to IEC 60068-2 |

## Design verification as per IEC/EN 61439

| Technical data for design verification   |                   |    |   |
|--|-------------------|----|---|
| Rated operational current for specified heat dissipation   | I <sub>n</sub>    | A  | 80  |
| Heat dissipation per pole, current-dependent   | P <sub>vid</sub>  | W  | 0   |
| Equipment heat dissipation, current-dependent  | P <sub>vid</sub>  | W  | 11.4  |
| Static heat dissipation, non-current-dependent   | P <sub>vs</sub>   | W  | 0   |
| Heat dissipation capacity  | P <sub>diss</sub> | W  | 0   |
| Operating ambient temperature min.   |                   | °C | -25   |
| Operating ambient temperature max.   |                   | °C | 60  |
|  |                   |    | Starting at 40 °C, the max. permissible continuous current decreases by 1.2% for every 1 °C |
| IEC/EN 61439 design verification   |                   |    |   |
| 10.2 Strength of materials and parts   |                   |    |   |
| 10.2.2 Corrosion resistance  |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.2.3.1 Verification of thermal stability of enclosures   |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects           |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.2.5 Lifting   |                   |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |                   |    |   |
| 10.2.6 Mechanical impact   |                   |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |                   |    |   |
| 10.2.7 Inscriptions  |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.3 Degree of protection of ASSEMBLIES  |                   |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |                   |    |   |
| 10.4 Clearances and creepage distances   |                   |    |   |
| Meets the product standard's requirements.   |                   |    |   |
| 10.5 Protection against electric shock   |                   |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |                   |    |   |
| 10.6 Incorporation of switching devices and components   |                   |    |   |
| Does not apply, since the entire switchgear needs to be evaluated.   |                   |    |   |
| 10.7 Internal electrical circuits and connections  |                   |    |   |
| Is the panel builder's responsibility.   |                   |    |   |
| 10.8 Connections for external conductors   |                   |    |   |
| Is the panel builder's responsibility.   |                   |    |   |
| 10.9 Insulation properties   |                   |    |   |
| 10.9.2 Power-frequency electric strength   |                   |    |   |
| Is the panel builder's responsibility.   |                   |    |   |
| 10.9.3 Impulse withstand voltage   |                   |    |   |
| Is the panel builder's responsibility.   |                   |    |   |
| 10.9.4 Testing of enclosures made of insulating material   |                   |    |   |
| Is the panel builder's responsibility.   |                   |    |   |
| 10.10 Temperature rise   |                   |    |   |
| The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |                   |    |   |
| 10.11 Short-circuit rating   |                   |    |   |
| Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |                   |    |   |
| 10.12 Electromagnetic compatibility  |                   |    |   |
| Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |                   |    |   |
| 10.13 Mechanical function  |                   |    |   |
| The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |                   |    |   |

## Technical data ETIM 7.0

| Circuit breakers and fuses (EG000020) / Residual current circuit breaker (RCCB) (EC000003)  |    |  |     |
|---|----|--|-----|
| Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) (ecl@ss10.0.1-27-14-22-01 [AAB906014]) |    |  |     |
| Number of poles   |    |  | 4   |
| Rated voltage   | V  |  | 400 |
| Rated current   | A  |  | 80  |
| Rated fault current   | mA |  | 300 |
| Rated insulation voltage U <sub>i</sub>   | V  |  | 440 |
| Rated impulse withstand voltage U <sub>imp</sub>  | kV |  | 4   |

|  |  |                 |          |
|--|--|-----------------|----------|
| Mounting method                                    |  |                 | DIN rail |
| Leakage current type                               |  |                 | A        |
| Selective protection                               |  |                 | No       |
| Short-time delayed tripping                        |  |                 | No       |
| Short-circuit breaking capacity (I <sub>cn</sub> ) |  | kA              | 10       |
| Surge current capacity                             |  | kA              | 0.25     |
| Frequency  |  |                 | 50 Hz    |
| Additional equipment possible                      |  |                 | Yes      |
| With interlocking device                           |  |                 | Yes      |
| Degree of protection (IP)                          |  |                 | IP20     |
| Width in number of modular spacings                |  |                 | 4        |
| Built-in depth                                     |  | mm              | 70.5     |
| Ambient temperature during operating               |  | °C              | -25 - 60 |
| Pollution degree                                   |  |                 | 2        |
| Connectable conductor cross section multi-wired    |  | mm <sup>2</sup> | 1.5 - 16 |
| Connectable conductor cross section solid-core     |  | mm <sup>2</sup> | 1.5 - 35 |