

Contactor relay, 22E, EN 50011, 2 NO + 2 NC flat connector terminal  
AC operation 120 V AC 60 Hz/110 V AC 50 Hz !!! Phased-out  
product !!! Successor is SIRIUS 3RH21



Figure similar

<b>Product designation</b>	Auxiliary contactor
<b>Product type designation</b>	3TH2
<b>Size of contactor</b>	0
Protection class IP on the front	IP00
<b>Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750</b>	K
<b>Reference code acc. to DIN EN 81346-2</b>	K
<b>Reference code acc. to DIN EN 61346-2</b>	K
<b>Type of voltage of the control supply voltage</b>	AC
<b>Control supply voltage at AC</b>	
• at 50 Hz rated value	110 V
• at 60 Hz rated value	120 V
<b>Control supply voltage frequency</b>	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
<b>Number of NC contacts for auxiliary contacts</b>	2
• delayed switching	0
• lagging switching	0

• make-before-break switching	0
<b>Number of NO contacts for auxiliary contacts</b>	2
• delayed switching	0
• leading contact	0
• make-before-break switching	0
Number of CO contacts for auxiliary contacts	0
<b>Identification number and letter for switching elements</b>	22 E
<b>Operating current at AC-15</b>	
• at 230 V rated value	4 A
• at 400 V rated value	3 A
<b>Mounting type</b>	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
<b>Height</b>	48 mm
<b>Width</b>	45 mm
<b>Depth</b>	64.5 mm
Type of electrical connection for auxiliary and control current circuit	tab terminals 2x 2.8 mm
B10 value with high demand rate acc. to SN 31920	400 000; With 0.3 x Ie
<b>T1 value for proof test interval or service life acc. to IEC 61508</b>	20 y
<b>Protection against electrical shock</b>	finger-safe

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH2022-1AK6>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH2022-1AK6>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2022-1AK6>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TH2022-1AK6&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH2022-1AK6&lang=en)

##### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2022-1AK6/char>

##### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TH2022-1AK6&objecttype=14&gridview=view1>

last modified:

09/13/2019