# **SIEMENS**

Data sheet 3NE1222-4

PV fuse link, with blade contacts, NH1, In: 125 A, gPV, Un DC: 1000 V, front indicator



Model	
Product brand name	SENTRON
Product designation	PV fuse link
Design of the product	With blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	Non-corroding, silver-plated
Design of the fuse link	Photovoltaic fuse, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH1
Operating class of the fuse link	gPV
Varying load factor (WL)	1
Supply voltage	
Type of voltage	DC
Current / at AC / rated value	125 A
Supply voltage	
• at DC	1 000 V
Switching capacity	
Switching capacity current	

• at DC / acc. to IEC 60947-2 / rated value	30 kA	
---	-------	--

Dissipation  Power loss IMI	26 W
Power loss [W] Power loss [W]	20 VV
for rated value of the current / at AC / in hot operating state / per pole	26 W
• maximum	26 W
• maximum  Product details	26 W

Product description Not non-interchangeable

## Mechanical Design

Mounting position Any, preferably vertical

• acc. to DIN EN 81346-2

Ambient temperature -20 ... +50 °C

**Environmental category** -20 to +50 at 95% relative humidity

### Certificates

Reference code

F • acc. to DIN EN 61346-2 F

**Declaration of Conformity** other



Miscellaneous

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1222-4

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3NE1222-4

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3NE1222-4

**CAx-Online-Generator** 

http://www.siemens.com/cax

**Tender specifications** 

http://www.siemens.com/specifications