SIEMENS

## Data sheet 5SU1354-0KK32

RCBO, 10 kA, 1P+N, Type AC, 30 mA, B char., In: 32 A, Un AC: 230 V

| Model | |
|---|---|
| Product brand name | SENTRON |
| Product designation | RCBO |
| Design of the product | Instantaneous |

| General technical data | |
|---|---|
| Number of poles | 2 |
| Number of poles / Note | 1P+N |
| Number of poles / with protection | 1 |
| Tripping characteristic class | B |
| circuit-breaker / Design | 5SU1 |
| Mechanical service life (switching cycles) / typical | 10 000 |
| Overvoltage category | III |

| Voltage | |
|---|---|
| Surge current resistance / at (8/20) µs | 1 kA |

| Supply voltage | |
|---|---|
| Type of voltage | AC |
| Current / at AC / rated value | 32 A |
| Supply voltage | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| • for testing equipment / minimum | 195 V |
| Supply voltage frequency / rated value | 50 Hz |

## Protection class

| | |
|---|---|
| Protection class IP | IP20, if the distribution board is installed, with connected conductors |

## Switching capacity

| | |
|---|---|
| Breaking capacity short-circuit current (Icn) / according to EN 61009-1 / rated value | 10 kA |
| Switching capacity current | |
| • acc. to EN 60898 / rated value | 10 kA |
| • acc. to IEC 60947-2 / rated value | 15 kA |
| Rated residual switching capacity (IΔm) / according to IEC 61009-1 | 10 kA |
| Energy limiting class | 3 |

## Dissipation

| | |
|---|---|
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 5.7 W |

## Current

| | |
|---|---|
| Tripping residual current / rated value | 30 mA |
| Tripping residual / rated value / derated current | |
| • at 30 Cel | 32 A |
| • at 40 Cel | 30.4 A |
| • at 45 Cel | 29.76 A |
| • at 50 Cel | 28.8 A |
| • at 55 Cel | 27.84 A |
| • at 60 Cel | 27.2 A |
| • at 65 Cel | 25.92 A |
| • at 70 Cel | 24.64 A |
| Type of fault current | AC |

## Product details

| | |
|---|---|
| Product function / neutral conductor switching | Yes |
| Product feature / Touch protection | Yes |
| Product feature | |
| • halogen-free | Yes |
| • silicon-free | Yes |

## Connections

| | |
|---|---|
| • Connectable conductor cross-section | |
| — solid | 0.75 ... 35 mm² |
| — stranded | 0.75 ... 35 mm² |
| • Connectable conductor cross-section / finely stranded / with core end processing | 0.75 ... 25 mm² |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| Tightening torque / with screw-type terminals | 2.5 ... 3 N·m |
| Position / of power supply cord | Either top or bottom |

## Mechanical Design

| | |
|---|---|
| Height | 90 mm |
| Width | 36 mm |
| Depth | 77 mm |
| Installation depth | 70 mm |
| Number of width units | 2 |
| Mounting position | any |
| Net weight | 289 g |

## Environmental conditions

| | |
|---|---|
| Influence of the surrounding temperature | Max. 95% humidity |
| Ambient temperature | -25 ... +55 °C |
| • during storage | -40 ... +75 °C |

## Certificates

| | |
|---|---|
| Reference code | |
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

| General Product Approval | | | | Declaration of Conformity | Test Certificates |
|---|---|---|---|---|---|
| CCC | IMQ | Miscellaneous | RCM | EG-Konf. | Special Test Certificate |

| Test Certificates | other | Railway | |
|---|---|---|---|
| Miscellaneous | Miscellaneous | Vibration and Shock | Confirmation |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,…)**
http://www.siemens.com/lowvoltage/catalogs

**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1354-0KK32

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/5SU1354-0KK32

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-0KK32

**CAx-Online-Generator**
http://www.siemens.com/cax


Subject to change without notice
© Copyright Siemens








Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens