

MINIZED, Switch disconnecter with Fuse, D02, 3-pole, In: 63 A, Un AC: 400 V, for Busbar system 8US 60 mm



Model	
Product brand name	MINIZED
Product designation	Switch disconnectors with fuses
Design of the product	For 60 mm 8US busbar system
General technical data	
Number of poles	3
Size of fuse system / acc. to DIN EN 60269-1	D02
Voltage	
Surge voltage resistance / rated value	6 kV
Supply voltage	
Current / at AC / rated value	63 A
Operating voltage / at AC / rated value	400 V
Protection class	
Protection class IP	IP20, with connected conductors
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	4.5 W

## Product details

Product feature / sealable Yes

## Mechanical Design

Height	100 mm
Width	27 mm
Depth	219 mm
Mounting position	any, preferably vertical
Net weight	688 g

## Certificates

Reference code

- acc. to DIN EN 61346-2 F
- acc. to DIN EN 81346-2 F

### General Product Approval

### Declaration of Conformity



## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7230>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG7230>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SG7230](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG7230)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



