

SAIH-CD-2x0.34/2x0.22-PUR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Weidmüller offers a large and comprehensive range of sensor-actuator cables. We provide both, sensor cables as well as bus and valve cables of various sizes and lengths. If you cannot find a specific product or a product in the desired length, just contact us.

General ordering data

Type	SAIH-CD-2x0.34/2x0.22-PUR
Order No.	1058630000
Version	Bus line, No. of poles: 5, Shielded: Yes, LED: No, Sheath material: PUR, Halogen: No
GTIN (EAN)	4032248800322
Qty.	100 m

SAIH-CD-2x0.34/2x0.22-PUR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight 7.5 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

Number of poles	5	Wire cross section	2 x 0.34 mm ² + 2 x 0.22 mm ²
Outside diameter	7 ± 0.3 mm	Shielded	Yes
Insulation	TPE	Colour coding	white, blue, red, black
Sheath material	PUR	Sheathing colour	black
Halogen	No	Temperature range, moving	-10...80 °C
Temperature range, stationary	-40...80 °C	Outer cladding in accordance with UL AWM style	20236 (80 °C / 30 V)
Suitable for cable carriers	Yes	Bending radius, min., stationary	5 x cable diameter
Bending radius, min., moving	10 x cable diameter	Acceleration	5 m/s ²
Speed	180 m/min	Bending cycles	3 Mio
Resistant to welding beads	No	Hybrid cable	No
Irradiation crosslinked	No	Configurable cable length	No

Classifications

ETIM 6.0	EC000830	eClass 6.2	27-06-91-90
eClass 7.1	27-06-91-90	eClass 8.1	27-06-91-90
eClass 9.0	27-06-18-05	eClass 9.1	27-06-90-90

Approvals

Approvals



ROHS Conform

Downloads
 Brochure/Catalogue [CAT 8 SAI 15/16 EN](#)
[FL FIELDWIRING EN](#)

Data sheet

SAIH-CD-2x0.34/2x0.22-PUR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

