

VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY

"Since 1982, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success."

BS-26 OTG USB ENDOSCOPE

CE
VERSION 12/21

N° 1783918

The product is used in combination with a computer or Android powered Smartphone as a visual aid for the optical troubleshooting and inspection on voltage-free installations and equipment. The endoscope is connected via a USB interface. Six white LEDs enable recordings also in dark areas.

FEATURES:

Use with Computer or Android Smartphone // Color camera //
6 white LEDs for lighting up dark areas // Brightness control //
Mirror, magnet and hook attachments // IP 67 waterproof camera head
and cable //

TECHNICAL DATA:

Input voltage/current	5 V/DC via USB, 200 mA
USB interface	USB 2.0
Camera sensor	CMOS 1/6"
Camera resolution	1600 x 1200 pixels
Video resolution / Frame rate	640 x 480 pixels, 30 FPS (frames per second)
White balance	automatic
Exposure	automatic
Video format	AVI / ASF (Windows®), MP4 (Android)
Photo format	PNG / BMP / JPEG
Camera lighting	6 LEDs, white
LED illuminance	1000 Lux ± 150 at a distance of 20 mm
Bending radius	> 45 mm
Field of view	54°
Focusing	> 30 mm
IP rating	IP67 (camera head and cable)
Supported operating systems	Windows® XP, Vista™, 7, 8, 8.1, 10, or above Android 4.4 (with OTG-function) or above
Operating conditions	0 to +45 °C, 15 - 85 % RH
Storage conditions	-10 to +50 °C, 15 - 85 % RH
Camera head Ø	8 mm
Camera head dimension (L)	4.4 cm
USB cable length	approx. 985 cm (±10 cm)
USB OTG connection cable length	approx. 11.5 cm
Weight	approx. 320 g (without accessories)



PACKAGE CONTENTS:

Endoscope // Attachments (hook, magnet, mirror) //
USB OTG connection cable // Software CD // Operating instructions //