

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





For many years, the name Klippon® has stood for competence and quality in enclosures.

The Klippon® EBi industrial enclosure series protects your components reliably if they are used in moderate environmental conditions and is designed for everyday applications.

With the ever-increasing need for individual application solutions, the Klippon® EBi with its high degree of protection and impact resistance is ideally suited to your needs.

Our standard product is the Klippon® EBi QL – with hinged door and double-bit key lock.

A variant with mounting screws is also available, but is only manufactured on request and is subject to a minimum order quantity. DNV GL and cULus approvals are also available on request.

General ordering data

| Туре | KEBI FS 303015 S2B0 |
|------------|---|
| Order No. | <u>2470920000</u> |
| Version | Klippon EBi FS (Essential Box industrial - Fixing Screw), Empty enclosure, stainless steel enclosure, Height: 299.5 mm, Width: 299.5 mm, Depth: 150 mm, Material: Stainless steel 1.4301 (304), Brushed, silver |
| GTIN (EAN) | 4050118591422 |
| Qty. | 1 pc(s). |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

| Width | 299.5 mm | Width (inches) | 11.791 inch |
|----------------------------|-------------|-----------------------------|-------------|
| Height | 299.5 mm | Height (inches) | 11.791 inch |
| Depth | 150 mm | Depth (inches) | 5.905 inch |
| Mounting dimension - width | 250 mm | Mounting dimension - height | 250 mm |
| Wall thickness, max. | 1.25 mm | Wall thickness, min. | 1.25 mm |
| Net weight | 5,086,000 g | Diameter | 9 mm |

Certificate numbers enclosure

| Certificate no. (cULus) | E256877 |
|-------------------------|---------|

General information

| Areas of use | Harbour facilities, Machine construction, Transportation, Marine | Installation advice | |
|---------------------------------|--|------------------------------|--|
| | engineering, Packaging industry, Process industry | | Welded assembly angle, Mounting plate |
| Material thickness | 1.25 mm | Material thickness of cover | 1.25 mm |
| Material thickness of enclosure | 1.25 mm | Material thickness of flange | 1.25 mm |
| Seal material of cover | Polyurethane foamed | Standards | DIN EN 62208, IEC 60529 |
| Torque for lid screws | 2.5 Nm | Material | Stainless steel 1.4301 (304) |
| Seal material | Polyurethane foamed | Surface finish | Brushed |
| Operating temperature, min. | -40 °C | Operating temperature, max. | 85 °C |
| Impact resistance | 10.00 J | Protection degree | IP66 |
| Enclosure attachment | Fixing lugs, Installation through the housing rear wall | Lid attachment | M6 torx stainless steel screws with slot, Removable cover + M6 screws |
| Integral fixing | Screwed | | |

Housing earth

| Earth, enclosure, cover | Welded-on M6 stainless- steel earth stud in | Earth, enclosure, external | |
|----------------------------|--|----------------------------|--------------------|
| | enclosure body and lid. | | M6 earth tab rivet |
| Earth, enclosure, internal | Welded-on M6 stainless- | | |
| | steel earth stud in enclosure body and lid. | | |

Classifications

| ETIM 6.0 | EC000261 | eClass 6.2 | 27-14-91-07 |
|------------|-------------|------------|-------------|
| eClass 9.0 | 27-18-01-01 | eClass 9.1 | 27-18-92-90 |

Product information

| Product information | Minimum order quantity (50 pieces) |
|---------------------|------------------------------------|



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

Dimensioned drawing

