Cabtite (cable entry system)
CABTITE SE 21-22 LRG BK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Whether a large or small cable diameter – Cabtite always offers the right seal insert.
The conical shape of the sealing elements allows the previously positioned snap-in grid inlays to be pushed in easily from the inside to the outside, it reliably seals intermediate spaces and provides strain relief in accordance with DIN EN 62444. The seal inserts combined with the frames achieve an IP 66 degree of protection. As a result of its slotted design with wave cut, it is especially suitable for pre-assembled cables.

- The black seal inserts are designed for a particularly high operating temperature and offer fire safety class UL 94 HB
- The grey sealing elements comply with fire safety class UL 94 V0 and are therefore suitable for the demands of the railway industry
- By using multiple inserts, two or more cables, as well as special cables, can be passed through a sealing element

General ordering data

Type	CABTITE SE 21-22 LRG BK
Order No.	2583770000
Version	Sealing element, Cabtite (cable entry system), TPE, Deep black, Height: 17.7 mm, Width: 43.1 mm, Depth: 17.7 mm, -40 °C...120 °C, IP54, IP65, IP66
GTIN (EAN)	4050118616705
Qty.	10 pc(s).

Cabtite (cable entry system)
CABTITE SE 21-22 LRG BK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	43.1 mm	Length (inches)	1.697 inch
Width	43.1 mm	Width (inches)	1.697 inch
Height	17.7 mm	Height (inches)	0.697 inch
Depth	17.7 mm	Depth (inches)	0.697 inch
Net weight	26.3 g		

General information

UL 94 flammability rating	HB	Sealing element	1 large sealing element
Outer cable diameter, min.	21 mm	Outer cable diameter, max.	22 mm
Halogen	No	Silicone	No
Material	TPE		

Classifications

ETIM 6.0	EC000879	eClass 6.2	27-14-92-01
eClass 9.0	27-14-44-21	eClass 9.1	27-14-44-21

Approvals

Approvals	
ROHS	Conform

Downloads

Engineering Data	STEP
User Documentation	Cabtite Installation Instructions