

**WM**  
**WM 2/21 3.5-5.0 MM WS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Un-detachable: WM**

Our closed, un-detachable markers are mounted without the need for additional tools. The cable is simply threaded through the openings at both ends before the cables are fixed in position. The inherent tension of the material fixes the marker in place. WM markers are available in four sizes for conductor cross-sections from 0.25mm<sup>2</sup> to 16mm<sup>2</sup>. Each size comes in three label lengths and two colours. This provides you with just the right assortment for carrying out everyday labelling of conductors in a cabinet.

**Your benefits with MultiMark**

- Compact, practice-oriented range of products
- Quickly printed and assembled
- Reliable identification of your connections
- Excellent material properties

**General ordering data**

|                    |                                                                                  |
|--------------------|----------------------------------------------------------------------------------|
| Type               | WM 2/21 3.5-5.0 MM WS                                                            |
| Order No.          | <a href="#">2006050000</a>                                                       |
| Version            | WM, Conductor and cable markers, 3.5 - 5 mm, 32 x 6.4 mm, white                  |
| GTIN (EAN)         | 4050118390407                                                                    |
| Qty.               | 2,000 pc(s).                                                                     |
| compatible printer | <a href="#">2430920000</a> <a href="#">2448870000</a> <a href="#">1140490000</a> |

**WM**  
**WM 2/21 3.5-5.0 MM WS**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 6.4 mm  | Width (inches)  | 0.252 inch |
| Height     | 32 mm   | Height (inches) | 1.26 inch  |
| Depth      | 0.5 mm  | Depth (inches)  | 0.02 inch  |
| Net weight | 0.174 g |                 |            |

**General data**

|                         |              |                             |               |
|-------------------------|--------------|-----------------------------|---------------|
| Colour                  | white        | Halogen                     | No            |
| Material                | Polyester    | Operating temperature range | -40... 150 °C |
| Size of labelling field | 22 x 6.4 mm  | UL 94 flammability rating   | HB            |
| Version                 | halogen-free | Width                       | 6.4 mm        |

**Conductor and cable markers**

|                               |                     |                               |                   |
|-------------------------------|---------------------|-------------------------------|-------------------|
| Conductor O.D.                | 3.5 - 5 mm          | Conductor O.D., max.          | 5 mm              |
| Conductor O.D., min.          | 3.5 mm              | Conductor cross-section, max. | 4 mm <sup>2</sup> |
| Conductor cross-section, min. | 2.5 mm <sup>2</sup> | Halogen                       | No                |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 5.0   | EC001530    | ETIM 6.0   | EC001530    |
| eClass 6.2 | 27-40-04-01 | eClass 9.0 | 27-40-04-01 |
| eClass 9.1 | 27-40-04-01 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |
| Engineering Data | <a href="#">STEP</a>                     |

### **WM** **WM 2/21 3.5-5.0 MM WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

