

har-speed M12Crimp SlimDesign x-coded



Part number	21 03 881 1805
Specification	har-speed M12Crimp SlimDesign x-coded
HARTING eCatalogue	https://b2b.harting.com/21038811805

Identification

Category	Connector
Series	Circular connectors M12
Identification	M12 Slim Design
Element	Cable connector
Specification	Straight

Version

Termination method	Crimp termination
Gender	Male
Locking type	Screw locking
Shielding	Shielded
Number of contacts	8
Coding	X-coding
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.08 ... 0.25 mm ²
Conductor cross-section	AWG 28 ... AWG 23
Wire outer diameter	≤1.4 mm
Rated current	0.5 A
Rated voltage	48 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	≥10 ⁸ Ω
Contact resistance	≤10 mΩ
Ambient temperature	-40 ... +85 °C -5 ... +50 °C During connection
Tightening torque	0.6 Nm



Pushing Performance

Technical characteristics

Wrench size	A/F 15 Knurled screw / knurled nut
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 when mated IP67 when mated
Cable diameter	5.7 ... 8.8 mm
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Overvoltage category	III
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	LCP
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

UL / CSA	UL 2238 CYJV2.E302521 CSA-C22.2 No. 182.3 CYJV8.E302521
----------	--

Commercial data

Packaging size	10
Net weight	36 g
Country of origin	Romania
Customs tariff number	85366990