

Han-Eco Mod.10-HCC-M32



Part number	19 41 010 0722
Specification	Han-Eco Mod.10-HCC-M32
HARTING eCatalogue	https://b2b.harting.com/19410100722
Identification	
Category	Hoods/Housings
Series of hoods/housingsHan-Eco [®] Modular	
Type of hood/housing	Cable to cable housing

Version

Locking type	Double locking lever
Size	10 B
Version	Top entry
Cable entry	1x M32

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65

Material properties

Material (hood/housing)	Polyamide Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Colour (seal)	RAL 9005 (jet black)
Material (locking)	Polyamide Fibre-glass reinforced
Colour (locking)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No

Page 1 / 2 | Creation date 2018-09-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 19 41 010 0722 Han-Eco Mod.10-HCC-M32



Material properties

REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	IEC 61984	
	EN 45545-2 R22: HL1, HL2, HL3	
	EN 45545-2 R23: HL1, HL2, HL3	
	EN 45545-2 R24: HL1, HL2, HL3	
111 / 000	UL 1977 ECBT2.E235076	
UL / CSA	CSA-C22.2 No. 182.3 ECBT8.E235076	
Commercial data		

Packaging size	1
Net weight	151.4 g
Country of origin	Germany
Customs tariff number	85389099