



Pushing Performance

## Han 3A-HTE, 9-17mm, PC black +glued seal



Part number	19 20 003 0418
Specification	Han 3A-HTE, 9-17mm, PC black +glued seal
HARTING eCatalogue	<a href="https://b2b.harting.com/19200030418">https://b2b.harting.com/19200030418</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han A®
Type of hood/housing	Hoods
Description of hood/housing	With glued seal With integrated cable gland Black

### Version

Locking type	Single locking lever
Size	3 A
Version	Top entry
Cable entry	1x Integrated
Field of application	Standard Hoods/housings for industrial applications

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP44 IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	4 4X 12
Cable diameter	9 ... 17 mm

### Material properties

Material (hood/housing)	Polycarbonate
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material flammability class acc. to UL 94	V-0



Pushing Performance

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	10
Net weight	18.4 g
Country of origin	Germany
Customs tariff number	85389099