



Isolating blade set, D02, 63A, 400 V

Part no. Z-SLS/TR-SET  
 Catalog No. 100660

### Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Disconnecter kit
For use with			Z-SLS/NEOZ Z-SLK/NEOZ Z-SLS/CEK
			Snap-fit on DIN rail 1 set consists of: 3 switch conversion sets, 3 current codings, 1 plastic box The fuse switch-disconnector is thus converted to a switch-disconnector
Rated uninterrupted current	$I_u$	A	63

### Technical data

#### Electrical

Rated operational voltage	$U_e$	V	
Rated operating voltage	$U_e$	V AC	400
Test voltage		kV	5
Rated uninterrupted current	$I_u$	A	63

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	63
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	1
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])			
Type of accessory			Contact set