



Dual Lock™ Reclosable Fastener SJ3870

Product Data Sheet

September 2022
Supersedes: January 2017

Product Description

3M™ Dual Lock™ Reclosable Fastener SJ3870 contains a modified acrylic adhesive. The fastener consists of continuous strips of polyolefine with 250 polyolefine stems per square inch having a mushroom shaped top.

Key Features

- Modified acrylic adhesive bonds to medium to high surface energy substrates (e.g. metal, ABS)
- Stem density: 250 stems/in²
- Closure cycle life > 1 000
- Mushroom shaped stems snap in place to ensure fastener is engaged
- Good aging performance and resistance against humidity
- Good initial adhesion
- Quick and easy to install
- Durable for indoor and outdoor applications

Physical Properties

Type	SJ3870
Adhesive Type	Modified acrylic adhesive
Tape Colour	Black
Backing	Black polypropylene
Stems	Black polypropylene
Release Liner	3M branded filmic liner
Engaged Thickness acc. DIN EN 1942: 2008	5.8 mm

Performance Characteristics

Type	SJ3870
90 ° Peel adhesion to Stainless Steel acc. to ISO 29862:2007, 90 ° peel angle @ RT, after 72h @ RT dwell	42 N/cm
90 ° Peel adhesion to PP acc. to ISO 29862:2007, 90 ° peel angle @ RT, after 72h @ RT dwell	3 N/cm
90 ° Peel adhesion to ABS acc. to ISO 29862:2007, 90 ° peel angle @ RT, after 72h @ RT dwell	53 N/cm
90 ° Peel adhesion to Stainless Steel acc. to ISO 29862:2007, 90 ° peel angle @ RT, after 72h @ RT dwell and after 10d @ 38 °C & 98 % rH	33 N/cm
Dyn. Tensile Engagement Strength acc. to ASTM D897-08, tested @ RT	113 N/in ²
Dyn. Tensile Disengagement Strength acc. to ASTM D897-08, tested @ RT	231 N/in ²
Dyn. Tensile Disengagement Strength acc. to ASTM D897-08, tested @ 70 °C	72 kPa
Dynamic Shear – Max. Force acc. ISO 29863:2007 to aluminium	83 kPa
Dynamic Shear – Elongation acc. ISO 29863:2007 to aluminium	69 %
Static Shear Strength Stainless Steel ISO 29863:2007, after 72h @ RT dwell (Holds minimum 77.5 g/cm ² for 10.000 minutes)	23 ° C – 500 g 70 ° C – 500 g
„T“ Peel (flexible to flexible) acc. ISO 29862:2007	50 N/cm

Storage & Shelf Life

Store at 16 °C – 25 °C and 40 – 65 % relative humidity in its original box. The product can be stored up to 24 months after production.

Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or humidity.

For Additional Information

To request additional product information or to arrange for sales assistance, call.....
Address correspondence to: 3M

Automotive Disclaimer

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

3M United Kingdom PLC
2M Centre, Cain Road, Bracknell
RG12 8HT
United Kingdom

3M Svenska AB
Herrjärva torg 4
170 67 Solna
Sweden

3M Eesti OÜ
Pärnu mnt. 158
11317 Tallinn
Estonia

3M Ireland Ltd
The Iveagh Building, 3rd Floor
The Park, Carrickmines 18
Ireland

3M a/s
Hannemanns Allé 53
DK-2300 Copenhagen S.
Denmark

3M Latvia SIA
K.Ulmaņa gatve 5
Rīga, LV-1004
Latvia

3M Belgium bvba/sprl
Hermeslaan 7
1831 Diegem
Belgium

3M Norge AS
Tærudgata 16
2004 Lillestrøm
Norway

3M Lietuva UAB
A.Goštauto g. 40
Vilnius LT- 03163
Lithuania

3M Nederland B.V.
Molengraaffsingel 29
2629 JD Delft
The Netherlands

Suomen 3M Oy
Keilaranta 6
02150 Espoo
Finland