



Starter package consisting of EASY-E4-UC-12RC1, XV-102-A0-35TQRB-1E4, Ethernet switch, 3xPatch cable, license easySoft 7



Part no. XV100-BOX-E4-UC1
Catalog No. 198515

Delivery program

Product range		Control relays easyE4
Basic function		Starter kit
Included devices		
Y7-197211 EASY-E4-UC-12RC1 Y7-198513 XV-102-A0-35TQRB-1E4 Y7-197226 EASYSOFT-SWLIC		easyE4 base unit Touchdisplay Software license Ethernet-Switch 3 x patch cables
Supply voltage		12/24 V DC 24 V AC
Software		EASYSOFT-SWLIC/easySoft 7 SW-GALILEO/Galileo 10

Design verification as per IEC/EN 61439

Technical data for design verification			
Static heat dissipation, non-current-dependent	P _{vs}	W	8
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	50
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Approvals

Product Standards		UL 60950-01; CSA-C22.2 No. 60950-1; IEC/EN 61131-2; CE marking
UL File No.		E208621
North America Certification		UL recognized, certified by UL for use in Canada

Conditions of Acceptability			<p>The investigated Pollution Degree is: 2</p> <p>The following end-product enclosures are required: Fire</p> <p>The unit must be supplied via a SELV source.</p> <p>The provided Ethernet Connection is only allowed to connect to inhouse networks.</p>
Specially designed for North America			No
Current Limiting Circuit-Breaker			No
Degree of Protection			IEC: IP20, UL/CSA Type: -