

KERN PNS600-3

The new standard in the laboratory with robust tuning fork measuring system



Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	5 °C

Power supply

Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US

Service

DAkkS Certificate:	963-127
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	321 x 410 x 329 mm
Gross weight:	5,100 kg
Net weight:	2,090 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	196 x 293 x 266 mm
Draft shield optional:	yes
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	196 x 293 x 266 mm
Revolving screw feet:	yes
Weighing space (WxDxH):	172 x 171 x 160 mm
Weighing surface (d):	140

Measuring system

Adjustment options:	External calibration
Linearity:	4 mg
Minimum weight (USP):	2 g
Readability [d]:	1 mg
Recommended adjusting weight:	600 g (E2)
Repeatability:	1 mg
Resolution:	620000
Stabilisation time under laboratory conditions:	3 s
Tare range:	620 g
Warm up time:	4 h
Weighing capacity [Max]:	620 g
Weighing units:	ct dwt g lb mo oz oz t (HK) tl (Singap. Malays) tl (Tw) tol

Display

Display digit height:	1,650 cm
-----------------------	----------

Counting

Counting resolution:	620000
Minimum piece weight at piece counting (Laboratory):	1 mg
Minimum piece weight at piece counting (Normal):	10 mg

Functions

Counting function:	yes
Percentage determination:	yes
Weighing with tolerance range:	yes


KERN PNS600-3



The new standard in the laboratory with robust tuning fork measuring system

Piktogramme

STANDARD



OPTION



FACTORY

