IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

Name/Description of battery					
1. Name/Description of battery					
1a. Name/Desc	ription of the cells inside t	the batteru			
101 11011107 2000	prion or the conto more	5 5 5 6 6 7			
The test summar	u of the cells inside the hat	tery must either be presented or und	der checknoint 9 and 9a i	t must	
be confirmed tha	t the UN 38.3 test summar	ry for the cells is available.	aci checkpoint o dha oa i	t mast	
2. Manufacture	er of battery				
Name					
Address					
Phone					
Email					
Website					
2a. Manufacture	er of the equipment (if the t	battery is contained in equipment)			
Name					
Address					
Phone					
Email					
Website					
3. Test laborate	ory of battery				
Name					
Address					
Phone					
Email					
Website					
4. ID-number a	and date				
Unique test repo	ort identification number		Date of test report		



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)					

#### **DESCRIPTION OF BATTERY**

5. M	ark the type of battery with an "•"				
	Lithium ion battery	Lithium metal b	attery		
	Lithium hybrid battery				
		•			
6. Pa	nrameters				
Mass	in gram (g):				
Lithiu	m ion: Indicate watt-hour rating (Wh):				
Lithiu	m metal: Indicate lithium metal content in gram (g):				
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):					
Element rigoria. Indicate utiliani metat content in grant (g) and water hour rating (vvii).					
7 0	tl.da.a.dalla.a.dh.alla.a.				
7. Pl	nysical description of battery				
8. M	odel numbers				

### **TESTS AND RESULTS**

9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail
T1 - Altitude simulation			
T2 - Thermal Test			
T3 - Vibration			
T4 - Shock			
T5 - External Short Circuit			
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.			
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.			
T7 - Overcharge			
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.			



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

9a.UN 38.3 Test Confirmation for the Cells inside the battery

When no separate document for the cells is provided, this confirms that

Name/Description of battery (taken from field 1)

Cell

the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.	UN 38 confirm	3.3 Test ned	UN 38.3 confi	Test NOT rmed	
needs to be dished.					
10. Reference to assembled battery testing requirements					
				N/A	
4. 5.4					
11. Reference to the revised edition of the Manual of Tests and Criteria used a	ind to amend	ments th	ereto		
ADDITIONAL SUPPLIER INQUIRY					
12. Quality management system for manufacturing batteries  Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?	?		YES	NO	
13. Are the following parameters exceeded?  Lithium ion battery: more than 100 Wh  Lithium metal battery: more than 2 g Lithium  Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh			YES	NO	
Check point 14 – 16 need to be answered when 13 has been ticked "YES":					
<b>14.</b> Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?			YES	NO	
15. Is each battery equipped with an effective means of preventing external shor	t circuits?		YES	NO	
<b>16.</b> Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	N/	'A	YES	NO	
17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batte	eries and lith	ium polyr	mer batte	ries	
State of Charge (SoC) max. 30 %	N/	Ά	YES	NO	

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)					

### BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:						
18.a) Only button cells enclosed?				YES	NO	
18.b) Number of enclosed batteries per equipment						
When the equipment is intentionally active/switched on during transport e.g. data loggers:						
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A YES				NO		
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160		N/A		YES	NO	

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
		CHOLOGA
		志康科技工