





Specification


*1) Rev.1 | 04.05.23 | techn. Details

Power Socket
CEE 7/7; IP 54; 16 A / 250 V / max. 3680 W
 screw type,
 splash-proof,
 suitable for industry / building site,
 resilient high-performance plastic,
 black / red

*1



Stripping length recommendation



O.D. range of the cable

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

本文未经许可不得转让及翻印，不允许引用或转载其内容，违者必纠，并须赔偿损失。保留专利及试样注册的所有权。

REACH: Must be fully comply with EC 1907/2006 concerning the Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) and must not contain any of the Substances of Very High Concern (SVHC) above the specified concentrations, as defined in Article 57 and Annex XIV (including all amendments) or any of the restricted substances, as defined in Article 67 and Annex XVII (including all amendments).

VerpackG: According to the Packaging Act (VerpackG), the cumulative concentration of lead, cadmium, mercury and hexavalent chromium does not exceed 100 mg per kg.

RoHS: All Materials must be in accordance with 2011/65/EU and 2015/863/EU.

	Date	Name	Designation:
Prep.:	20.07.22	Ro	
Check.:			
Rev.			
Approv.			
transmedia keep in contact			TRANSMEDIA-No.:
			Power Socket
			NV 48 KL
			Page: 1
			Page tot.: 1

04.05.2023

X Rosenzweig

Signiert von: transmedia.rosenzweig

Rev.1 OK 04.05.2023 Ro