LogiLink®

Compact 48W USB-C™ GaN 2-Port Wall Charger

1 x USB-A & 1 x USB-C™

Art. No.: **PA0230**

High Efficiency USB-C wall charger with GaN technology to charge your smartphones, tablets and laptops at full speed; compact size to carry anywhere.

Built-in GaN Technology

By replacing the silicon wafer with gallium nitride (GaN), it takes performance to new heights with faster speeds and greater efficiency.

Up to 45W with USB-C Port

Up to 45W when only charging through the USB-C port, and up to 48W when charging through both ports.

RoHS compliant   CE

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

PA0230

4 052792 057744

Made in China

LogiLink®

Compact 48W USB-C™ GaN 2-Port Wall Charger

1 x USB-A & 1 x USB-C™

Art. No.: **PA0230**

Compact Design, Ultra-Powerful

Easy to carry with high output for laptops/ smartphones, simplify and save space in your luggage while traveling.

Protection Against
- ☑ Overcurrent
- ☑ Overvoltage
- ☑ Overheating
- ☑ Short Circuit

Multiple Protection

Supports overcurrent, overvoltage, overheating and short circuit protection.

RoHS compliant CE

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

PA0230

4 052792 057744

Made in China

LogiLink®

Compact 48W USB-C™ GaN 2-Port Wall Charger
1 x USB-A & 1 x USB-C™

Art. No.: PA0230

Wide Compatibility

Compatible with most mobile devices: smartphones, tablets, laptops and much more.

Specification:

Input	100-240V AC 50/60Hz 1A max.
Output Power	USB-A: 5V 3A (15W) / 9V 2A (18W) / 12V 1.5A (18W) max. USB-C: 5V 3A (15W) / 9V 3A (27W) / 15V 2A (30W) 20V 1.5A (30W) max. USB-C: 5V 3A (15W) / 9V 3A (27W) / 15V 3A (45W) 20V 2.25A (45W) max. *USB-A: no load
Protections	Overcurrent, overvoltage, overheating and short circuit
Operating Temperature	0~25°C
Storage Temperature	-20~85°C
Operating Relative Humidity	20%~90% (non-condensing)
Storage Relative Humidity	5%~95% (non-condensing)
Dimension	92 x 36.4 x 40mm
Weight	120g

Best Connectivity

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

PA0230

4 052792 057744

Made in China

LogiLink®

Compact 48W USB-C™ GaN 2-Port Wall Charger
1 x USB-A & 1 x USB-C™

Art. No.: PA0230

INPUT 100-240V AC | **OUTPUT** 48W max | OCP OVP OTP Protection | **Fast Charging**

Package Contents:
» 1 x USB-C GaN Wall Charger
» 1 x User Manual

Package Information:
» Packing Dimension: mm
» Packing Weight: kg
» Carton Dimension: 0mm
» Carton Q'ty: pcs
» Carton Weight: kg

Best Connectivity

RoHS compliant CE

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

PA0230
4 052792 057744
Made in China