LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

f Product cell logical Development r f cell com date QAE-EF02-150824-CY1 D15. 08. 24		anjing,		
r f cell Com Jate QAE-EF02-150824-CY1 015. 08. 24		injing,		
r f cell Com Jate QAE-EF02-150824-CY1 015. 08. 24		injing,		
r f cell com date QAE-EF02-150824-CY1 015. 08. 24		injing,		
r f cell com date QAE-EF02-150824-CY1 015. 08. 24				
f cell com late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	18650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	18650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	18650M26			
f cell com late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
com Jate QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
com Jate QAE-EF02-150824-CY1 015. 08. 24	18650M26			
com Jate QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
com Jate QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
late QAE-EF02-150824-CY1 015. 08. 24	18650M26			
late QAE-EF02-150824-CY1 015. 08. 24	1.8650M26			
late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
late QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
QAE-EF02-150824-CY1 015. 08. 24	L8650M26			
QAE-EF02-150824-CY1 015. 08. 24	18650M26			
015. 08. 24	1865UIVIZ6			
rk with an"V"\		Date of test report 2015. 08. 24 DESCRIPTION OF CELL (Mark with an"X")		
Lithium ion cell X Lithium metal cell				
_				
Mass in gram (g): Lithium ion: Indicate watt-hour rating (Wh): 9.36				
.36				
of cell				
rc				
13				
II TS				
	N/A Pa	ass	Fail	
'	10			
		x		
		X		
		X		
l .		Х		
T		Χ		
		ILTS	N/A Pass X X X X X X X X X	

X

having a diameter of less than 18 mm

T7 – Overcharge

T8 - Forced Discharge

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?	Yes	
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %	YES		
---------------------------------	-----	--	--

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark		Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?		Χ	
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data loggers:			
17c) Confirmation that no dangerous amount of heat is emitted from the equipment		Χ	
17d)Confirmation that the equipment when transported by air fulfills the defined air		Х	
transport standards for electromagnetic radiation according to DO-160			

	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 Einzel Zelle / Batterie	LITHIUM - IONEN UN 3481 Zelle / Batterie in Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Place, Date	Signature	Company stamp and Signature
Frankfurt, 29.06.2020		Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. Fon +49(0)69/90 47 55 2-0 Fax -16