

## Sigma | Sigma SC

TE Internal #: 1623939-2

Sigma SC, High Frequency & RF Inductors, Radio Frequency, Through Hole - Solder, Ammo Packed, 10 x 4.2 mm, 10 Passive

Component Tolerance

View on TE.com >



Passive Components > Inductors > High Frequency & RF Inductors



Inductor Type: Radio Frequency

Termination Method to Printed Circuit Board: Through Hole - Solder

Packaging Method: Ammo Packed

Passive Component Dimensions: 10 x 4.2 mm

Passive Component Tolerance: 10 %

## **Features**

## **Product Type Features**

Inductor Type	Radio Frequency
Element Type	Wire Wound
Electrical Characteristics	
Self Resonant Frequency	.0022 GHz
Passive Component Tolerance	10 %
Inductance	1000 μΗ
Current Rating (Max)	76 mA
DC Resistance	40 Ω
Body Features	
Passive Component Lead Type	Axial-Leaded
Termination Features	

#### **Termination Features**

Termination Method to Printed Circuit Board	Through Hole - Solder	
---	-----------------------	--

# **Dimensions**

# **Usage Conditions**

Operating Temperature Range	-55 – 100 °C
operating verification of	

# **Packaging Features**



Packaging Method	Ammo Packed
Other	
Inductor Quality Factor	40

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**














# Also in the Series | Sigma SC









# Customers Also Bought



TE Part #2212282-1 FORGE, ASSY PIN, 5#0-0#4-0#8-0#12-0#22



TE Part #2212284-1 FORGE, ASSY SCKT, 5#0-0#4-0#8-0#12-0#22




TE Part #1879278-2 RP 2A 28K 0.1% 15PPM 1K RL

















## **Documents**

## **Product Drawings**

SC10-10-0549-10 1000UH AMMO 1000

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1623939-2\_BA.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1623939-2\_BA.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1623939-2\_BA.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

1309350\_PASSIVE\_COMPONENT

English

Axial Leaded Power Inductors - Type SC10, SC15, SC30 Series - Tyco Electronics Passives

English