

5786144-1 ✓ ACTIVE

AMPLIMITE

TE Internal #: 5786144-1

PCB D-Sub Connectors, Receptacle, Board-to-Board, 15 Position, 2.74mm [.108in] Centerline, 2 Row, Row-to-Row Spacing 2.84 mm [.112 in]

[View on TE.com >](#)



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors >

D-Sub Receptacle Assy: Vertical, Action Pin, Shell Size 2, 2.74mm



Connector & Housing Type: **Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **15**

Centerline (Pitch): **2.74 mm [.108 in]**

Number of Rows: **2**

[All D-Sub Receptacle Assy: Vertical, Action Pin, Shell Size 2, 2.74mm \(8\)](#)

## Features

### Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Grounding Indents                 | Without               |
| Grounding Straps                  | Without               |
| Shell Type                        | Front Metal Shell     |
| Connector & Housing Type          | Receptacle            |
| Connector System                  | Board-to-Board        |
| D-Sub Shell Size                  | 2                     |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| Product Type                      | Connector             |

### Configuration Features

|                       |          |
|-----------------------|----------|
| Number of Positions   | 15       |
| Number of Rows        | 2        |
| PCB Mount Orientation | Vertical |
| Preloaded             | Yes      |

### Body Features

|         |    |
|---------|----|
| Plastic | No |
|---------|----|



|                           |                 |
|---------------------------|-----------------|
| Female Screwlock Material | Brass           |
| Connector Profile         | Standard        |
| Shell Material            | Carbon Steel    |
| Shell Plating Material    | Tin over Copper |

#### Contact Features

|   |                          |
|---|--------------------------|
| Contact Mating Area Plating Material          | Gold                     |
| Contact Underplating Material                 | Nickel, Palladium Nickel |
| PCB Contact Termination Area Plating Material | Tin                      |
| Contact Base Material                         | Copper Alloy             |
|   | 30 µin                   |

#### Termination Features

|   |                          |
|---|--------------------------|
| Grounding Clips                             | Without                  |
| Termination Method to Printed Circuit Board | Through Hole - Press-Fit |
| Termination Post Length                     | 5.8 mm[.228 in]          |

#### Mechanical Attachment

|                          |                                      |
|--------------------------|--------------------------------------|
| Panel Mount Feature      | Without                              |
| PCB Mount Retention      | With                                 |
| PCB Mount Retention Type | Action/Compliant Tail, Mounting Hole |
| Mating Retention         | With                                 |
| Mating Retention Type    | Female Screwlocks, Fixed             |
| Connector Mounting Type  | Board Mount                          |
| Mounting Hole Diameter   | 3.05 mm[.12 in]                      |

#### Housing Features

|                    |                        |
|--------------------|------------------------|
| Centerline (Pitch) | 2.74 mm[.108 in]       |
| Housing Material   | Nylon GF, Polyester GF |
| Housing Color      | Black                  |

#### Dimensions

|                             |                                    |
|-----------------------------|------------------------------------|
| Row-to-Row Spacing          | 2.84 mm[.112 in]                   |
| PCB Thickness (Recommended) | 1.57 mm, 2.36 mm[.062 in][.093 in] |

#### Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|

#### Operation/Application



|                     |        |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

### Industry Standards

|                        |          |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

### Packaging Features

|                    |      |
|--------------------|------|
| Packaging Method   | Tray |
| Packaging Quantity | 104  |

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |  |
|---|--|
| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions  |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2021 (211)<br>Candidate List Declared Against: JAN 2021 (211)<br>SVHC > Threshold:<br>Pb (3.7% in Component Part)<br><b>Article Safe Usage Statements:</b><br>Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.   |
| Solder Process Capability                     | Not applicable for solder process capability   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # CAT-AM7-H3  
IDC D-Sub: Plug Assembly, Low Profile, Signal, 2.77 mm



TE Part # CAT-AM7-248H3  
IDC D-Sub: Plug Assembly, Wire to Wire, Signal, 2.77 mm



TE Part # CAT-AM7-248H7  
IDC D-Sub: Plug Assembly, Wire to Wire, Signal, 2.74 mm



TE Part # CAT-AM7-248H4  
IDC D-Sub: Connector Kit, Plug, Wire to Wire, Signal, 2.77 mm



TE Part # 206509-1  
SIZE 20 KEYING PLUG

### Customers Also Bought



TE Part #2-647123-8  
08P MTA156 SHRD HDR ASSY SQ SN



TE Part #1622603-1  
LR1L 5% R47



TE Part #148452-5  
160 ENH EURO LONG REC 6MM ASSY



TE Part #2-1761679-9  
IDC LOW PRO HDR 26P VERT BLUE



TE Part #1879350-4  
RR01 5% R30 AMMO



TE Part #2-1623703-0  
CPG0603 10K 1% 50PPM



TE Part #T4041017041-000  
M8 Panel Mount PCB



TE Part #203966-1  
CORNER GUIDE SKT,M SERIES



TE Part #104078-7  
80 SYSTEM 50 RCPT ASSY DRST



TE Part #1571550-6  
DIP Socket: Standard, Screw Machine, Closed, Tin

### Documents



### Product Drawings

#### 15 RCPT ACT PIN/MS SCRLK

English

---

### CAD Files

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_5786144-1\\_B.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_5786144-1\\_B.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_5786144-1\\_B.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

### Product Specifications

#### Application Specification

English

---

### Agency Approvals

#### UL Report

English