



Mini-SAS

TE Internal #: 1888019-6
Mini-SAS, Mini-SAS, Receptacle, Cable-to-Board, 36 Position, 2
Rows, 1 Ports, Right Angle, Surface Mount, .8mm [.031in] Centerline
[View on TE.com >](#)

Connectors > PCB Connectors > SAS & MiniSAS > Mini-SAS Shielded Receptacle Assemblies



SAS Connector Type: **Mini-SAS**
Connector & Housing Type: **Receptacle**
Connector System: **Cable-to-Board**
Number of Positions: **36**
Number of Rows: **2**

[All Mini-SAS Shielded Receptacle Assemblies \(19\)](#)

Features

Product Type Features

Shell	With
SAS Connector Type	Mini-SAS
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Key Type	2
Stackable	No
Number of Positions	36
Number of Rows	2
Number of Ports	1
PCB Mount Orientation	Right Angle



Contact Features

	30 µin
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	.5 A

Termination Features

Termination Post & Tail Length	2.8 mm[.11 in]
Termination Method to Printed Circuit Board	Surface Mount

Mechanical Attachment

PCB Mount Retention	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	.8 mm[.031 in]
--------------------	----------------

Usage Conditions

High Temperature Housing	Yes
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Packaging Features

Packaging Quantity	125
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-M6907-C76264
Mini-SAS Shielded Receptacle Assemblies

Also in the Series | Mini-SAS

SAS & MiniSAS(29)


Customers Also Bought

TE Part #1393793-2
Signal Relays: PCB mount, 3 amp

TE Part #1734839-8
0.5mm FPC Connectors

TE Part #1775485-2
Battery Holder, 3.6mm, BLU, low profile

TE Part #1586040-2
2P VAL-U-LOK VRT HDR W/P V0




TE Part #1-794074-1
14P MINI UMNL HDR W/O DH AU LF




TE Part #1-1734035-2
MINI USB, TYPE B, R/A, SMT



TE Part #1393117-8
KUP-1D55-24=KU



TE Part #1375799-1
ASSY, 120 POS PC104 PLUS



TE Part #1586042-2
2P VAL-U-LOK R/A HDR V0



TE Part #794075-1
16P MINI UMNL HDR W/O DH SN

Documents

Product Drawings

Shielded Right Angle Receptacl

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1888019-6_A1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1888019-6_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1888019-6_A1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

EVERCLEAR Mini Multi-Lane High Speed Interconnects Datasheet 1773447-2

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_1888019-6_030320172241_dmtec

1888019-6

Mini-SAS, Mini-SAS, Receptacle, Cable-to-Board, 36 Position, 2 Rows, 1 Ports, Right Angle, Surface Mount, .8mm [.031in] Centerline



English

[MD_1888019-6_030320172241_dmtec](#)

English