

LUMAWISE | LUMAWISE Endurance S

TE Internal #: 2329013-2

LUMAWISE Endurance S, Zhaga Book 18 Street Lighting

Connectors, Connector, Gray Housing Color, Product Height 39.25

mm, Keyed / Not Vented, Zhaga

View on TE.com >



Connectors > Lighting Connectors > Street Lighting Controls > Zhaga Book 18 Street Lighting Connectors > LUMAWISE Endurance S Domes











Lighting Product Type: Connector

Housing Color: Gray

Product Height: 39.25 mm

Lighting Connector Features Included: Keyed, Not Vented

Agency/Standard: Zhaga

All LUMAWISE Endurance S Domes (13)

Features

Product Type Features

Lighting Product Type	Connector
Sealable	Yes

Configuration Features

Lighting Connector Features Included	Keyed, Not Vented
Number of Positions	1

Housing Features

Housing Color	Gray	
---------------	------	--

Dimensions

Product Diameter	40 mm
Product Height	39.25 mm

Usage Conditions

	,	
IP Water Sealing Level	6	



IP Dust Sealing Level	6
Operating Temperature Range	-40 – 90 °C
Industry Standards	
Agency/Standard	Zhaga

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | LUMAWISE Endurance S





Customers Also Bought


















Documents

Product Drawings

LUMAWISE 40MM DIA DOME SMOKE GRAY TALL

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_2329013-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2329013-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2329013-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

LUMAWISE ENDURANCE Connector System

English

Lumawise Endurance S Modules

English

LUMAWISE STREET LIGHT DIMMING AND CONTROL QUICK REFERENCE GUIDE

English

Product Specifications

Application Specification

English

Agency Approvals

LUMAWISE Endurance S CB Certificate

English

LUMAWISE Endurance S CB Test Report

English