



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **62**

Centerline (Pitch): **5 mm [.197 in]**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Columns	5
Number of Loaded Positions	62
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	62
Number of Rows	5

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Contact Layout	Matrix
PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Mating Pin Diameter	1.75 mm[.069 in]



Contact Underplating Material Thickness	1.27 µm[50 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Finish	Bright
Contact Mating Area Plating Material Thickness	.76 µm[29.92 µin]
Contact Type	Receptacle
Contact Current Rating (Max)	7.5 A

Termination Features

Rectangular Termination Post & Tail Thickness	.32 mm[.013 in]
Rectangular Termination Post & Tail Width	.03 mm[.64 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Screw Mount
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	5 mm[.197 in]
Housing Color	Black
Housing Material	Polyester

Dimensions

Connector Length	98.3 mm[3.87 in]
Connector Height	39.34 mm[1.549 in]
Connector Width	40.18 mm[1.582 in]
Row-to-Row Spacing	5 mm[.197 in]

Usage Conditions

Operating Temperature Range	-55 – 130 °C[-67 – 266 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------



Industry Standards

UL Flammability Rating	UL 94V-0
Agency/Standard	CSA, UL
UL Rating	Recognized
VDE Tested	Yes

Packaging Features

Packaging Quantity	5
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Also in the Series | AMP Metrimate



Insertion & Extraction Tools(1)



Rectangular Boots & Strain Relief(9)



Rectangular Connector Hardware(4)



Rectangular Connector Housings(35)



Rectangular Connector Keying Plugs(1)



Rectangular Contact Inserts(7)



Rectangular Power Connectors(2)



Standard Rectangular Connectors(5)



Wire-to-Board Headers & Receptacles (83)

Customers Also Bought



TE Part #175289-3
DYNAMIC 3000 CONTACT




TE Part #1-179555-6
DYNAMIC 3200 REC AND TAB HSG



TE Part #205738-3
D-Sub Receptacle Assembly: Vertical, Shell Size 3, 2.77mm



TE Part #208334-5
PLUG ASSY,62 POS,METRIMATE



TE Part #2-100716-1
CABLE TY 200X4,8NAT



TE Part #2-31161-1
DG R 22-16 COMM 22-18 MIL 10



TE Part #1-776163-1
AMPSEAL HEADERS



TE Part #F257523001
100G1141-0.50-F959CK0226



TE Part #1-2322122-1
HVP800 2P HEADER ASSY

Documents

Product Drawings

MMATE,RCPT,62P,PSTD LF

English

CAD Files

Customer View Model

ENG_CVM_211580-4_N.3d_igs.zip

English

Customer View Model

ENG_CVM_211580-4_N.3d_stp.zip

English

Customer View Model

ENG_CVM_211580-4_N.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

METRIMATE_PIN_SOCKET_CATALOG

English

Product Specifications

Application Specification

English

Application Specification

English

METRIMATE Self-Locking Connectors

Japanese

Application Specification

Japanese

Agency Approvals

CSA Certificate

English

211580-4

AMP Metrimate, PCB Mount Header, Vertical, Wire-to-Board, 62 Position, 5mm [.197in] Centerline, 5 Row, Gold, Black Housing Color, Fully Shrouded

