

Power Double Lock

TE Internal #: 5-177913-1

Power Double Lock, Rectangular Power Connectors, Housing, Cap,

Wire-to-Wire, 12 Position, 3.96mm [.156in] Centerline, Wire &

Cable, UL 94V-0

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > STD Temp Power Double Lock Cap











Rectangular Power Connector Type: Housing

Connector & Housing Type: Cap Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 3.96 mm [.156 in]

All STD Temp Power Double Lock Cap (33)

Features

Product Type Features

Rectangular Power Connector Type Housin	ng
Connector & Housing Type Cap	
Connector System Wire-to	o-Wire
Sealable	
Connector & Contact Terminates To Wire &	« Cable

Configuration Features

Number of Positions	12
Number of Power Positions	12
Number of Signal Positions	0
Number of Rows	3

Electrical Characteristics

Operating Voltage	300 VAC	



Contact Features

Contact Retention Within Housing	Without
Contact Type	Tab
Termination Features	

Termination Method to Wire & Cable	Crimp	

Mechanical Attachment

Connector Mounting Type	Panel Mount
Connector Mounting Type	Tarici Modifi

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Nylon 6/6

Dimensions

Row-to-Row Spacing 4.6 mm[.181 in]

Usage Conditions

Operating remperature kange -30 – 105 °C[-22 – 221 °F]	Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
--	-----------------------------	----------------------------

Operation/Application

Circuit Application Power	
---------------------------	--

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Method	Bag
Packaging Quantity	150

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211)



$D_{\alpha\alpha\alpha}$	n 0+	aantain	REACH	CV/LIC
Does	not	contain	KEACH	SVHU

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts










Also in the Series | Power Double Lock





Insertion & Extraction Tools(2)









Customers Also Bought





















Documents

Product Drawings

POWER DBL LOCK CAP HSG P/M 12P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-177913-1_AC.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_5-177913-1_AC.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-177913-1_AC.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

AMP POWER DOUBLELOCK CONNECTOR SERIES

English

Agency Approvals

UL Report

English