


TE Internal #: 448518-1
PCB Mount Receptacle, Vertical, Board-to-Board, 34 Position, 2.54 mm [.1in] Centerline, Gold, Printed Circuit Board, 3A Contact Current Rating (Max)

[View on TE.com >](#)



Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**
PCB Mount Orientation: **Vertical**
Connector System: **Board-to-Board**
Number of Positions: **34**
Centerline (Pitch): **2.54 mm [.1 in]**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Coax Positions	8
Number of Rows	2
Stackable	No
PCB Mount Orientation	Vertical
Number of Positions	34

Contact Features

Contact Layout	Staggered
	30 μin
Contact Shape & Form	Square
PCB Contact Termination Area Plating Material	Gold
Contact Base Material	Beryllium Copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]



Contact Type	Socket
Contact Current Rating (Max)	3 A

Termination Features

Terminations per Post	3 High
Square Termination Post & Tail Dimension	.64 mm[.025 in]
Termination Post & Tail Length	18.42 mm[.725 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Mounting Hole
Mating Alignment	With
Mating Alignment Type	Keyed
PCB Mount Retention	With
Connector Mounting Type	Panel Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Blue
Housing Material	Diallyl Phthalate

Dimensions

Connector Height	10.16 mm[.4 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Stack Height	15.24 mm[.6 in]
PCB Thickness (Recommended)	2.44 mm[.096 in]

Usage Conditions

Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1
Packaging Method	Package



Other

Comment	Accepts Micro-miniature Coax Contacts
---------	---------------------------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2019 (197) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Customers Also Bought

TE Part #532447-9
HDI PIN ASSY 3 ROW 180 POS

TE Part #2-211991-2
RECEPT ASSY,SZ 2,ARINC 600

TE Part #448464-1
LGH 1/2,RCPT,MOD,W/3/8-24 UNF

TE Part #1617131-8
JMSW-6XM = M39016/11-019M






TE Part #YDTS20W25-35ABV001
D38999: Square Flange, 25-35 insert




TE Part #1045422-1
SSMA R/A Cable Plug 1007 7985 00



TE Part #1058576-1
SCD,4526 5004 02,BMA



TE Part #1825533-2
7 MTE HDR SRST LATCH .100CL



TE Part #1888291-1
FPH-0421G=FLXPAC HDR P 04 ST LF



TE Part #1437564-7
TST11DGPC1D=TINY SEALED TOGGLE

Documents

Product Drawings

2 ROW BOX RECP 34 POS 100 C/L

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_448518-1_C_c-448518-1-c.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_448518-1_C_c-448518-1-c.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_448518-1_C_c-448518-1-c.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Products for Aerospace and Defense

English

Product Specifications

Application Specification

English