

Alcoswitch | Alcoswitch Gemini AE

TE Internal #: 1-1825143-7 Alcoswitch Gemini AE, Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), Sealed Toggle Switch, Copper, Gold, Process Sealed

View on TE.com >



Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): Double Pole - Double Throw

Sealed Toggle Switch: Yes

Contact Base Material: Copper

Switch Contact Plating Material: Gold

Process Sealed: Yes

Features

Product Type Features

Product Type	Switch
Sealed Toggle Switch	Yes
Toggle Style	Baton Long

Toggle Switch Type	Toggle
Toggle Actuation	Vertical
Configuration Features	
Configuration (Pole-Throw)	Double Pole - Double Throw
Operating Function	On Off On
Electrical Characteristics	
Dielectric Strength	1000 VAC
Insulation Resistance	1000 MΩ
Contact Resistance	10 mΩ
Toggle Switch Voltage Rating	20 V
Body Features	
Actuator Finish	Nickel
Toggle Switch Seal Type	Terminal Seal (Epoxy)
Bushing Style	Unthreaded
Contact Features	

1-1825143-7

Alcoswitch Gemini AE, Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), Sealed Toggle Switch, Copper, Gold, Process Sealed



Contact Base Material	Copper
Switch Contact Plating Material	Gold
Toggle Switch Contact Current Rating	.4 A
Termination Features	
Termination Type	Vertical Right Angle
Mechanical Attachment	
Toggle Switch Mounting Type	Through Hole
Housing Features	
Process Sealed	Yes
Dimensions	
Toggle Length	12.7 mm[.5 in]
Industry Standards	
UL Rating	Contact Only
UL Flammability Rating	UL 94V-0
Other	
Comment	Process seal meets MIL-STD-202, Method 112 test cond. A & D at 85°C.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2018 (181) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C
Product Compliance Disclaimer This information is provided based on reasonable inquiry of our suppliers and based on the information they provided. This information is subject to change	•


1-1825143-7

Alcoswitch Gemini AE, Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), Sealed Toggle Switch, Copper, Gold, Process Sealed



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Alcoswitch Gemini AE



Toggle Switches(36)	


Customers Also Bought



1-1825143-7

Alcoswitch Gemini AE, Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), Sealed Toggle Switch, Copper, Gold, Process Sealed





Documents

Product Drawings AE203SD1AV2B04

English

Datasheets & Catalog Pages SWITCHES_CORE_PROGRAM_CATALOG

English

GEMINI_SERIES_SWITCHES_QUICK_REF_GUIDE_2-1773458-5

English