

OZ-SS-124LM1,200

✓ ACTIVE

OEG | OEG Power PCB Relay OZ/OZT


TE Internal #: 2-1440002-9

OEG Power PCB Relay OZ/OZT, Power Relays, Standard,
Monostable, DC, 500 – 600mW Coil Power Rating Class, 540mW
Coil Power Rating DC

[View on TE.com >](#)



Relays, Contactors & Switches > Relays > Power Relays > STD SCHRACK RZF Power Relays



Power Relay Type: **Standard**
Coil Magnetic System: **Monostable, DC**
Coil Power Rating Class: **500 – 600 mW**
Coil Power Rating DC: **540 mW**
Coil Resistance: **1100 Ω**

[All STD SCHRACK RZF Power Relays \(80\)](#)

Features

Product Type Features

Power Relay Type	Standard
------------------	----------

Electrical Characteristics

Insulation Initial Dielectric Between Coil & Contact Class	4000 V
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	16 A
Contact Limiting Short-Time Current	16 A
Contact Limiting Continuous Current	16 A
Insulation Creepage Class	5.5 – 8 mm
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms
Insulation Initial Resistance	1000 MΩ
Insulation Creepage Between Contact & Coil	8 mm[.315 in]
Contact Limiting Breaking Current	16 A
Coil Magnetic System	Monostable, DC



Coil Power Rating Class	500 – 600 mW
Coil Power Rating DC	540 mW
Coil Resistance	1100 Ω
Coil Special Features	Sensitive Version, UL Coil Insulation Class A
Coil Voltage Rating	24 VDC
Contact Switching Load (Min)	100mA @ 5V
Contact Switching Voltage (Max)	24 VDC
Contact Voltage Rating	30 VDC

Body Features

Insulation Special Features	10000V Initial Surge Withstand Voltage between Contacts & Coil
Product Weight	13 g[.459 oz]

Contact Features

Contact Arrangement	1 Form A (NO)
Contact Current Class	10 – 20 A, 16 A
Contact Current Rating (Max)	16 A
Contact Material	AgSnO
Contact Number of Poles	1
Terminal Type	PCB-THT

Mechanical Attachment

Relay Mounting Type	Printed Circuit Board
---------------------	-----------------------

Dimensions

Length Class (Mechanical)	25 – 30 mm
Insulation Clearance Class	5 – 8 mm
Height Class (Mechanical)	20 – 25 mm
Insulation Clearance Between Contact & Coil	5.5 mm[.217 in]
Width Class (Mechanical)	12 – 16 mm
Product Width	12.8 mm[.504 in]
Product Length	29.21 mm[1.15 in]
Product Height	20.6 mm[.811 in]

Usage Conditions

Environmental Ambient Temperature Class	50 – 70 °C
---	------------



Environmental Ambient Temperature (Max)

70 °C[158 °F]

Packaging Features

Packaging Method	Box & Carton
------------------	--------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # CAT-OE4-OZ8
STD SCHRACK RZF Power Relays



TE Part # 1649399-6
OZ-SS-124L1,200

Also in the Series | OEG Power PCB Relay OZ/OZT



Customers Also Bought

TE Part #1-1827872-0
DYNAMIC 1100 HDR ASSY

TE Part #1-1423008-8
PCB Power Relay: 40 Amp, Monostable

TE Part #1217056-1
250 FASTON,PCB TAB,TPBR

TE Part #1-2176079-0
EP 3W 330R 5%

TE Part #1-1419126-8
STD OEG PCB PCFN Solar Power Relays

TE Part #9-1440003-3
PCFN SOLAR RELAY

TE Part #1-1623789-6
Wirewound Resistor: Vertical Mount

TE Part #1-1721260-1
OJ-SH-112LMH2

Documents

- CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1440002-9_H.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1440002-9_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1440002-9_H.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

- Datasheets & Catalog Pages

OZ_OZT Series Relay Data Sheet - English

English



Product Specifications

Definitions, Handling, Processing, Testing and Use of Relays

English

Product Specification

Japanese

Product Environmental Compliance

Product Compliance

English

Product Compliance

English