

TE Internal #: 2267077-2

Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), 1/4-40, Sealed Toggle Switch, Gold, Terminal Seal (Epoxy),

Baton Long

View on TE.com >



Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): Double Pole - Double Throw

Bushing Thread Size: 1/4-40
Sealed Toggle Switch: Yes

Switch Contact Plating Material: Gold

Process Sealed: No

Features

Product Type Features

Sealed Toggle SwitchYesToggle StyleBaton LongToggle Switch TypeToggleToggle ActuationVertical	Product Type	Switch
Toggle Switch Type Toggle	Sealed Toggle Switch	Yes
	Toggle Style	Baton Long
Toggle Actuation Vertical	Toggle Switch Type	Toggle
	Toggle Actuation	Vertical

Configuration Features

Configuration (Pole-Throw)	Double Pole - Double Throw
Operating Function	On On

Electrical Characteristics

Toggle Switch Voltage Rating	20 V	

Body Features

Color	Red
Bushing Thread Size	1/4-40
Toggle Switch Seal Type	Terminal Seal (Epoxy)
Bushing Style	Threaded

Contact Features

Switch Contact Plating Material	Gold
Toggle Switch Contact Current Rating	.4 A



Termination Features

Termination Type	Printed Circuit
Mechanical Attachment	
Toggle Switch Mounting Type	Through Hole
Housing Features	
Process Sealed	No
Dimensions	
Toggle Length	10.4 mm[.41 in]
Industry Standards	
UL Rating	Flame Rating Only
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts











Customers Also Bought





TE Part #1825910-6 FSM4JH=6MM TACT SWITCH, HIGH




















Documents

Product Drawings

TMD1T4B5M2RE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2267077-2_A_c-2267077-2-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2267077-2_A_c-2267077-2-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2267077-2_A_c-2267077-2-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Subminiature Switches

English