



Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): **Three Pole - Double Throw**

Bushing Thread Size: **1/4-40**

Sealed Toggle Switch: **Yes**

Contact Base Material: **Copper Alloy**

Switch Contact Plating Material: **Gold Flash over Silver**

## Features

### Product Type Features

Product Type	Switch
Sealed Toggle Switch	Yes
Toggle Style	Locking
Toggle Switch Type	Toggle
Toggle Actuation	Vertical

### Configuration Features

Configuration (Pole-Throw)	Three Pole - Double Throw
Operating Function	On None On

### Electrical Characteristics

Dielectric Strength	1500 VAC
Insulation Resistance	1000 MΩ
UL/CSA Current Rating (250V)	3 A
Contact Resistance	10 mΩ
Toggle Switch Voltage Rating	28 VDC

### Body Features

Actuator Finish	Chrome
Color	Green
Bushing Thread Size	1/4-40



Toggle Switch Seal Type	Terminal Seal (Insert Molded)
Bushing Style	Threaded

**Contact Features**

Contact Base Material	Copper Alloy
Switch Contact Plating Material	Gold Flash over Silver
Toggle Switch Contact Current Rating	6 A

**Termination Features**

Termination Type	Vertical, Wire Lugs
------------------	---------------------

**Mechanical Attachment**

Toggle Switch Mounting Type	Panel
-----------------------------	-------

**Housing Features**

Process Sealed	No
----------------	----

**Dimensions**

Toggle Length	16.51 mm[.65 in]
---------------	------------------

**Industry Standards**

UL Flammability Rating	UL 94V-0
------------------------	----------

**Other**

Comment	UL available when ordering - consult factory.
---------	---

**Product Compliance**

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (1.13% in component) <b>Article Safe Usage Statements:</b> Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # 3-1437559-7  
MTL206N=(MSTL) SW TOG LOCKING



TE Part # 3-1437559-4  
MTL106D=(MSTL) SWITCH TOG LOCK



TE Part # 3-1437559-9  
MTL206P=(MSTL) SW TOG LOCKING



TE Part # 3-1437559-5  
MTL106E=(MSTL) SW TOG LOCKING




TE Part # 4-1437559-4  
MTL406N=(MSTL) SW TOG LOCKING



TE Part # 4-1437559-3  
MTL306E=3PDT GREEN LOCKING TOG

### Also in the Series | Alcoswitch MTL



Toggle Switches(6)

### Customers Also Bought



## Documents

### Product Drawings

[MTL306D=\(MSTL\) SW TOG LOCKING](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_4-1437559-2\\_E.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_4-1437559-2\\_E.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_4-1437559-2\\_E.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages



[2-1773458-6\\_GREEN\\_SERIES\\_SWITCHES](#)

English