

TE Internal #: 7-1617805-1

Time Delay Relays, Fixed, 28VDC Time Delay Relay Input Voltage, 115VACA / 10A@28VDCA Time Delay Relay Contact Current

Rating, Delay on Release

View on TE.com >



Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Fixed

Time Delay Relay Input Voltage: 28 VDC

Time Delay Relay Contact Current Rating: 10A@28VDC A, 115VAC A

Mode of Operation: Delay on Release

Delay Time: 30 seconds

Features

Product Type Features

Enclosure Type He	Hermetic Sealed Metallic
Product Type Re	Relay
Relay Type Ti	ime Delay
Product Category El	Electromechanical Relays
Magnetic Blow-Out Device W	Vithout

Configuration Features

Status Indicator Type	None
Multiple Timing Ranges	Without

Electrical Characteristics

Actuating System	DC
Time Delay Relay Input Voltage	28 VDC

Contact Features

Contact Arrangement	2 Form C, DPDT, 2 C/O
Contact Base Material	Silver Cadmium Oxide
Type of Control	Fixed
Time Delay Relay Contact Current Rating	10A@28VDC A, 115VAC A
Delay Time	30 seconds

Termination Features



Termination Type	Solder Pin Terminal
Mechanical Attachment	
Time Delay Relay Mounting Type	Raised Vertical Flange Mount
Dimensions	
Dimensions (L x W x H) (Approximate)	25.79 x 25.79 x 25.4 mm[1.015 x 1.015 x 1 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C
Operation/Application	
Mode of Operation	Delay on Release
Other	
Repeatability (Max)	±10%

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Customers Also Bought













Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1617805-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1617805-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1617805-1_A.3d_stp.zip

Time Delay Relays, Fixed, 28VDC Time Delay Relay Input Voltage, 115VACA / 10A@28VDCA Time Delay Relay Contact Current Rating, Delay on Release



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

High_Performance_Relays_Section5

English